09/939225

```
Welcome to STN International
                 Web Page URLs for STN Seminar Schedule - N. America
NEWS 1
NEWS 2 Apr 08 "Ask CAS" for self-help around the clock
NEWS 3 Apr 09 BEILSTEIN: Reload and Implementation of a New Subject Area
NEWS 4 Apr 09 ZDB will be removed from STN
NEWS 5 Apr 19 US Patent Applications available in IFICDB, IFIPAT, and IFIUDB
NEWS 6 Apr 22 Records from IP.com available in CAPLUS, HCAPLUS, and ZCAPLUS
NEWS 7 Apr 22 BIOSIS Gene Names now available in TOXCENTER
NEWS 8 Apr 22 Federal Research in Progress (FEDRIP) now available
NEWS 9 Jun 03 New e-mail delivery for search results now available
NEWS 10 Jun 10 MEDLINE Reload
NEWS 11 Jun 10 PCTFULL has been reloaded
NEWS 12 Jul 02 FOREGE no longer contains STANDARDS file segment
NEWS 13 Jul 22 USAN to be reloaded July 28, 2002;
                 saved answer sets no longer valid
NEWS 14 Jul 29 Enhanced polymer searching in REGISTRY
NEWS 15 Jul 30 NETFIRST to be removed from STN
NEWS 16 Aug 08 CANCERLIT reload
NEWS 17 Aug 08 PHARMAMarketLetter(PHARMAML) - new on STN
NEWS 18 Aug 08 NTIS has been reloaded and enhanced
NEWS 19 Aug 19 Aquatic Toxicity Information Retrieval (AQUIRE)
                 now available on STN
NEWS 20 Aug 19 IFIPAT, IFICDB, and IFIUDB have been reloaded
NEWS 21 Aug 19 The MEDLINE file segment of TOXCENTER has been reloaded
NEWS 22 Aug 26 Sequence searching in REGISTRY enhanced
NEWS 23 Sep 03 JAPIO has been reloaded and enhanced
NEWS 24 Sep 16 Experimental properties added to the REGISTRY file
NEWS 25 Sep 16 Indexing added to some pre-1967 records in CA/CAPLUS
NEWS 26 Sep 16 CA Section Thesaurus available in CAPLUS and CA
NEWS 27 Oct 01 CASREACT Enriched with Reactions from 1907 to 1985
NEWS 28 Oct 21 EVENTLINE has been reloaded
NEWS 29 Oct 24 BEILSTEIN adds new search fields
NEWS 30 Oct 24 Nutraceuticals International (NUTRACEUT) now available on STN
NEWS 31 Oct 25 MEDLINE SDI run of October 8, 2002
NEWS 32 Nov 18 DKILIT has been renamed APOLLIT
NEWS 33 Nov 25 More calculated properties added to REGISTRY
NEWS EXPRESS October 14 CURRENT WINDOWS VERSION IS V6.01,
              CURRENT MACINTOSH VERSION IS V6.0a(ENG) AND V6.0Ja(JP),
              AND CURRENT DISCOVER FILE IS DATED 01 OCTOBER 2002
              STN Operating Hours Plus Help Desk Availability
NEWS HOURS
              General Internet Information
NEWS INTER
              Welcome Banner and News Items
NEWS LOGIN
              Direct Dial and Telecommunication Network Access to STN
NEWS PHONE
              CAS World Wide Web Site (general information)
NEWS WWW
```

Enter NEWS followed by the item number or name to see news on that specific topic.

All use of STN is subject to the provisions of the STN Customer agreement. Please note that this agreement limits use to scientific research. Use for software development or design or implementation of commercial gateways or other similar uses is prohibited and may result in loss of user privileges and other penalties.

* * * * * * * * * * * * * * * * STN Columbus * * * * * * * * * * * * * * * * * *

FILE 'HOME' ENTERED AT 17:37:08 ON 01 DEC 2002

=> file caplus
COST IN U.S. DOLLARS

SINCE FILE TOTAL
ENTRY SESSION
0.21 0.21

FULL ESTIMATED COST

FILE 'CAPLUS' ENTERED AT 17:37:39 ON 01 DEC 2002
USE IS SUBJECT TO THE TERMS OF YOUR STN CUSTOMER AGREEMENT.
PLEASE SEE "HELP USAGETERMS" FOR DETAILS.
COPYRIGHT (C) 2002 AMERICAN CHEMICAL SOCIETY (ACS)

Copyright of the articles to which records in this database refer is held by the publishers listed in the PUBLISHER (PB) field (available for records published or updated in Chemical Abstracts after December 26, 1996), unless otherwise indicated in the original publications. The CA Lexicon is the copyrighted intellectual property of the American Chemical Society and is provided to assist you in searching databases on STN. Any dissemination, distribution, copying, or storing of this information, without the prior written consent of CAS, is strictly prohibited.

FILE COVERS 1907 - 1 Dec 2002 VOL 137 ISS 23 FILE LAST UPDATED: 29 Nov 2002 (20021129/ED)

This file contains CAS Registry Numbers for easy and accurate substance identification.

CAS roles have been modified effective December 16, 2001. Please check your SDI profiles to see if they need to be revised. For information on CAS roles, enter HELP ROLES at an arrow prompt or use the CAS Roles thesaurus (/RL field) in this file.

=> s fatty acid

309984 FATTY

13 FATTIES

309987 FATTY

(FATTY OR FATTIES)

3489628 ACID

1337893 ACIDS

3953780 ACID

(ACID OR ACIDS)

L1 273225 FATTY ACID

(FATTY(W)ACID)

=> fat or oil

FAT IS NOT A RECOGNIZED COMMAND

The previous command name entered was not recognized by the system. For a list of commands available to you in the current file, enter "HELP COMMANDS" at an arrow prompt (=>).

=> s fat or oil

152363 FAT

83943 FATS

193076 FAT

(FAT OR FATS)

638125 OIL

276291 OILS

```
(OIL OR OILS)
        837432 FAT OR OIL
L2
=> 1 and 2
1 IS NOT A RECOGNIZED COMMAND
The previous command name entered was not recognized by the system.
For a list of commands available to you in the current file, enter
"HELP COMMANDS" at an arrow prompt (=>).
=> s 1 and 2
       7358197 1
       7534268 2
       4639081 1 AND 2
L3
=> del 13 y
\Rightarrow s 11 and 12
         92558 L1 AND L2
=> s 13 and (fuel oe coal)
        283034 FUEL
        134381 FUELS
        328783 FUEL
                  (FUEL OR FUELS)
         18691 OE
          1418 OES
         20099 OE
                  (OE OR OES)
        196235 COAL
         34046 COALS
        199574 COAL
                  (COAL OR COALS)
             O FUEL OE COAL
                  (FUEL (W) OE (W) COAL)
             0 L3 AND (FUEL OE COAL)
L4
=> s 13 and (fuel or coal)
        283034 FUEL
        134381 FUELS
        328783 FUEL
                  (FUEL OR FUELS)
        196235 COAL
         34046 COALS
        199574 COAL
                  (COAL OR COALS)
          2364 L3 AND (FUEL OR COAL)
L5
=> s 15 and (burn? or ignit? or energy)
        148095 BURN?
         60602 IGNIT?
        1587150 ENERGY
        286579 ENERGIES
        1684689 ENERGY
                  (ENERGY OR ENERGIES)
            342 L5 AND (BURN? OR IGNIT? OR ENERGY)
L6
=> s 16 and emission
         394304 EMISSION
         70881 EMISSIONS
         427663 EMISSION
```

(EMISSION OR EMISSIONS)

716050 OIL

L7 56 L6 AND EMISSION

=> d 17 1-56 all

L7 ANSWER 1 OF 56 CAPLUS COPYRIGHT 2002 ACS

Full Text

AN 2002:810252 CAPLUS

DN 137:341362

- TI Purification of regenerative **fuel** exhaust gases from diesel motors with oxy- and SCR catalysts
- AU Lachenmaier-Kolch, Jurgen

CS Gunzburg, Germany

- SO Fortschritt-Berichte VDI, Reihe 15: Umwelttechnik (2002), 241, i-ix,1-111 CODEN: FRUMFB; ISSN: 0178-9589
- PB VDI Verlag GmbH
- DT Journal
- LA German
- CC 59-3 (Air Pollution and Industrial Hygiene)
 Section cross-reference(s): 52, 67
- The chair Energy and Environmental Technologies of the Food Industry AΒ operates a small co-generation plant with the ability of analyzing the std. emission components. Results of an investigation on 3 different fuels (diesel fuel, food recycling oil Me ester (AME) and rapeseed oil) with oxidn.- and SCR-catalysts will be presented. Also a high temp. reactor was designed and instrumented for analyzing SCR-catalysts with a chem.-ionization-mass-spectrometer. The aim is an optimization of oxidn.- and SCR-catalysts for best NOx-redn. rates addnl. with the possibility of using renewable fuels. The optimal conversion rate for NOx with the SCR-catalyst is a temp. range 200-350°. The best Alpha-value is 90-110%. The CO-, HC- and particle emissions of rapeseed oil and AME is lower then the emissions of diesel fuel. The emissions of NOx for rapeseed oil rise up to 20% in comparison to diesel fuel. The redn. rate of the emissions of NOx rise (with the help of urea injection) up to 54, 61, and 67% for rapeseed oil, AME, and diesel fuel, resp. The CO-emissions are reduced to 89% with the use of the oxidn. catalysts, with urea injection 1-3% more redn. The HC-emissions are reduced to 43% with the use of the oxidn. catalysts, with the injection of urea 1-8% more redn. Ammonia is detected after urea injection up to 7 mg/m3 for all fuels. N2O emissions are detected after the injection of urea. The use of diesel fuel causes the doubled value of particle emissions in comparison to the renewable fuels.
- ST regenerative diesel fuel exhaust treatment catalytic
- IT Diesel fuel substitutes

(biodiesel; emission redn. of regenerative fuel powered co-generation plants with oxy- and SCR catalysts)

IT Air pollution

(control; emission redn. of regenerative fuel powered co-generation plants with oxy- and SCR catalysts)

IT Exhaust gases (engine)

(diesel; emission redn. of regenerative fuel powered co-generation plants with oxy- and SCR catalysts)

IT Diesel fuel

Exhaust gas catalytic converters

Exhaust gases (engine)

Exhaust particles (engine)

(emission redn. of regenerative fuel powered co-generation plants with oxy- and SCR catalysts)

IT Hydrocarbons, processes

RL: REM (Removal or disposal); PROC (Process)

(emission redn. of regenerative fuel powered

co-generation plants with oxy- and SCR catalysts)

IT Fats and Glyceridic oils, uses

- STN Columbus RL: TEM (Technical or engineered material use); USES (Uses) (emission redn. of regenerative fuel powered co-generation plants with oxy- and SCR catalysts) Fatty acids, uses RL: TEM (Technical or engineered material use); USES (Uses) (emission redn. of regenerative fuel powered co-generation plants with oxy- and SCR catalysts) RL: TEM (Technical or engineered material use); USES (Uses) (emission redn. of regenerative fuel powered co-generation plants with oxy- and SCR catalysts) 630-08-0, Carbon monoxide, processes 7664-41-7, Ammonia, processes 10102-44-0, Nitrogen oxide (NO2), processes 11104-93-1, Nitrogen oxide, processes RL: REM (Removal or disposal); PROC (Process) (emission redn. of regenerative fuel powered co-generation plants with oxy- and SCR catalysts) THERE ARE 88 CITED REFERENCES AVAILABLE FOR THIS RECORD RE.CNT 88 RE (1) Ahlborn Mess- und Regelungstechnik; Handbuch Almemo 1996, V5590-2 (2) Anon; Prufung von Mineralogen und anderen brennbaren Flussigkeiten, Bestimmung des Phosphorgehaltes ASTM D 3231-94 (3) Anon; VDI-Handbuch Reinhaltung der Luff 1990, V6(VD1-Richtlinie 3476) (4) Anon; http://www.biodiesel.de 2001 (5) Anon; http://www.ufop.de/ 1999 (6) Anon; http://www.umweltbundesamt.de 1999 (7) Bayer Diagnostics; Handbuch COMPUR FID 1990
- (8) Bayerische Landesanstalt fur Landtechnik Weihenstephan; Protokoll des 3. LTV-Arbeitskreises "Dezentrale Pflanzenolgewinnung" 1996
- (9) Bayerische Landesanstalt fur Landtechnik Weihenstephan; Protokoll des 5. LTV-Arbeitskreises "Dezentrale Pflanzenolgewinnung" 1999
- (10) Bayerische Landesanstalt fur Landtechnik Weihenstephan; Qualitatsstandard fur Rapsol als Kraftstoff (RK-Qualitatsstandard) 2000
- (11) Belting, T; Blockheizkraftwerke: Ein Informationspaket 1993
- (12) Bettoni, F; Dissertation, Eidgenossische Technische Hochschule Zurich 1997
- (13) Birkner, C; Dissertation, Universitat Kaiserslautern, Fachbereich Maschinenwesen 1995
- (14) Bock, J; Thermo-okonomische Analyse der Kraft-Warme-Kopplung mit Klein-Blockheizkraftwerken fur die dezentrale Warmeversorgung 1991
- (15) Breton, H; Staub-Reinhaltung der Luft 1992, V52, P195 CAPLUS
- (16) Bronstein, I; Taschenbuch der Mathematik 1989
- (17) Buchholz, F; Dissertation, Universitat Karlsruhe 2000
- (18) Budzikiewicz, H; Massenspektrometrie. 2. Aufl 1980
- (19) Claus, B; Beitrag zur Verbrennung von Rapsol und Rapsolmethylester in direkteinspritzenden Dieselmotoren 1994
- (20) Connemann, J; Workshop "Biodiesel" der Forschungsvereinigung Verbrennungskraftmaschinen (FVV) 1997
- (21) Davids, P; Die TA Luft '86 Technischer Kommentar 1986
- (22) Dobiasch, A; Diplomarbeit, TU Munchen-Weihenstephan, Lehrstuhl for Energie- und Umwelttechnik der Lebensmittelindustrie 1996
- (23) Dobiasch, A; Dissertation, TU Munchen-Weihenstephan, Lehrstuhl for Energie- und Umwelttechnik der Lebensmittelindustrie 2000
- (24) Dobiasch, A; KongreBzeitschrift zur Fachtagung im Fortbildungszentrum des Bayerischen Landesamtes fur Umweltschutz "Energetische Nutzung von Pflanzenolen" 1998
- (25) Dobiasch, A; KongreBzeitschrift zur Fachtagung im Fortbildungszentrum des Bayerischen Landesamtes fur Umweltschutz "Energetische Nutzung von Pflanzenolen" 1998
- (26) Dobiasch, A; Proceedings Fisita 1998 World Automotive Congress 1998,
- (27) Dobiasch, A; Proceedings of Fisita 1998 World Automotive Congress 1998,

- (28) Dobiasch, A; VDI-Berichte 1999, 1457, P359
- (29) Dusterdiek, T; Katalytische Stickoxidminderung im Abgas von Dieselmotoren 1997
- (30) Espig, G; VDI-Tagung Pflanzenole als Kraftstoffe fur Fahrzeugmotoren und Blockheizkraftwerke 1994, P41 CAPLUS
- (31) Fischer Rosemount GmbH Co; Handbuch Binos 1992, V1000(Sachnummer: 90000301)
- (32) Fischer Rosemount GmbH Co; Handbuch Oxynos 1991, V100
- (33) Forster, U; Umweltschutztechnik 1993
- (34) Fritz, U; Dissertation, TU Munchen-Weihenstephan, Lehrstuhl for Energieund Umwelttechnik der Lebensmittelindustrie 1994
- (35) Gailfuss, M; CO2-Minderungspotentiale durch Ausbau der Blockheizkraftwerke in Deutschland 1998
- (36) Gesellschaff fur dezentrale Energieversorgung eV; Pflanzenol-Technik (Pflanzenol - Kraftstoff aus der Sonne) 1992, V1
- (37) Gifhorn, A; Dissertation, TU Munchen-Weihenstephan, Lehrstuhl for Energieund Umwelttechnik der Lebensmittelindustrie 1997
- (38) Hartmann, H; Energie aus Biomasse 1996, Landtechnik-Bericht Heft 18
- (39) Henning, R; Produktion und Nutzung von Pflanzenol als Kraftstoff im Sahel, am Beispiel von Mali 1992
- (40) Herrmann, S; Dissertation, Schweizerische Ingenieurschule fur Landwirtschaft 1995
- (41) Jurisch, C; Pflanzenolgeeignete Dieselmotoren deutscher Hersteller 1994, VDI Berichte Nr 1126
- (42) Jurisch, C; SchluBbericht, TU Munchen-Weihenstephan, Lehrstuhl fur Energie- und Umwelttechnik der Lebensmittelindustrie 1995
- (43) Kind, W; Beitrag zur NOx-Verminderung im Abgas von Dieselmotoren durch selective katalytische Reduktion mit Harnstoff 1997
- (44) Klingenberg, H; AbgasmeBtechnik 1995
- (45) Kuchling, H; Taschenbuch der Physik 1989
- (46) Kunz, D; Dissertation, Universitat Kaiserslautern 1996
- (47) Lachenmaier, J; Bayern Regenerativ 2000, Fachkongress "Kraftstoffe aus Pflanzenol 2000
- (48) Lachenmaier, J; Diplomarbeit, TU Munchen-Weihenstephan, Lehrstuhl fur Energie- und Umwelttechnik der Lebensmittelindustrie 1998
- (49) Lachenmaier, J; Fachtagung "Regenerative Energien in Ungam und in Deutschland 2000, P101
- (50) Lachenmaier, J; Fifth International Conference on Technologies and Combustion for a Clean Environment, Proceedings 1999
- (51) Lachenmaier, J; Fifth International Congress on Catalysis and Automotive Pollution Control, Proceedings 2000
- (52) Lachenmaier, J; OTTI-Anwenderforum Energetische Nutzung von Pflanzenol und Biogas, Kloster Banz 1999, P193
- (53) Lachenmaier, J; Sixth International Conference on Technologies and Combustion for a Clean Environment, Proceedings 2001, P459
- (54) Lachenmaier, J; Tomul 1998, V43(57), P85
- (55) Lachenmaier, J; VDI-Fachtagung "Fortschrittliche Energie-wandlung und -anwendung 2001, VDI-Berichte 1594, P365
- (56) Max-Plank-Institut fur Meteorologie; http://www.mpimet.mpg.de 2001
- (57) May, H; AbschluBbericht zum Forschungsvorhaben, "Untersuchungen zum vergleichenden Einsatz von Dieselkraftstoff und Rapsolmethylester an verschiedenen Dieselmotoren" 1994
- (58) Meyer-Pittroff, R; Vorlesungsskriptum Kessel- Kraft- und Kalteanlagen 1998
- (59) Mortimer, C; Chemie: das Basiswissen der Chemie 1996
- (60) Muller Weigert GmbH; Handbuch fur das WirkleistungsmeBgerat 1997, Sachnummer: 2786688812
- (61) Negrea, V; Concerning the evaluation meanings of the environment pollution level for the diesel engines working with conventional and non-conventional fuels 1998
- (62) Neumann, C; Suddeutsche Zeitung 1999, PL12
- (63) Neumann, C; Suddeutsche Zeitung 1999, PL12
- (64) Perkin Elmer Bodenseewerk; Handbuch MCS 1994, V100(091188, SN213)

- (65) Pfyl, J; Abgasentgiftungssysteme in Theorie und Praxis 1987
- (66) Pischinger, F; Verbrennungsmotoren (Vorlesungsdruck) 1994
- (67) Precht, M; Bio-Statistik 1987
- (68) Proll, M; Dissertation, TU Munchen-Weihenstephan, Lehrstuhl fur Energieund Umwelttechnik der Lebensmittelindustrie 1991
- (69) Rabl, H; Dissertation, TU Munchen-Weihenstephan, Lehrstuhl fur Energieund Umwelttechnik der Lebensmittelindustrie 1999
- (70) Reinhardt, G; Energie- und CO2-Bilanzierung Nachwachsender Rohstoffe: Theorethische Grundlagen und Fallstudie Raps 1993
- (71) Reiser, W; Ermittlung von motor- und verbrennungstechnischen Kenndaten an einem Dieselmotor mit Direkteinspritzung bei Betrieb mit unterschiedlich aufbereitetem Rapsol 1997
- (72) Richter, F; Abschlußbericht im Auftrag des BMFT 1991
- (73) Rompp, H; Rompp Chemie Lexikon 1995
- (74) Schafer, F; Schadstoffreduzierung und Kraftstoffverbrauch von PKW-Verbrennungsmotoren 1993
- (75) Schindler, V; Kraftstoffe fur morgen: Eine Analyse von Zusammenhangen und Handlungsoptionen 1997
- (76) Schuster, W; Olpflanzen in Europa 1992
- (77) VSE GmbH; Datenblatt VSE Axialturbinen-DurchfluBsensor 1997
- (78) Villinger, J; Personliche Mitteilungen
- (79) Villinger, J; SAE Technical Paper Series 1993, V932017
- (80) Warnatz, J; Verbrennung: Physikalisch-Chemische Grundlagen, Modellierung, und Simulation, Experimente, Schadstoffentstehung 1997
- (81) Wehinger, C; Dissertation, TU Munchen-Weihenstephan, Lehrstuhl fur Energie- und Umwelttechnik der Lebensmittelindustrie 1994
- (82) Weidmann, K; Automobiltechnische Zeitschrift 1995, V97(5)
- (83) Weisweiler, W; Technischer Bericht, Projekt "GD-Kat" 1999
- (84) Widmann, B; Dissertation an der Technischen Universitat Munchen 1994
- (85) Widmann, B; Fachgesprach: Emissionen von Pflanzenolkraftstoffen und ihre Umweltwirkungen 1994
- (86) Wunsch, R; Dissertation, Universitat Karlsruhe 1996
- (87) Zelkowski, J; Kohleverbrennung, VGB-Kraftwerkstechnik 1986
- (88) Zell, B; Zweites OTTI-Anwenderforum Energetische Nutzung von Pflanzenol und Biogas, Kloster Banz 2000, P69
- L7 ANSWER 2 OF 56 CAPLUS COPYRIGHT 2002 ACS

Full Text

- AN 2002:754505 CAPLUS
- DN 137:281625
- TI Plant extracts-jojoba oil-based additives for liquid fuels for reduced pollutant emissions
- IN Jordan, Frederick L.
- PA Oryxe Energy International, Inc., USA
- SO PCT Int. Appl., 173 pp. CODEN: PIXXD2
- DT Patent
- LA English
- IC ICM C10L010-02
- CC 51-7 (Fossil Fuels, Derivatives, and Related Products)

FAN.CNT 1

| | PATENT NO. | | | | KIND | | DATE | | APPLICATION NO. D | | | | | | DATE | | | |
|----|---------------|-----|-----|-----|------|----------|------|-------------------------|-------------------|-----|-----|-----|-----|-----|------|-----|-----|-----|
| | | | | | | | | | | | | | | | | | | |
| PI | WO 2002077131 | | | A2 | | 20021003 | | WO 2002-US6137 20020226 | | | | | | | | | | |
| | | W: | ΑE, | AG, | AL, | AM, | ΑT, | AU, | ΑZ, | BA, | BB, | BG, | BR, | BY, | BZ, | CA, | CH, | CN, |
| | | | CO, | CR, | CU, | CZ, | CZ, | DE, | DE, | DK, | DK, | DM, | DZ, | EC, | EE, | EE, | ES, | FI, |
| | | | FI, | GB, | GD, | GE, | GH, | GM, | HR, | HU, | ID, | IL, | IN, | IS, | JP, | KE, | KG, | KP, |
| | | | KR, | KZ, | LC, | LK, | LR, | LS, | LT, | LU, | LV, | ΜA, | MD, | MG, | MK, | MN, | MW, | MX, |
| | | | MZ, | NO, | NZ, | OM, | PH, | PL, | PT, | RO, | RU, | SD, | SE, | SG, | SI, | SK, | SK, | SL, |
| | | | TJ, | TM, | TN, | TR, | TT, | TZ, | UA, | UG, | US, | UΖ, | VN, | YU, | ZA, | ZM, | ZW, | AM, |
| | | | | BY, | | | | | | | | | | | | | | |
| | | RW: | GH, | GM, | KE, | LS, | MW, | MZ, | SD, | SL, | SZ, | TZ, | UG, | ZM, | ZW, | AΤ, | BE, | CH, |

```
CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR,
             BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG
PRAI US 2001-278011P
                      P
                            20010322
    A fuel additive suitable for any liq. fuel, coal, or other
    hydrocarbon fuel consists of an antioxidant (preferably
    \beta-carotene), a thermal stabilizer (preferably jojoba oil or a
    C20-22-monounsatd. fatty acid ester), and a plant oil ext. other
     than alfalfa oil (preferably vetch ext., barley ext., and an ext. from a
    plant of the Leguminosae family). In addn., the fuel additive can
     contain an oxygenate, esp. chosen from methanol, ethanol, Me tert-Bu
     ether, Et tert-Bu ether, and tert-amyl Me ether. Addnl. additives that
    may be present include octane improvers, cetane improvers, detergents,
     demulsifiers, corrosion inhibitors, metal deactivators, ignition
     accelerators, dispersants, antiknock additives, antioxidants,
     demulsifiers, etc. The additives can reduce emissions and can improve
     fuel economy and engine cleanliness.
     fuel additive plant ext jojoba oil beta carotene; gasoline diesel
ST
     fuel additive plant ext; coal fuel oil additive plant ext;
     Leguminosae barley vetch ext liq fuel additive
     Fatty acids, uses
     RL: MOA (Modifier or additive use); USES (Uses)
        (C20-22-monounsatd., esters, thermal stabilizers; plant exts.-jojoba
        oil-based additives for liq. fuels for reduced
        pollutant emissions)
     Jet aircraft fuel
TΤ
        (additives; plant exts.-jojoba oil-based additives for liq.
        fuels for reduced pollutant emissions)
     Coal, miscellaneous
ΙT
     RL: MSC (Miscellaneous)
        (combustion additives for; plant exts.-jojoba oil-based
        additives for liq. fuels for reduced pollutant
     Barley
     Embryophyta
     Fabaceae
     Vicia
        (exts.; plant exts.-jojoba oil-based additives for liq.
        fuels for reduced pollutant emissions)
     Chlorophylls, uses
тт
     RL: MOA (Modifier or additive use); USES (Uses)
        (exts.; plant exts.-jojoba oil-based additives for liq.
        fuels for reduced pollutant emissions)
     Lubricating oil additives
        (for two-cycle engines; plant exts.-jojoba oil-based
        additives for liq. fuels for reduced pollutant
        emissions)
IT
     Fuels
        (liq., additives; plant exts.-jojoba oil-based additives for
        liq. fuels for reduced pollutant emissions)
     Antioxidants
IT
     Diesel fuel additives
       Fuel oil additives
     Gasoline additives
     Heat stabilizers
         (plant exts.-jojoba oil-based additives for liq.
         fuels for reduced pollutant emissions)
     RL: MOA (Modifier or additive use); USES (Uses)
         (thermal stabilizers; plant exts.-jojoba oil-based additives
         for liq. fuels for reduced pollutant emissions)
     7235-40-7, \beta-Carotene
     RL: MOA (Modifier or additive use); USES (Uses)
```

(antioxidants; plant exts.-jojoba oil-based additives for liq. fuels for reduced pollutant emissions) 64-17-5, Ethanol, uses 108-88-3, Toluene, uses 994-05-8. 637-92-3 tert-Amyl methyl ether 1634-04-4, Methyl tert-butyl ether RL: MOA (Modifier or additive use); USES (Uses) (diluent; plant exts.-jojoba oil-based additives for liq. fuels for reduced pollutant emissions) 479-61-8 ΙT RL: MOA (Modifier or additive use); USES (Uses) (exts.; plant exts.-jojoba oil-based additives for liq. fuels for reduced pollutant emissions) 67-56-1, Methanol, uses TT RL: MOA (Modifier or additive use); USES (Uses) (plant exts.-jojoba oil-based additives for liq. fuels for reduced pollutant emissions) ANSWER 3 OF 56 CAPLUS COPYRIGHT 2002 ACS

L7

- 2002:669053 CAPLUS AN
- 137:203825 DN
- Biodiesel a growing fuel and its marketability ΤI
- ΑU Fischer, Jurgen
- Oelmuehle Leer Connemann GmbH, Leer, Germany CS
- Mineraloeltechnik (2002), 47(5), 1-19 so CODEN: MTCKAZ; ISSN: 0341-1893
- Beratungsgesellschaft fuer Mineraloel-Anwendungstechnik PB
- Journal; General Review DT
- German LΑ
- 52-0 (Electrochemical, Radiational, and Thermal Energy Technology) CC Section cross-reference(s): 51
- A review. According to our today's knowledge liq. energy sources are the best way to assure mobility. Petroleum products like gasoline, diesel fuel and kerosene keep us travelling long distances and make it possible to deliver goods to every place in the world. But restricted crude oil resources and environmental problems like the global warming effect are suitable arguments to look for alternative energy sources. The most important renewable energy sources for transportation purposes are liq. fuels based on plant oils. Pure plant oils are hardly suitable to be used in modern Diesel engines. By using a simple chem. process, the transesterification, fatty acid Me esters can be produced which have phys. properties similar to Diesel fuel and are commonly known as Biodiesel. Besides the CO2 balance which is significantly better than from Diesel, Biodiesel shows some more advantages. Low soot contents, reduced hydrocarbon emissions along with low cancerogenic potential are characteristic for emissions from Biodiesel. Low toxicity and biodegradedability are the most effective characteristics which gives Biodiesel the potential as an alternative fuel for regions sensitive to ecol. risks. The advantages of Biodiesel could even be better by using an optimized engine, esp. designed for this fuel. In particular the structure of particles emitted by Biodiesel driven engines shows a way to achieve extremely low emission limits without using expensive exhaust treatment systems. Based on electronic control devices modern fuel injection systems like Common-Rail-Injection and Pump-Injector-Units offer a variety of possibilities. Const. and high level quality are basic requirements for fuels suitable for cars. Concerning Biodiesel there are existing a no. of national stds. all over Europe including a European draft std. These stds. have been developed in cooperation with the car manufacturers. Approvals and warranties by the car manufacturers are based on these stds. Increasing prodn. capacities, a reliable and sufficient supply of raw materials as well as the most recent market conditions for Biodiesel caused a rapid sales increase over the last months. Supported by enhanced prodn. figures, including new facilities

```
planned and imported quantities the demand for Biodiesel in Germany in
     2001 is expected to be around 600.000 tons.
    review biodiesel diesel fuel substitute
ST
IT
    Diesel fuel substitutes
        (biodiesel; growing fuel and its marketability)
     ANSWER 4 OF 56 CAPLUS COPYRIGHT 2002 ACS
L7
Full Text
ΑN
     2001:921628 CAPLUS
     136:234304
DN
     Biofuels derived from vegetable oils and fats
ΤI
    Knothe, Gerhard; Dunn, Robert O.
ΑU
     Agricultural Research Service, National Center for Agricultural
CS
     Utilization Research, US Department of Agriculture, Peoria, IL, 61604, USA
     Oleochemical Manufacture and Applications (2001), 106-163. Editor(s):
SO
     Gunstone, Frank D.; Hamilton, Richard J. Publisher: Sheffield Academic
     Press, Sheffield, UK.
     CODEN: 69CCQZ
     Conference; General Review
DT
     English
LΑ
     51-0 (Fossil Fuels, Derivatives, and Related Products)
     Section cross-reference(s): 45, 52
     A review on the use of vegetable oil-based diesel fuels, particularly
AB
     in the form of esters (biodiesel). Topics discussed include sources and
     prodn. of such fuels, general comparison of fuels from vegetable
     oils and animal fats, process economics, regulatory issues, history
     and development, combustion of and emissions from biodiesel fuels,
     properties of biodiesel (e.g., low-temp. properties and storage
     stability), blending with conventional diesel fuels,
     transesterification, use of waste vegetable oils, pyrolyzed vegetable
     oils, use of microemulsions, and outlook for biodiesel fuels.
     Although vegetable oil-based fuels cannot replace all petroleum-based
     diesel fuels, they play an important role among the alternative fuels
     and contribute to the goal of energy independence and security.
     review diesel fuel vegetable oil biodiesel; transesterification
ST
     vegetable oil biodiesel review
     Fatty acids, preparation
IT
     RL: IMF (Industrial manufacture); PRP (Properties); PREP (Preparation)
        (Et esters, biodiesel; biodiesel fuels derived from vegetable
        oils and fats)
     Fatty acids, preparation
     RL: IMF (Industrial manufacture); PRP (Properties); PREP (Preparation)
         (Me esters, biodiesel; biodiesel fuels derived from vegetable
        oils and fats)
     Transesterification
IT
         (biodiesel fuels derived from vegetable oils and
        fats)
ΙT
     Glycerides, reactions
     RL: CPS (Chemical process); PEP (Physical, engineering or chemical
     process); RCT (Reactant); PROC (Process); RACT (Reactant or reagent)
         (biodiesel fuels derived from vegetable oils and
        fats)
     Diesel fuel substitutes
IT
         (biodiesel; biodiesel fuels derived from vegetable
        oils and fats)
     Diesel fuel additives
TT
         (cetane improvers, for biodiesel; biodiesel fuels derived
```

from vegetable oils and fats)

vegetable oils and fats)

Thermal decomposition

(of biodiesel fuels; biodiesel fuels derived from

IT

 \mathbf{IT}

(of glycerides; biodiesel fuels derived from vegetable oils and fats)

Fats and Glyceridic oils, processes

RL: CPS (Chemical process); PEP (Physical, engineering or chemical process); PROC (Process)

(vegetable, waste, glyceride source; biodiesel fuels derived from vegetable oils and fats)

279 THERE ARE 279 CITED REFERENCES AVAILABLE FOR THIS RECORD

- (1) Ahn, E; Sep Sci Technol 1995, V30, P2021 CAPLUS
- (2) Ahouissoussi, N; Industrial Uses of Agricultural Materials 1995, P35
- (3) Ali, Y; Bioresour Technol 1994, V47, P131 CAPLUS
- (4) Ali, Y; Bioresour Technol 1994, V50, P153 CAPLUS
- (5) Ali, Y; Bioresour Technol 1995, V52, P185 CAPLUS
- (6) Ali, Y; Bioresour Technol 1995, V52, P237 CAPLUS
- (7) Ali, Y; J Am Oil Chem Soc 1995, V72, P1557 CAPLUS
- (8) Andrews, A; Energy Agric 1984, V3, P323 CAPLUS
- (9) Anon; Biodiesel Report 1996
- (10) Anon; INFORM 1999, V10, P886
- (11) Anon; Oil Gas J 2000, V98, P53
- (12) Anon; Oil World 2001, V44, P71
- (13) Anon; www.unitedsoybean.org 2000, V1(5), P2
- (14) Applewhite, T; Kirk-Othmer, Encyclopedia of Chemical Technology, 3rd edn 1980, V9, P795 CAPLUS
- (15) Avella, F; Riv Combust 1992, V46, P181 CAPLUS
- (16) Bacon, D; Beyond the Energy Crisis 1981, V3, P1525
- (17) Bagby, M; ASAE Paper No 87-1583, 1987 Int Winter Meeting ASAE 1987
- (18) Bagby, M; Proc 9th Int Conf Jojoba Uses 3rd Int Conf New Industr Crops Prod 1996, P220
- (19) Bagley, S; Environ Sci Technol 1998, V32, P1183 CAPLUS
- (20) Bailer, J; Fresenius' J Anal Chem 1991, V340, P186 CAPLUS
- (21) Batel, W; Grundl Landtechnik 1980, V30, P40
- (22) Bessee, G; Soc Automot Eng, [Spec Publ] 1997, VSP-1274, P221 CAPLUS
- (23) Bettis, B; Agron J 1982, V74, P335 CAPLUS
- (24) Billaud, F; J Am Oil Chem Soc 1995, V72, P1149 CAPLUS
- (25) Bohmke, U; EP 543356 1993 CAPLUS
- (26) Bondioli, P; J Am Oil Chem Soc 1995, V72, P699 CAPLUS
- (27) Bondioli, P; Riv Ital Sostanze Grasse 1992, V69, P467 CAPLUS
- (28) Bondioli, P; Riv Ital Sostanze Grasse 1992, V69, P7 CAPLUS
- (29) Bondioli, P; Riv Ital Sostanze Grasse 1994, V71, P287 CAPLUS
- (30) Bondioli, P; Riv Ital Sostanze Grasse 1996, V73, P349 CAPLUS (31) Boocock, D; Biomass Bioenergy 1996, V11, P43 CAPLUS
- (32) Boocock, D; J Am Oil Chem Soc 1996, V73, P1247 CAPLUS
- (33) Boocock, D; J Am Oil Chem Soc 1998, V75, P1167 CAPLUS
- (34) Borgelt, S; Liq Fuels, Lubr Addit Biomass, Proc Altern Energy Conf 1994, P67 CAPLUS
- (35) Bormann, K; DE DD287048 1991
- (36) Boruff, P; Trans ASAE 1982, V25, P47 CAPLUS
- (37) Braun, D; Alternative fuel blends and diesel engine tests, Vegetable Oil Fuels 1982, P294
- (38) Breccia, A; J Microwave Power Electromagn Energy 1999, V34, P3
- (39) Bruwer, J; 1980 National Energy Symposium 1980, Pl1
- (40) Bruwer, J; 1980 Symposium 1980, P7
- (41) Bruwer, J; Energy Biomass Conf, 1st 1981, EUR 1981, EUR 7091, P934
- (42) Bunger, J; J Mutation Res 1998, V415, P13 CAPLUS
- (43) Bunger, J; Mutagenesis 2000, V15, P391 CAPLUS
- (44) Canakci, M; Trans ASAE 1999, V42, P1203 CAPLUS
- (45) Canakci, M; Trans ASAE 1999, V42, P1565 CAPLUS
- (46) Carraro, E; J Environ Pathol, Toxicol Oncol 1997, V16, P101 MEDLINE
- (47) Cecchi, G; Rev Fr Corps Gras 1987, V34, P397 CAPLUS
- (48) Chang, D; J Am Oil Chem Soc 1996, V73, P1549 CAPLUS
- (49) Charpentier, C; Entropie 1987, V23, P27 CAPLUS

- (50) Chavanne, C; BE 422877 1937 CAPLUS
- (51) Chavanne, G; Bull Soc Chim 1943, V10, P52 CAPLUS
- (52) Choo, Y; Chem Ind 2000, P530 CAPLUS
- (53) Choo, Y; Lipid Technologies and Applications 1997, P771 CAPLUS
- (54) Clark, S; J Am Oil Chem Soc 1984, V61, P1632 CAPLUS
- (55) Claude, S; Lipid Technology Newsletter 2000, V6, P105
- (56) Clevenger, M; Trans ASAE 1988, V31, P381
- (57) Clothier, P; Chem Soc Rev 1993, V22, P101 CAPLUS
- (58) Connemann, J; Fat Sci Technol 1994, V96, P536
- (59) Crookes, R; Arch Combust 1993, V13, P57 CAPLUS
- (60) Cruz, J; Resour Conserv 1981, V6, P69 CAPLUS
- (61) Cvengros, J; Bioresour Technol 1996, V55, P145 CAPLUS
- (62) Cvengros, J; J Am Oil Chem Soc 1994, V71, P1349 CAPLUS
- (63) Cvengrosova, Z; Petroleum Coal 1997, V39, P36 CAPLUS
- (64) Da Rocha, F; Fuel 1993, V72, P543
- (65) Darcey, C; Trans ASAE 1983, V26, P1626 CAPLUS
- (66) Davies, B; WO 9410267 1994 CAPLUS
- (67) de, B; Fett/Lipid 1999, V101, P404 CAPLUS
- (68) de Filippis, P; J Am Oil Chem Soc 1995, V72, P1399 CAPLUS
- (69) de Guzman, D; Chem Market Reporter 2001, V259, P10
- (70) Demmering, G; DE 4040317 1992 CAPLUS
- (71) Diesel, R; Engineering 1912, V93, P395 CAPLUS
- (72) Diesel, R; Proc Inst Mech Eng 1912, P179 CAPLUS
- (73) Dimmig, T; Chem Tech (Leipzig) 1999, V51, P326 CAPLUS
- (74) Dos Anjos, J; Appl Catal 1983, V5, P299 CAPLUS
- (75) Douros, T; Erdoel, Erdgas, Kohle 1987, V103, P228 CAPLUS
- (76) Dunn, R; J Dispers Sci Technol 1992, V13, P77 CAPLUS
- (77) Dunn, R; J Dispers Sci Technol 1993, V14, P1 CAPLUS
- (78) Freedman, B; J Am Oil Chem Soc 1986, V63, P1370 CAPLUS
- (79) Freedman, B; J Am Oil Chem Soc 1986, V63, P1375 CAPLUS
- (80) Freedman, B; J Am Oil Chem Soc 1989, V66, P1601 CAPLUS
- (81) Freedman, B; J Am Oil Chem Soc 1990, V67, P565 CAPLUS
- (82) Freedman, B; J Am Oil Chem Soc 1990, V66, P595
- (83) Freedman, B; SAE Technical Pap Ser 900343 1990, P9
- (84) Gelbard, G; J Am Oil Chem Soc 1995, V72, P1239 CAPLUS
- (85) Geller, D; Indust Crops Prod 1999, V9, P85 CAPLUS
- (86) Geyer, S; Trans ASAE 1984, V27, P375 CAPLUS
- (87) Glassman, I; Combustion, 3rd edn 1996
- (88) Goering, C; Evaluation of soybean oil-aqueous ethanol microemulsions, Vegetable Oil Fuels 1982, P279 CAPLUS
- (89) Goering, C; J Am Oil Chem Soc 1984, V61, P1638
- (90) Goering, C; Trans ASAE 1982, V25, P1472 CAPLUS
- (91) Goering, C; Trans ASAE 1983, V26, P1602 CAPLUS
- (92) Goodrum, J; Trans ASAE 1982, V25, P897 CAPLUS
- (93) Googin, J; Energy Res 1983, V3, P173 CAPLUS
- (94) Graboski, M; Prog Energy Combust Sci 1998, V24, P125 CAPLUS
- (95) Graille, J; Oleagineux 1982, V37, P421 CAPLUS
- (96) Graille, J; Oleagineux 1985, V40, P271 CAPLUS
- (97) Graille, J; Oleagineux 1986, V41, P457 CAPLUS
- (98) Gryglewicz, S; Bioresour Technol 1999, V70, P249 CAPLUS
- (99) Gunstone, F; Lipid Handbook 2nd edn 1994
- (100) Gusmao, J; Catal Today 1989, V5, P533 CAPLUS
- (101) Gutsche, B; Fett/Lipid 1997, V99, P418 CAPLUS
- (102) Haas, M; J Am Oil Chem Soc 2000, V77, P373 CAPLUS
- (103) Harrington, K; Biomass 1986, V9, P1 CAPLUS
- (104) Harrington, K; J Am Oil Chem Soc 1985, V62, P1009 CAPLUS
- (105) Hassan, M; J Energy, Heat Mass Transfer 1993, V15, P293 CAPLUS
- (106) Hochhauser, A; Kirk-Othmer, Encyclopedia of Chemical Technology, 4th edn 1994, V12, P341
- (107) Holcapek, M; J Chromatogr, A 1999, V858, P13 CAPLUS
- (108) Howell, S; SAE Technical Pap Ser 971687 in State of Alternative Fuel Technologies 1997, P203 CAPLUS

- (109) Hunter, H; US 5380343 1995 CAPLUS
- (110) Ikwuagwu, O; Industr Crops Prod 2000, V12, P57 CAPLUS
- (111) Isigigur, A; Appl Biochem Biotechnol 1993, V39-40, P89 CAPLUS
- (112) Isigigur, A; Appl Biochem Biotechnol 1994, V45-46, P103 CAPLUS
- (113) Isigigur, A; Appl Biochem Biotechnol 1994, V45-46, P93 CAPLUS
- (114) Kaieda, M; J Bioscience Bioeng 1999, V88, P627 CAPLUS
- (115) Karaosmanoglu, F; Energy Sources 1999, V21, P221 CAPLUS
- (116) Karaosmanoglu, F; Renewable Energy: Technol Environ Proc World Renewable Energy Congr 2nd 1992, V3, P1455 CAPLUS
- (117) Kato, M; Sekiyu Gakkaishi 1992, V35, P115 CAPLUS
- (118) Kaufman, K; Trans ASAE 1984, V27, P1626 CAPLUS
- (119) Kaufmann, H; Fett Seifen Anstrichm 1958, V60, P919 CAPLUS
- (120) Kildiran, G; J Am Oil Chem Soc 1996, V73, P225 CAPLUS
- (121) Klopfenstein, W; J Am Oil Chem Soc 1982, V59, P531 CAPLUS
- (122) Klopfenstein, W; J Am Oil Chem Soc 1985, V62, P1029 CAPLUS
- (123) Knothe, G; ACS Symposium Series 666: Fuels and Chemicals from Biomass 1997, P172 CAPLUS
- (124) Knothe, G; INFORM 1996, V7, P827
- (125) Knothe, G; J Am Oil Chem Soc 1991, V68, P259 CAPLUS
- (126) Knothe, G; J Am Oil Chem Soc 1992, V69, P341 CAPLUS
- (127) Knothe, G; J Am Oil Chem Soc 1998, V75, P1007 CAPLUS
- (128) Knothe, G; J Am Oil Chem Soc 1999, V76, P795 CAPLUS
- (129) Knothe, G; J Am Oil Chem Soc 2000, V77, P489 CAPLUS
- (130) Knothe, G; J Am Oil Chem Soc 2000, V77, P865 CAPLUS
- (131) Knothe, G; SAE Technical Pap Ser 971681 in State of Alternative Fuel Technologies 1997, P127 CAPLUS
- (132) Knothe, G; SAE Technical Paper Series 920194 1992
- (133) Komers, K; Fett/Lipid 1998, V100, P507 CAPLUS
- (134) Korus, R; Polymerization of vegetable oils, (Vegetable Oil Fuels) 1982, P218 CAPLUS
- (135) Krahl, J; Landbauforschung Volkenrode 1994, V44, P182
- (136) Krahl, J; Motortechn Z 1996, V57, P24
- (137) Krahl, J; SAE Tech Pap Ser 961847 1996, P14
- (138) Krahl, J; SAE Tech Pap Ser 962096 1996, P319
- (139) Krawczyk, T; INFORM 1996, V7, P801
- (140) Krisnangkura, K; J Am Oil Chem Soc 1986, V63, P552 CAPLUS
- (141) Ladommatos, N; Fuel 1995, V74, P1083 CAPLUS
- (142) Ladommatos, N; Fuel 1996, V75, P8 CAPLUS
- (143) Lal, K; US 5338471 1994 CAPLUS
- (144) Lal, K; EP 604125 1994 CAPLUS
- (145) Lane, J; Kirk-Othmer, Encyclopedia of Chemical Technology, 3rd Edn 1980, V11, P682
- (146) Last, R; Soc Automot Eng [Spec Publ] 1995, VSP-1093, P9 CAPLUS
- (147) Lechner, M; J High Resolut Chromatogr 1997, V20, P581 CAPLUS
- (148) Lee, I; J Am Oil Chem Soc 1995, V72, P1155 CAPLUS
- (149) Lee, I; J Am Oil Chem Soc 1996, V73, P631 CAPLUS
- (150) Lepori, W; Liq Fuels Renewable Resour, Proc Altern Energy Conf 1992, P89 CAPLUS
- (151) Lewtas, K; WO 9318115 1993 CAPLUS
- (152) Lilly, L; Diesel Engine Reference Book, 1st edn 1980
- (153) Linko, Y; J Biotechnol 1998, V66, P41 CAPLUS
- (154) Lozano, P; Fresenius' J Anal Chem 1996, V354, P319 CAPLUS
- (155) Ma, F; Bioresour Technol 1999, V70, P1 CAPLUS
- (156) Ma, F; Bioresour Technol 1999, V69, P289 CAPLUS
- (157) Ma, F; Ind Eng Chem Res 1998, V37, P3768 CAPLUS
- (158) Ma, F; Trans ASAE 1998, V41, P1261 CAPLUS
- (159) Mackay, R; Nonionic Surfactants: Physical Chemistry, Surf Sci Ser 1987, V23, P297 CAPLUS
- (160) Mariani, C; Riv Ital Sostanze Grasse 1991, V68, P549 CAPLUS
- (161) Martin, J; EP 587551 1994 CAPLUS
- (162) Masjuki, H; J Energy, Heat Mass Transfer 1994, V16, P295 CAPLUS
- (163) Mason, M; Prepr Am Chem Soc, Div Pet Chem 1998, V43, P579 CAPLUS

- (164) McBain, M; Solubilization and related phenomena 1955, P179
- (165) McDonald, J; Soc Automot Eng [Spec Publ] 1995, VSP-1093, P191 CAPLUS
- (166) Miller, N; Spill Sci Technol Bull 1997, V4, P17 CAPLUS
- (167) Mills, G; J Inst Energy 1983, V56, P131 CAPLUS
- (168) Mittelbach, M; Bioresour Technol 1996, V56, P7 CAPLUS
- (169) Mittelbach, M; Chromatographia 1993, V37, P623 CAPLUS
- (170) Mittelbach, M; Chromatographia 1996, V42, P431 CAPLUS
- (171) Mittelbach, M; Energy Agric 1983, V2, P369 CAPLUS
- (172) Mittelbach, M; Energy Agric 1985, V4, P207 CAPLUS
- (173) Mittelbach, M; J Am Oil Chem Soc 1990, V92, P145 CAPLUS
- (174) Mittelbach, M; J Am Oil Chem Soc 1990, V67, P168 CAPLUS
- (175) Mittelbach, M; J Am Oil Chem Soc 1999, V76, P545 CAPLUS
- (176) Mittelbach, M; Liq Fuels Renewable Resour, Proc Altern Energy Conf 1992, P74 CAPLUS
- (177) Mittelbach, M; Liq Fuels, Lubr Addit Biomass, Proc Altern Energy Conf 1994, P151 CAPLUS
- (178) Mittelbach, M; Oesterr Chem Z 1989, V90, P147 CAPLUS
- (179) Msipa, C; Trans ASAE 1983, V26, P1669 CAPLUS
- (180) Mudge, S; Spill Sci Technol Bull 1999, V5, P353 CAPLUS
- (181) Mulangala, M; Entropie 1981, V98, P97 CAPLUS
- (182) Muller, M; EP 406684 1991 CAPLUS
- (183) Munavu, R; Kenya J Sci Technol 1984, V5, P45 CAPLUS
- (184) Nagle, N; Appl Biochem Biotechnol 1990, V24-25, P355 CAPLUS
- (185) Nelson, L; INFORM 1995, V6, P509
- (186) Nelson, L; J Am Oil Chem Soc 1996, V73, P1191 CAPLUS
- (187) Noureddini, H; J Am Oil Chem Soc 1997, V74, P1457 CAPLUS
- (188) Noureddini, H; J Am Oil Chem Soc 1998, V75, P1775 CAPLUS
- (189) Nunes, P; Rev Inst Fr Pet 1986, V41, P421 CAPLUS
- (190) Nye, M; J Am Oil Chem Soc 1983, V60, P1598 CAPLUS
- (191) Owen, K; Automotive Fuels Reference Book 2nd ed 1995
- (192) Pande, S; Fuel 1990, V69, P437 CAPLUS
- (193) Pestes, M; J Test Eval 1984, V12, P61 CAPLUS
- (194) Peters, R; INFORM 1996, V7, P502
- (195) Peterson, C; Trans ASAE 1983, V26, P322 CAPLUS
- (196) Peterson, C; Trans ASAE 1987, V30, P28 CAPLUS
- (197) Peterson, G; J Am Oil Chem Soc 1984, V61, P1593 CAPLUS
- (198) Plank, C; Fett Wiss Technol 1994, V96, P379 CAPLUS
- (199) Plank, C; J Chromatogr, A 1994, V683, P95 CAPLUS
- (200) Plank, C; J Chromatogr, A 1995, V697, P461 CAPLUS (201) Plank, C; J High Resolut Chromatogr 1992, V15, P609 CAPLUS
- (202) Plank, C; J High Resolut Chromatogr 1993, V16, P483 CAPLUS
- (203) Poirier, M; US 5454842 1995 CAPLUS
- (204) Posorske, L; J Am Oil Chem Soc 1984, V61, P1758 CAPLUS
- (205) Prankl, H; Proc Third Liquid Fuel Conference: Liquid Fuels and Industrial Products from Renewable Resources 1996, P191 CAPLUS
- (206) Pryor, R; Trans ASAE 1983, V26, P333 CAPLUS
- (207) Puckett, A; U S Bur Mines, Inform Circ 1948, 7474, P14
- (208) Purcell, D; J Am Oil Chem Soc 1996, V73, P381 CAPLUS
- (209) Rakopoulos, C; Renewable Energy 1992, V2, P327 CAPLUS
- (210) Raneses, A; Industr Crops Prods 1999, V9, P151
- (211) Reed, T; Energy Biomass Wastes 1991, V15, P907 CAPLUS
- (212) Rewolinski, C; J Am Oil Chem Soc 1985, V62, P1120 CAPLUS
- (213) Ricardo Consulting Engineers; Diesel Engine Reference Book, 2nd edn 1998
- (214) Ryan, T; J Am Oil Chem Soc 1984, V61, P1610 CAPLUS
- (215) Sadeghi-Jorabchi, H; Spectrosc Eur 1994, V6, P16 CAPLUS
- (216) Schmidt, A; Automobiltechn Z 1933, V36, P212 CAPLUS
- (217) Schmidt, A; Erdoel, Erdgas, Kohle 1992, V108, P415 CAPLUS
- (218) Scholl, K; Alternate Fuels: A Decade of Success and Promise 1994, P555 CAPLUS
- (219) Schon, S; US 5004479 1991 CAPLUS
- (220) Schuchardt, U; J Braz Chem Soc 1998, V9, P199 CAPLUS
- (221) Schwab, A; US 4451265 1984 CAPLUS

```
(222) Schwab, A; US 4451267 1984 CAPLUS
(223) Schwab, A; US 4526586 1985 CAPLUS
(224) Schwab, A; US 4557734 1985 CAPLUS
(225) Schwab, A; Fuel 1987, V66, P1372 CAPLUS
(226) Schwab, A; J Am Oil Chem Soc 1988, V65, P1781 CAPLUS
(227) Schwab, A; J Dispers Sci Technol 1982, V3, P45 CAPLUS
(228) Schwab, A; J Dispers Sci Technol 1983, V4, P1 CAPLUS
(229) Schwab, A; J Dispers Sci Technol 1985, V6, P563 CAPLUS
(230) Selmi, B; J Am Oil Chem Soc 1998, V75, P691 CAPLUS
(231) Sercheli, R; J Am Oil Chem Soc 1999, V76, P1207 CAPLUS
(232) Sexton, M; EP 475620 1992 CAPLUS
(233) Shay, E; Biomass Bioenergy 1993, V4, P227 CAPLUS
(234) Shimada, Y; J Am Oil Chem Soc 1999, V76, P789 CAPLUS
(235) Siekmann, R; Proc Vegetable Oil Diesel Fuel, Seminar III, Agricultural
    Reviews and Manuals 1983, P163
(236) Siekmann, R; Vegetable Oil Fuels 1982, P117
(237) Sii, H; J Am Oil Chem Soc 1995, V72, P905 CAPLUS
(238) Siler-Marinkovic, S; Fuel 1998, V77, P1389 CAPLUS
(239) Simkovsky, N; Erdoel, Erdgas, Kohle 1999, V115, P317 CAPLUS
(240) Simkovsky, N; Fett/Lipid 1998, V100, P534 CAPLUS
(241) Sims, R; Trans ASAE 1985, V28, P716 CAPLUS
(242) Srivastava, A; Renew Sust Energy Rev 2000, V4, P111 CAPLUS
(243) Staat, F; Chem Ind 1994, P863 CAPLUS
(244) Stage, H; Fett Wiss Technol 1988, V90, P28 CAPLUS
(245) Stalder, K; Landtechnik 1995, V50, P266
(246) Starr, M; SAE Tech Pap Ser 972904 1997
(247) Stournas, S; J Am Oil Chem Soc 1995, V72, P433 CAPLUS
(248) Stumborg, M; Energy Biomass Wastes 1993, V16, P721 CAPLUS
(249) Sumera, F; Philipp J Sci 1990, V119, P333 CAPLUS
(250) Suppes, G; Fuel 1999, V78, P73 CAPLUS
(251) Tat, M; J Am Oil Chem Soc 2000, V77, P285
(252) Thompson, J; Trans ASAE 1998, V41, P931 CAPLUS
(253) Trathnigg, B; J Liquid Chromatogr 1990, V13, P95 CAPLUS
(254) Vaitilingom, G; Entropie 1991, V27, P39 CAPLUS
(255) van Den Abeele, M; Bull Agr Congo Belge 1942, V33, P3 CAPLUS
(256) van Gerpen, J; ASAE paper 996134 1999
(257) van Gerpen, J; Diesel Engine Reference Book 1998, P89
(258) Vellguth, G; Grundl Landtechnik 1982, V32, P177
(259) Vicente, G; Ind Crops Prod 1998, V8, P29 CAPLUS
(260) Wallace, F; Diesel Engine Reference Book 1998, P3
(261) Walton, J; Gas Oil Power 1938, V33, P167 CAPLUS
(262) Watanabe, Y; J Am Oil Chem Soc 2000, V77, P355 CAPLUS
(263) Weast, R; Handbook of Chemistry and Physics, 66th edn 1985-1986, PD-272
(264) Wehlmann, J; Fett/Lipid 1999, V101, P249 CAPLUS
(265) Wenzel, G; Fat Sci Technol 1995, V97, P475 CAPLUS
(266) Willing, A; Fett/Lipid 1999, V101, P192 CAPLUS
(267) Wu, W; J Am Oil Chem Soc 1998, V75, P1173 CAPLUS
(268) Wu, W; J Am Oil Chem Soc 1999, V76, P517 CAPLUS
(269) Yaginuma, R; Sekiyu Gakkaishi 1999, V42, P173 CAPLUS
(270) Yean, C; J Appl Organomet Chem 2000, V14, P304 CAPLUS
(271) Yu, L; J Am Oil Chem Soc 1998, V75, P1821 CAPLUS
(272) Zaher, F; Energy Sources 1993, V15, P499 CAPLUS
(273) Zaher, F; Grasas Aceites (Seville) 1990, V41, P82 CAPLUS
(274) Zemanek, G; Fett/Lipid 1999, V101, P321 CAPLUS
```

- (275) Zhang, X; Trans ASAE 1998, V41, P1423 CAPLUS (276) Zhang, Y; Soc Automot Eng, [Spec Publ] SP 1996, VSP-1160, P1 CAPLUS
- (277) Ziejewski, M; J Am Oil Chem Soc 1984, V61, P1620 CAPLUS
- (278) Ziejewski, M; SAE Tech Pap Ser 911765 1991
- (279) Zubik, J; Trans ASAE 1984, V27, P1251

ANSWER 5 OF 56 CAPLUS COPYRIGHT 2002 ACS Full Text

```
2001:816820 CAPLUS
AN
    135:346706
   Liquefied gas fuel for compression ignition engines
TI
    Tamura, Masamitsu; Goto, Shinichi; Sugiyama, Kouseki; Kajiwara, Masataka;
IN
     Sagara, Makoto
     Iwatani International Corporation, Japan
PΑ
so
     PCT Int. Appl., 29 pp.
     CODEN: PIXXD2
DT
     Patent
   English
IC ICM C10L
     51-7 (Fossil Fuels, Derivatives, and Related Products)
CC
FAN.CNT 1
                                             APPLICATION NO. DATE
                     KIND DATE
     PATENT NO.
     _____
                                             _____
     WO 2001083646 A2 20011108
                                            WO 2001-JP3719 20010427
PΤ
         W: AE, AU, CA, CN, CZ, ID, IN, KR, MX, PL, SG, US, VN
         RW: BE, DE, ES, FR, GB, IT, NL, SE
JP 2001342474 A2 20011214 JP 2000-161506 20000531
JP 2002012879 A2 20020115 JP 2000-369658 20001205
JP 2002173691 A2 20020621 JP 2000-369661 20001205
AU 2001052646 A5 20011112 AU 2001-52646 20010427
PRAI JP 2000-161506 A 20000428
JP 2000-161506 A 20000531
     JP 2000-369658 A 20001205
     JP 2000-369661 A 20001205
     WO 2001-JP3719 W 20010427
     Disclosed is a liquefied gas fuel, which can reduce emissions of air
     pollutants, such as black smoke, particulate matter, NOx and SOx in an
     exhaust gas of a compression ignition engine. The liquefied gas fuel
     comprises liquefied petroleum gas added with a radical generating agent, a
     lubricity improving agent and liq. hydrocarbon, or di-Me ether added with
     the lubricity improving agent.
     LPG lubricant peroxide additive
     Alkanes, uses
     RL: MOA (Modifier or additive use); USES (Uses)
         (C8-14, esters; liquefied gas fuel for compression
        ignition engines)
     Alcohols, uses
TΤ
       Fatty acids, uses
     RL: MOA (Modifier or additive use); USES (Uses)
         (C8-14; liquefied gas fuel for compression ignition
        engines)
IT
     Petroleum products
     RL: PEP (Physical, engineering or chemical process); PROC (Process)
         (gases, liquefied; liquefied gas fuel for compression
         ignition engines)
     Petroleum, processes
ΙT
     RL: PEP (Physical, engineering or chemical process); PROC (Process)
         (heavy; liquefied gas fuel for compression ignition
         engines)
     Lubricants
ΙT
     Soot
         (liquefied gas fuel for compression ignition
         engines)
ΙT
     Nitrates, uses
      RL: CAT (Catalyst use); USES (Uses)
         (liquefied gas fuel for compression ignition
         engines)
IT
     Azo compounds
      RL: MOA (Modifier or additive use); USES (Uses)
         (liquefied gas fuel for compression ignition
```

engines) Naphtha RL: MOA (Modifier or additive use); USES (Uses) (liquefied gas fuel for compression ignition engines) Nitrites RL: MOA (Modifier or additive use); USES (Uses) (liquefied gas fuel for compression ignition engines) IT Paraffin oils RL: MOA (Modifier or additive use); USES (Uses) (liquefied gas fuel for compression ignition engines) TΨ Peroxides, uses RL: MOA (Modifier or additive use); USES (Uses) (liquefied gas fuel for compression ignition engines) IT Kerosene RL: PEP (Physical, engineering or chemical process); PROC (Process) (liquefied gas fuel for compression ignition engines) Petroleum products (oils; liquefied gas fuel for compression ignition engines) 110-05-4, Di-tert-butyl peroxide RL: MOA (Modifier or additive use); USES (Uses) (liquefied gas fuel for compression ignition engines) 74-98-6, Propane, processes 106-97-8, Butane, processes TΨ RL: PEP (Physical, engineering or chemical process); PROC (Process) (liquefied gas fuel for compression ignition 12624-32-7, Sulfur oxide 11104-93-1, Nitrogen oxide, processes IT RL: REM (Removal or disposal); PROC (Process) (liquefied gas fuel for compression ignition ANSWER 6 OF 56 CAPLUS COPYRIGHT 2002 ACS L7 Full Text 2001:765380 CAPLUS AN DN 136:122538 Emission reduction of regenerative fuel powered co-generation plants ΤI with SCR- and oxidation-catalysts Lachenmaier, J.; Dobiasch, A.; Meyer-Pittroff, R. ΑU Lebensmittelindustrie, Technische Universitat Munchen, Freising, D-85350, CS Topics in Catalysis (2001), 16/17(1-4), 437-442 SO CODEN: TOCAFI; ISSN: 1022-5528 Kluwer Academic/Plenum Publishers PΒ DTJournal LA English 59-3 (Air Pollution and Industrial Hygiene) CC Section cross-reference(s): 67 Since the beginning of combustion engine development in this recent AB century various different fuels have been successfully tested. Diesel engines have been adapted to fuels made from mineral oils because of the rising importance and the cheapness in comparison to other fuels. On the other hand, it is possible to burn regenerative fuels in engines and achieve some significant advantages in comparison to fossil diesel fuel. This is, for example, a closed carbon dioxide (CO2) cycle

which causes no green house effect. It is possible to ext. oil from various seeds like rapeseed. It is also possible to burn used oil

from the food processing industry or waste grease and oil from food recycling companies. The great advantages: (1) food recycling oils can produce energy instead of use as animal food, and (2) as nobody knows exactly the consistency of the collected oils, poisonous pollution is possible. These regenerative fuels can be burned without any further processing in special adapted diesel engines, for example an Elsbett engine, or in precombustion engines with large swept vols. Most researchers focused on operating diesel engines with regenerative fuels and reducing the emissions caring only about regulated exhaust components. In comparison to these studies it is necessary to learn more about the emissions beyond the exhaust regulations. Addnl. emission redn. is possible by using an SCR-catalyst (selective catalytic redn.) to reduce the NO2 combined with an oxidn.-catalyst which reduces any kind of oxidizable emissions. The TU Munchen, Lehrstuhl fur Energie- und Umwelttechnik der Lebensmittelindustrie, operates a small co-generation plant with the ability of analyzing the std. emission components (CO, NO2, HC, particles, CO2, O2) and unregulated components (SO2, NH3, polycyclic arom. hydrocarbons (PAH), aldehyde, ketone). The emissions show some significant differences in comparison to fossil diesel fuel which is caused by the diversity of each fuel. Results of an investigation on four different fuels (wastefat Me ester (WME), rapeseed Me ester (RME), rapeseed oil and diesel fuel) burned in a small co-generation plant with a SCR- and oxidn.-catalyst will be presented. A comparison to the emissions before and after the catalysts will be shown addnl. to the results of the different redn. potential of diesel fuel, Me ester or untreated oils. The combination of regenerative fuel and catalyst shows good potential for reducing the emissions. Furthermore the use of regenerative fuels is a sustainable prodn. of energy with an overall efficiency of almost 90%. Regenerative fuels based on vegetable oils and waste fat are a valuable form of energy and have some significant advantages in comparison to diesel fuel, like an almost closed carbon dioxide cycle, rapid biol. decompn. and lower CO, HC and particle emissions. Regenerative fuels should also meet min. stds. discussed in the paper to avoid the risk of engine damage and to reduce emissions. regenerative fuel combustion exhaust treatment

```
regenerative fuel combustion exhaust treatment

Fats and Glyceridic oils, uses

RL: TEM (Technical or engineered material use); USES (Uses)

(Me esters; emission redn. of regenerative fuel

powered co-generation plants with SCR- and oxidn.-catalysts)

IT Diesel fuel substitutes
```

(biodiesel; **emission** redn. of regenerative **fuel** powered co-generation plants with SCR- and oxidn.-catalysts)

IT Diesel fuel

Exhaust gases (engine)

(emission redn. of regenerative fuel powered co-generation plants with SCR- and oxidn.-catalysts)

IT Hydrocarbons, processes

RL: REM (Removal or disposal); PROC (Process)
(emission redn. of regenerative fuel powered
co-generation plants with SCR- and oxidn.-catalysts)

IT Rape oil

RL: TEM (Technical or engineered material use); USES (Uses)
(emission redn. of regenerative fuel powered
co-generation plants with SCR- and oxidn.-catalysts)

IT Fatty acids, uses

RL: TEM (Technical or engineered material use); USES (Uses) (rape-oil, esters; emission redn. of regenerative fuel powered co-generation plants with SCR- and oxidn.-catalysts)

IT 630-08-0, Carbon monoxide, processes 10024-97-2, Nitrous oxide, processes 10102-44-0, Nitrogen dioxide, processes 11104-93-1, Nitrogen

oxide, processes

RL: REM (Removal or disposal); PROC (Process)
(emission redn. of regenerative fuel powered
co-generation plants with SCR- and oxidn.-catalysts)

RE.CNT 12 THERE ARE 12 CITED REFERENCES AVAILABLE FOR THIS RECORD

- (1) Bayerische Landesanstalt Fur Landtechnik; Symposium Dezentrale Pflanzenolgewinnung 2000
- (2) Dobiasch, A; Kongresszeitschrift zur Fachtagung im Fortbildungszentrum des Bayerischen Landesamtes fur Umweltschutz "Energetische Nutzung von Pflanzenolen," 1998
- (3) Dobiasch, A; Proc Fisita 1998 World Automotive Congress 1998, F98P515
- (4) Dobiasch, A; VDI-Berichte, Nr 1457, Fortschrittliche Energiewandlung und Anwendung 1999, V16, PS359
- (5) Jurisch, C; VDI Berichte Nr 1126 1994
- (6) Klingenberg, H; Automobil-Messtechnik 1995
- (7) Lachenmaier, J; Buletinul Stiintific al Universitatii "Politechnica" din Timisoara 1998, V43, P85
- (8) Lachenmaier, J; OTTI-Anwenderforum Energetische Nutzung von Pflanzenol und Biogas 1999, P193
- (9) Lachenmaier, J; Proc 5th Int Conf on Technologies and Combustion for a Clean Environment 1999
- (10) May, H; Motortechnische Zeitschrift 1997, V58
- (11) May, H; Neuere Untersuchungen uber die Umweltvertraglichkeit und die Dauerstandfestigkeit von Vorkammer- und Direkteinpritzenden Dieselmotoren bei Betrieb mit Rapsol und Rapsolmethylester 1992
- (12) Schuster, W; Olpflanzen in Europa 1992
- L7 ANSWER 7 OF 56 CAPLUS COPYRIGHT 2002 ACS

- AN 2001:466265 CAPLUS
- DN 135:213297
- TI Wear assessment in a biodiesel fuelled compression ignition engine
- AU Agarwal, Avinash Kumar; Bijwe, Jayashree; Das, L. M.
- CS Engine Research Center, University of Wisconsin, Madison, WI, 53706, USA
- ICE (American Society of Mechanical Engineers) (2001), 36-3(Engine Systems: Lubrication, Wear, Components, System Dynamics, and Design), 29-37
 - CODEN: ICEIEG; ISSN: 1066-5048
- PB American Society of Mechanical Engineers
- DT Journal
- LA English
- CC 52-1 (Electrochemical, Radiational, and Thermal Energy Technology)
 Section cross-reference(s): 51
- Biodiesel is prepd. using linseed oil and methanol by the process of AΒ transesterification. Use of linseed oil Me ester (LOME) in compression ignition engine was found to develop a highly compatible engine-fuel system with low emission characteristics. Two similar engines were operated using optimum biodiesel blend and mineral diesel oil resp. These were subjected to long-term endurance tests. Lubricating oil samples drawn from both engines after a fixed interval were subjected to elemental anal. Quantification of various metal debris concns. was done by at. absorption spectroscopy (AAS). Wear metals were found to be about 30% lower for biodiesel-operated engine system. Lubricating oil samples were also subjected to ferrog. indicating lower wear debris concns. for biodiesel-operated engine. The addnl. lubricating property of LOME present in the fuel resulted in lower wear and improved life of moving components in biodiesel-fuelled engine. However, this needed exptl. verification and quantification. A series of expts. were thus conducted to compare the lubricity of various concns. of LOME in biodiesel blends. Long duration tests were conducted using reciprocating motion in SRV optimal wear tester to evaluate the coeff. of friction, specific wear

rates, etc. The extent of damage, coeff. of friction, and specific wear rates decreased with increase in the percentage of LOME in the biodiesel blend. SEM was conducted on the surfaces exposed to wear. The disk and pin using 20% biodiesel blend as lubricating oil showed lesser damage compared to the one subjected to diesel oil as lubricating fluid, confirming addnl. lubricity of biodiesel.

ST linseed oil Me ester biodiesel; engine wear lubricating oil biodiesel

IT Diesel fuel substitutes

(biodiesel; wear assessment in a biodiesel fuelled compression ignition engine)

IT Lubricating oils

(diesel; wear assessment in a biodiesel fuelled compression
ignition engine)

IT Fatty acids, uses

RL: NUU (Other use, unclassified); USES (Uses)
(linseed-oil, Me esters; wear assessment in a biodiesel
fuelled compression ignition engine)

IT Wear

(wear assessment in a biodiesel fuelled compression **ignition** engine)

RE.CNT 11 THERE ARE 11 CITED REFERENCES AVAILABLE FOR THIS RECORD

RE
(1) American Riofuel Association: Riodiesel: a technology, performance

- (1) American Biofuel Association; Biodiesel: a technology, performance and regulatory overview 1994
- (2) Anon; Ten Energy Economy Simulation and Evaluation Model 1998
- (3) Freedman, B; JAOCS 1986, V63(10)
- (4) Krawczyk, T; Inform 1996, V7(8), P801
- (5) Kumar Agarwal, A; Manuscript submitted to ASME Journal of engineering for gas turbine and power 2000
- (6) Kumar Agarwal, A; Manuscript submitted to ASME Journal of engineering for gas turbine and power 2000
- (7) Kumar Agarwal, A; PhD thesis, Centre for Energy Studies, Indian Institute of Technology 1999
- (8) Peterson, C; Proceedings Of "Alcohol and Vegetable Oil as Alternative Fuels" 1981
- (9) Richardson, D; SAE paper 1999, 912388
- (10) Van Dyne, D; Bioresource Technology 1996, V56 CAPLUS
- (11) Weber, J; Proceedings of the Third fuel conference 1996

L7 ANSWER 8 OF 56 CAPLUS COPYRIGHT 2002 ACS

- AN 2001:309850 CAPLUS
- DN 134:313356
- TI Alternative diesel fuels from vegetable oils and animal fats
- AU Dunn, Robert O.; Knothe, Gerhard
- CS Oil Chemical Research, Agricultural Research Service (ARS), National Center for Agricultural Utilization Research (NCAUR), U.S. Department of Agriculture (USDA), Peoria, IL, 61604, USA
- SO Journal of Oleo Science (2001), 50(5), 415-426 CODEN: JOSOAP; ISSN: 1345-8957
- PB Japan Oil Chemists' Society
- DT Journal
- LA English
- CC 51-9 (Fossil Fuels, Derivatives, and Related Products)
- AB Biodiesel, defined as the mono-alkyl esters of fatty acids derived from vegetable oils or animal fats, is a strong candidate alternative fuel for combustion in compression ignition (diesel) engines. With respect to petroleum middle distillates, biodiesel has superior cetane no. and lubricity characteristics, has comparable heats of combustion and kinematic viscosities, and is non-flammable making it safer to store and handle. Biodiesel is renewable and can help reduce dependence upon imported petroleum. Biodiesel is environmentally friendly because it is

readily biodegradable and its combustion reduces most harmful exhaust emissions, including carbon monoxide, unburned hydrocarbons, particulate matter, and polyarom. hydrocarbons. In the United States, the Energy Policy Act (EPACT) of 1992 and Clean Air Act with its subsequent amendments have combined to help establish a favorable atm. for development of biodiesel; however, many technol. hurdles must be removed before widespread commercialization will be feasible. During cooler weather, biodiesel "gels" at temps. near freezing (0°C) compared with - 15 to - 17°C for conventional diesel fuel. Another concern for biodiesel is its long-term storage stability with respect to oxidative degrdn. Finally, most reports indicate biodiesel does not significantly reduce nitrogen oxides (NOx) emissions. This is a particular concern because NOx may react in the atm. to form ozone, a component of smog. This work reviews recent progress in the development of biodiesel with emphasis on removing these technol. hurdles.

- ST biodiesel **fuel** property vegetable **oil** animal **fat**; combustion biodiesel compression **ignition** engine
- IT Fats and Glyceridic oils, processes

RL: PEP (Physical, engineering or chemical process); PROC (Process) (animal; properties of alternative diesel fuels from vegetable oils and animal fats)

IT Air pollution

(biodiesel from vegetable oils and animal fats in relation to)

IT Diesel fuel

(biodiesel; properties of alternative diesel **fuels** from vegetable **oils** and animal **fats**)

IT Lubrication

(lubricity of biodiesel)

IT Cetane number

(of biodiesel)

IT Combustion

(of biodiesel in compression ignition engines)

IT Fats and Glyceridic oils, processes

RL: PEP (Physical, engineering or chemical process); PROC (Process) (vegetable; properties of alternative diesel fuels from vegetable oils and animal fats)

RE.CNT 113 THERE ARE 113 CITED REFERENCES AVAILABLE FOR THIS RECORD RE

- (1) Adams, C; J Am Oil Chem Soc 1983, V60, P1574 CAPLUS
- (2) Agarwal, A; ASME ICE, 34-3 (Alternative Fuels, Dimethyl Ether and Natural Gas Engines) 2000, P17 CAPLUS
- (3) Ali, Y; Bioresour Technol 1995, V52, P185 CAPLUS
- (4) Anon; Annual Book of ASTM Standards 1991, ASTM D975
- (5) Anon; Annual Book of ASTM Standards 1999, ASTM PS 121
- (6) Anon; Biodiesel Bull 2000
- (7) Anon; Biodiesel Report 1996
- (8) Anon; Diesel Engine Reference Book 1984, P18/9
- (9) Baranescu, R; ASAE Spec 1982, P364
- (10) Bondioli, P; J Am Oil Chem Soc 1995, V72, P699 CAPLUS
- (11) Brown, G; Erdoel, Kohle, Erdgas Petrochemie 1990, V43, P196 CAPLUS
- (12) Bruwer, J; 1st Energy Biomass Conf 1981, P934 CAPLUS
- (13) Bruwer, J; Proc South African Institute of Agricultural Engineers Symposium 1980
- (14) Bruwer, J; Proc South African Institute of Agricultural Engineers Symposium 1980
- (15) Canakci, M; Trans ASAE 1999, V42, P1203 CAPLUS
- (16) Cecchi, G; Rev Fr Corps Gras 1987, V34, P397 CAPLUS
- (17) Chandler, J; SAE Tech Paper Ser Paper No 922186 1992
- (18) Clark, S; Final Report 1983, 59-2201-1-6-0-059-0
- (19) Clark, S; J Am Oil Chem Soc 1984, V61, P1632 CAPLUS
- (20) Clothier, P; Chem Soc Rev 1993, V22, P101 CAPLUS

- (21) Cvengros, J; J Am Oil Chem Soc 1994, V71, P1349 CAPLUS
- (22) Da Rocha Filho, G; Fuel 1993, V72, P543 CAPLUS
- (23) Dimmig, T; Chem Tech (Leipzig) 1999, V51, P326 CAPLUS
- (24) Dos Anjos, J; Appl Catal 1983, V5, P299 CAPLUS
- (25) du Plessis, L; J Am Oil Chem Soc 1985, V62, P748 CAPLUS
- (26) du Plessis, L; Vegetable Oil as Diesel Fuel, Seminar 3 1983, P57
- (27) Duff, H; Introduction to Fats and Oils Technology 1991, P105
- (28) Dunn, R; J Am Oil Chem Soc 1994, V71, P101 CAPLUS (29) Dunn, R; J Am Oil Chem Soc 1995, V72, P895 CAPLUS
- (30) Dunn, R; J Am Oil Chem Soc 1996, V73, P1719 CAPLUS
- (31) Dunn, R; J Dispersion Sci Technol 1992, V13, P77 CAPLUS
- (32) Dunn, R; J Dispersion Sci Technol 1993, V14, P1 CAPLUS
- (33) Dunn, R; Proc Third Liquid Fuels Conf 1996, P95 CAPLUS
- (34) Dunn, R; Soc Automot Eng 1997, P133 CAPLUS
- (35) Dunn, R; Trans ASAE in press 2000, V43 CAPLUS
- (36) Dykstra, G; Thesis University of Illinois 1985
- (37) Einfalt, J; Trans ASAE 1985, V28, P70 CAPLUS
- (38) Engler, C; J Am Oil Chem Soc 1983, V60, P1592 CAPLUS
- (39) Foglia, T; J Liq Chromatogr Relat Technol 1997, V20, P1829 CAPLUS
- (40) Freedman, B; J Am Oil Chem Soc 1984, V61, P1215 CAPLUS
- (41) Freedman, B; J Am Oil Chem Soc 1984, V61, P1638 CAPLUS
- (42) Freedman, B; J Am Oil Chem Soc 1986, V63, P1370 CAPLUS
- (43) Gelbard, G; J Am Oil Chem Soc 1995, V72, P1239 CAPLUS
- (44) Geyer, S; Trans ASAE 1984, V27, P375 CAPLUS
- (45) Glassman, I; Combustion 3rd edn 1996
- (46) Goering, C; Final Report 1984, 59-2171-1-6-057-0
- (47) Goering, C; Proc International Winter Meeting of the ASAE 1987
- (48) Goering, C; Trans ASAE 1983, V26, P1602 CAPLUS
- (49) Gunstone, F; An Introduction to the Chemistry and Biochemistry of Fatty Acids and Their Glycerides 2nd edn 1967, P105
- (50) Gusmao, J; Catal Today 1989, V5, P533 CAPLUS
- (51) Harrington, K; Biomass 1986, V9, P1 CAPLUS
- (52) Holcapek, M; J Chromatogr A 1999, V858, P13 CAPLUS
- (53) Howell, S; ASTM Standardization News 1997, P16
- (54) Ito, K; J Colloid Sci 1964, V19, P152 CAPLUS
- (55) Kaieda, M; J Biosci Bioeng 1999, V88, P627 CAPLUS
- (56) Knothe, G; ACS Symp Ser 666, Fuels and Chemicals from Biomass 1997, P172 CAPLUS
- (57) Knothe, G; Inform 1996, V7, P827
- (58) Knothe, G; J Am Oil Chem Soc 1999, V76, P795 CAPLUS
- (59) Knothe, G; J Am Oil Chem Soc 2000, V77, P489 CAPLUS
- (60) Knothe, G; Soc Automot Eng 1997, Pl27 CAPLUS
- (61) Ladommatos, N; Fuel 1996, V75, P8 CAPLUS
- (62) Last, R; Soc Automot Eng 1995, P9 CAPLUS
- (63) Lee, I; J Am Oil Chem Soc 1995, V72, P1155 CAPLUS
- (64) Lee, I; J Am Oil Chem Soc 1996, V73, P631 CAPLUS
- (65) Litwinienko, G; Ind Eng Chem Res 2000, V39, P13 CAPLUS
- (66) Litwinienko, G; Ind Eng Chem Res 2000, V39, P7 CAPLUS
- (67) Litwinienko, G; J Am Oil Chem Soc 1999, V76, P655 CAPLUS
- (68) Mackay, R; Surfactant Science Series 1987, V23, P297 CAPLUS (69) McBain, M; Solubilization and Related Phenomena 1955, P153
- (70) McDonald, J; Soc Automot Eng 1995, P191 CAPLUS
- (71) Mills, G; J Inst Energy 1983, V56, P131 CAPLUS
- (72) Mittelbach, M; Energy Agric 1985, V4, P207 CAPLUS
- (73) Msipa, C; Trans ASAE 1983, V26, P1669 CAPLUS
- (74) Nelson, L; J Am Oil Chem Soc 1996, V73, P1191 CAPLUS
- (75) Nitske, W; Rudolf Diesel: Pioneer of the Age of Power 1965, P139
- (76) Nunes, P; Rev Inst Fr Pet 1986, V41, P421 CAPLUS
- (77) Owen, K; Automotive Fuels Handbook 1990, P292
- (78) Owen, K; Automotive Fuels Handbook 1990, P353
- (79) Peterson, C; J Am Oil Chem Soc 1983, V60, P1579 CAPLUS
- (80) Peterson, C; Trans ASAE 1987, V30, P28 CAPLUS

- (81) Peterson, C; Trans ASAE 1999, V42, P23
- (82) Plank, C; J Chromatogr, A 1995, V697, P461 CAPLUS
- (83) Pryde, E; Seminar 3, Vegetable Oil as Diesel Fuel 1983, P90
- (84) Purcell, D; J Am Oil Chem Soc 1996, V73, P381 CAPLUS
- (85) Roscoe, R; Brit J Appl Phys 1952, V3, P267
- (86) Rosen, M; Surfactants and Interfacial Chemistry 2nd edn 1989, P322
- (87) Ryan, T; J Am Oil Chem Soc 1984, V61, P1610 CAPLUS
- (88) Schmidt, A; Automobiltechn Z 1933, V36, P212 CAPLUS
- (89) Scholl, K; SAE Tech Paper Ser Paper No 930934 1993
- (90) Schwab, A; Fuel 1987, V66, P1372 CAPLUS
- (91) Schwab, A; J Am Oil Chem Soc 1988, V65, P1781 CAPLUS
- (92) Schwab, A; J Dispersion Sci Technol 1983, V4, P1 CAPLUS
- (93) Schwab, A; J Dispersion Sci Technol 1985, V6, P563 CAPLUS
- (94) Shimada, Y; J Am Oil Chem Soc 1999, V76, P789 CAPLUS
- (95) Simkovsky, N; Erdoel, Erdgas, Kohle 1999, V115, P317 CAPLUS
- (96) Simkovsky, N; Fett/Lipid 1998, V100, P534 CAPLUS
- (97) Stavinoha, L; Report, Oxidative and Thermal Stability Testing Methods for Biodiesel: Literature Summary 1998, P49
- (98) Stavinoha, L; Report, Oxidative and Thermal Stability Testing Methods for Biodiesel: Summary Overview 1998, Pl
- (99) Stavinoha, L; Soc Automot Eng 1999, P79 CAPLUS
- (100) Stumborg, M; Energy Biomass Wastes 1993, V16, P721 CAPLUS
- (101) Swain, E; J Inst Energy 2000, V73, P100 CAPLUS
- (102) Tat, M; J Am Oil Chem Soc 2000, V77, P285
- (103) Trathnigg, B; J Liquid Chromatogr 1990, V13, P95 CAPLUS
- (104) Van Gerpen, J; Proc International Winter Meeting of the ASAE 1999
- (105) Walton, J; Gas Oil Power 1938, V33, P167 CAPLUS
- (106) Watanabe, Y; J Am Oil Chem Soc 2000, V77, P355 CAPLUS
- (107) Wenzel, G; Fat Sci Technol 1995, V97, P475 CAPLUS
- (108) Wu, W; J Am Oil Chem Soc 1998, V75, P1173 CAPLUS
- (109) Zaher, F; Energy Sources 1993, V15, P499 CAPLUS
- (110) Ziejewski, M; J Am Oil Chem Soc 1983, V60, P1567 CAPLUS
- (111) Ziejewski, M; J Am Oil Chem Soc 1984, V61, P1620 CAPLUS
- (112) Ziejewski, M; SAE Tech Ser Paper No 860301 1986
- (113) Ziejewski, M; SAE Tech Ser Paper No 860302 1986

L7 ANSWER 9 OF 56 CAPLUS COPYRIGHT 2002 ACS

- AN 2001:184652 CAPLUS
- DN 134:328979
- TI Emission testing on a biodiesel produced from waste animal fats
- AU Koo, B. C. P.; Leung, D. Y. C.
- CS Department of Mechanical Engineering, The University of Hong Kong, Hong Kong, Peop. Rep. China
- Sustainable Energy and Environmental Technologies, Proceedings of the Asia-Pacific Conference, 3rd, Hong Kong, China, Dec. 3-6, 2000 (2001), Meeting Date 2000, 242-246. Editor(s): Hu, Xijun; Yue, Po Lock. Publisher: World Scientific Publishing Co. Pte. Ltd., Singapore, Singapore.
- CODEN: 69AZSS
- DT Conference LA English
- CC 52-1 (Electrochemical, Radiational, and Thermal Energy Technology)
 Section cross-reference(s): 45, 60
- AB Biodiesel is a clean-burning fuel made from renewable sources.

 Technologies to produce biodiesel from neat vegetable oils, have been developed elsewhere for sometimes and biodiesel fuel is com. available in several countries including USA and Germany. The feasibility of using waste cooking oil (animal fats/vegetable oils) as feedstock of biodiesel was studied by us in 1999. This study was initiated due to the large amt. of waste oil generated by local restaurants, posing a heavy burden on the trade as well as on the municipal wastewater treatment

facilities. Preliminary tests were conducted on a 240 HP Cummins bus engine and a 5-ton lorry. The results of the tests were encouraging - smoke and air pollutants were reduced without any significant power penalty. A larger scale and comprehensive study on the characteristics of biodiesel on various engines is currently undertaken. In this paper, results on a diesel generator with different biodiesel/diesel blending ratios were presented. Air pollutants, such as nitrogen oxides and carbon monoxide, were measured by a combustion analyzer. The power output and fuel consumption were also recorded during the measurement.

- ST air pollution exhaust biodiesel waste fat; animal waste fat restaurant transesterification biodiesel
- IT Fatty acids, uses

RL: NUU (Other use, unclassified); USES (Uses)
(Me esters; emission testing on a biodiesel produced from waste animal fats)

- IT Fats and Glyceridic oils, processes
 - RL: PEP (Physical, engineering or chemical process); PROC (Process) (animal, waste, transesterification of; emission testing on a biodiesel produced from waste animal fats)
- IT Diesel fuel substitutes

(biodiesel; emission testing on a biodiesel produced from waste animal fats)

IT Combustion

Transesterification

(emission testing on a biodiesel produced from waste animal

- IT Air pollution
 - (exhaust; emission testing on a biodiesel produced from waste animal fats)
- IT Fats and Glyceridic oils, processes
 - RL: PEP (Physical, engineering or chemical process); PROC (Process) (vegetable; emission testing on a biodiesel produced from waste animal fats)
- - RL: POL (Pollutant); OCCU (Occurrence)

(emission testing on a biodiesel produced from waste animal fats)

- RE.CNT 13 THERE ARE 13 CITED REFERENCES AVAILABLE FOR THIS RECORD
- (1) Ali, Y; Bioresource Technology 1995, V52, P237 CAPLUS
- (2) Ali, Y; Bioresource Technology 1995, V53, P243 CAPLUS
- (3) Graboski, M; Prog Energy Combust Sci 1998, V24, P125 CAPLUS
- (4) Ma, F; Bioresource Technology 1999, V69, P289 CAPLUS
- (5) Miller, N; Spill Science Technology Bulletin 1997, V4(1), P17 CAPLUS
- (6) Peterson, C; Applied Engineering in Agriculture 1997, V13(1), P71
- (7) Peterson, C; Biodiesel'94 1994
- (8) Peterson, C; Biomass and Bioenergy 1996, V10(5/6), P331 CAPLUS
- (9) Planning, Environment and Lands Bureau, Hong Kong Special Administrative Region Government; Clean air for Hong Kong
- (10) Police, G; Fuels for Automotive and Industrial Diesel Engines 1993, P139 CAPLUS
- (11) Schumacher, L; Bioresource Technology 1996, V57, P31 CAPLUS
- (12) Srivastava, A; Renewable and Sustainable Energy Reviews 2000, V4, P111 CAPLUS
- (13) Zhang, X; Trans ASAE 1998, V41(5), P1423 CAPLUS
- L7 ANSWER 10 OF 56 CAPLUS COPYRIGHT 2002 ACS

- AN 2001:145332 CAPLUS
- DN 134:165483
- TI Fuel for compression ignition engines

```
Andel, Miroslav
IN
PΑ
    Czech Rep.
    Czech Rep., 15 pp.
SO
    CODEN: CZXXED
DT
    Patent
LΑ
    Czech
TC
    ICM C10L001-08
     ICS C10L001-10; C10L001-14
     51-9 (Fossil Fuels, Derivatives, and Related Products)
     Section cross-reference(s): 52
FAN.CNT 1
                                          APPLICATION NO. DATE
                     KIND DATE
     PATENT NO.
                                          -----
     _____
    CZ 286005 B6 19991215 CZ 1993-1781 19930830
PΤ
     Fuel for diesel engines consists of 10-90 rape oil Me ester
AΒ
     (preferably 30-40) and 10-90 wt.% S-free middle petroleum distillate
     (preferably 60-70%). No harmful emissions are generated during
     combustion.
     alternate fuel diesel engine
ST
ΙT
     Fuels
        (alternative; for diesel engines)
ΙT
     Diesel fuel substitutes
        (biodiesel; rape oil Me ester)
     Diesel fuel
IT
        (blend with rape oil Me ester)
IT
     Fatty acids, uses
     RL: TEM (Technical or engineered material use); USES (Uses)
        (rape-oil, Me esters; rape oil Me ester as
        fuel for diesel engines)
     ANSWER 11 OF 56 CAPLUS COPYRIGHT 2002 ACS
L7
Full Text
     2000:903534 CAPLUS
AN
     134:268663
     The potential of using vegetable oil fuels as fuel for diesel engines
ΤI
     Altin, R.; Cetinkaya, S.; Yucesu, H. S.
ΑU
     Projects Coordination Unit, Ministry of Education, Ankara, 06500, Turk.
CS
     Energy Conversion and Management (2000), Volume Date 2001, 42(5), 529-538
SO
     CODEN: ECMADL; ISSN: 0196-8904
     Elsevier Science Ltd.
DΒ
     Journal
דת
     English
LA
     52-1 (Electrochemical, Radiational, and Thermal Energy Technology)
CC
     Section cross-reference(s): 45, 59
     Vegetable oils are produced from numerous oil seed crops. While all
AΒ
     vegetable oils have high energy content, most require some processing
     to assure safe use in internal combustion engines. Some of these oils
     already have been evaluated as substitutes for diesel fuels. The
     effects of vegetable oil fuels and their Me esters (raw sunflower
     oil, raw cottonseed oil, raw soybean oil and their Me esters,
     refined corn oil, distd. opium poppy oil and refined rapeseed oil)
     on a direct injected, four stroke, single cylinder diesel engine
     performance and exhaust emissions was investigated in this paper. The
     results show that from the performance viewpoint, both vegetable oils
     and their esters are promising alternatives as fuel for diesel engines.
     Because of their high viscosity, drying with time and thickening in cold
     conditions, vegetable oil fuels still have problems, such as flow,
     atomization and heavy particulate emissions.
     vegetable oil methyl ester diesel fuel; exhaust air pollution diesel
     vegetable oil; sunflower cottonseed soybean corn oil ester; opium
     poppy rapeseed oil diesel fuel
```

Diesel fuel substitutes

25

```
(biodiesel; potential of using vegetable oil fuels
        as fuel for diesel engines)
    Fatty acids, uses
ΤТ
    RL: NUU (Other use, unclassified); USES (Uses)
        (cottonseed-oil, Me esters; potential of using vegetable
        oil fuels as fuel for diesel engines)
    Air pollution
ΙT
        (exhaust; potential of using vegetable oil fuels as
        fuel for diesel engines)
    Fats and Glyceridic oils, uses
IT
    RL: NUU (Other use, unclassified); USES (Uses)
        (poppyseed; potential of using vegetable oil fuels
        as fuel for diesel engines)
    Atomizing (spraying)
IT
     Combustion
        (potential of using vegetable oil fuels as
        fuel for diesel engines)
ΙT
    Corn oil
     Cottonseed oil
     Rape oil
     RL: NUU (Other use, unclassified); USES (Uses)
        (potential of using vegetable oil fuels as
        fuel for diesel engines)
     Fatty acids, uses
IT
     RL: NUU (Other use, unclassified); USES (Uses)
        (rape-oil, Me esters; potential of using vegetable
        oil fuels as fuel for diesel engines)
     Fatty acids, uses
TТ
     RL: NUU (Other use, unclassified); USES (Uses)
        (soya, Me esters; potential of using vegetable oil
        fuels as fuel for diesel engines)
     Fatty acids, uses
ΙT
     RL: NUU (Other use, unclassified); USES (Uses)
        (sunflower-oil, Me esters; potential of using vegetable
        oil fuels as fuel for diesel engines)
     Fats and Glyceridic oils, uses
IT
     RL: NUU (Other use, unclassified); USES (Uses)
        (vegetable; potential of using vegetable oil fuels
        as fuel for diesel engines)
     630-08-0, Carbon monoxide, occurrence 10102-44-0, Nitrogen dioxide,
     occurrence
     RL: POL (Pollutant); OCCU (Occurrence)
        (potential of using vegetable oil fuels as
        fuel for diesel engines)
              THERE ARE 15 CITED REFERENCES AVAILABLE FOR THIS RECORD
RE.CNT 15
RE
(1) Altin, R; PhD Thesis, Gazi University, Institute of Science and Technology
(2) Anon; Icten Yanmali Motorlar-Muayene ve Deney Esaslari 1991, TS 1231
(3) Anon; Superstar diesel engine manual 1980
(4) Anon; Technical document of rapeseed oil 1999
(5) Cetinkaya, S; Gazi U Teknik Egitim Fakultesi, Docentlik Takdim Tezi 1994
 (6) Cetinkaya, S; Isi Bilimi ve Teknigi Dergisi (J Thermal Sci Technol) 1995
 (7) Doysan Yag Tic AS; Biochemical specifications of vegetable oils 1997
 (8) Fort, E; Vegetable Oil Fuels Proceedings of the International Conference on
    Plant and Vegetable Oils as Fuel, ASAE 1982
 (9) Goering, G; Trans of ASEA 1982
 (10) Hemmerlein, M; SAE Paper 1991, 910848
 (11) Schlick, M; ASAE 1988, V31, P5
 (12) Schumacher, L; http://stratsov.aq.uiuc.edu./~stratsoy/research/usb9.html
 (13) Shay, E; Diesel fuel from vegetable oils, status and opportunities 1993
```

- (14) Sinha, S; Diesel fuel alternative from vegetable oils 1997
- (15) Turkiye Istatistik Yilligi; TC Basbakanlik DIE Yayin 1999, 2240
- L7 ANSWER 12 OF 56 CAPLUS COPYRIGHT 2002 ACS

- AN 2000:712590 CAPLUS
- DN 133:254844
- TI Reuse of used edible oils/fats in the energetic-technological area. A method and its evaluation
- AU Suss, Ananta Andy Anggraini
- CS Weimar, Germany
- SO Fortschritt-Berichte VDI, Reihe 15: Umwelttechnik (1999), 219, I-III, V, VII-XIV, 1-193
 CODEN: FRUMFB; ISSN: 0178-9589
- PB VDI Verlag GmbH
- DT Journal; General Review
- LA German
- CC 52-0 (Electrochemical, Radiational, and Thermal Energy Technology)
 Section cross-reference(s): 17
- A discussion and review with 166 refs. In the development of alternative AB fuel sources, used cooking oils have gained a high value as raw material for biofuel prodn. Although used cooking oils seem as animal feedstuffs economically more attractive, their toxic components restrict their use in animal nutrition sectors. Therefore, their use in the energetic-tech. sectors offers an environmentally far more attractive form of disposal and discovers simultaneously renewable energy sources. Because of their tech. and phys. properties, used cooking oils can not be used as direct replacements for diesel fuel. The suitability of used cooking oil as a fuel for diesel engines can be improved by appropriate transesterification. The unknown compn. and varying quality of used cooking oils, however, cause some problems on their use as a primary material for methylester fuel prodn. To realize this concept, it is necessary to develop and to optimize a technol., which is able to convert the used cooking oils into high quality Me ester fuel. Through the developed transesterification technol., used cooking oil methylesters (AME) can be produced in a quality close to existing stds. without expensive purifn. steps of the ester. Used cooking oils were transesterified by reaction at temps. between 20 and 70°C, on normal pressure, without excess methanol and under basic conditions. The catalyst, potassium hydroxide, should be exactly measured to adapt the transesterification process. The content of free fatty acid of raw material should not be more than 10% and the upper limit of impurities like mineral oil (from fossil resources) is 7.5%. If AME is used at temps. over 20°C, the animal fat content of the raw material can be accepted till 30%. Fuel properties of AME are remarkably similar to diesel fuel. Thus AME is suitable as fuel for diesel engines and for heating systems. Its m.p., however, is so high, that it can be used only at relatively high temps. To overcome this problem, AME needs to be modified to keep it in liq. form under colder conditions. A simple redn. of m.p. can be achieved by blending it with diesel fuel. This can be approached also by adding fuel additives. Heating the fuel might promise a possible soln. of this problem too. Darkness, lower temps. and anaerobic storage are suggested to guarantee a const. quality of AME for long term. It is also recommended, that storage period should not be longer than one year. The comparison between AME and rapeseed oil and its derivate showed that AME prodn. is less expensive and gives better energy balance. The other advantage is that there are no repeated agricultural activities in the prodn. steps, so that N20-emissions from nitrogen decompn. are not produced. Just as rapeseed oil, the sulfur content of AME is basically zero. Therefore, no SO2-emission was obsd. during its burning in diesel engine and in a heating system. There was found also a redn. in particle emissions.

- review edible oil fat reuse biofuel biodiesel ST Diesel fuel substitutes IT (biodiesel; reuse of used edible oils/fats in energetic-technol.) IT Fuels (biofuels; reuse of used edible oils/fats in energetic-technol.) Diesel fuel substitutes IT Energy balance Recycling (reuse of used edible oils/fats in energetic-technol.) Edible oils ΤТ Fats and Glyceridic oils, uses RL: PEP (Physical, engineering or chemical process); TEM (Technical or engineered material use); PROC (Process); USES (Uses) (reuse of used edible oils/fats in energetic-technol.) THERE ARE 166 CITED REFERENCES AVAILABLE FOR THIS RECORD RE.CNT 166 (1) Ackermann, I; Perspektiven einer dezentralen Pflanzenolgewinnung Zeitschrift Landtechnik 1994, P49 (2) Ahbe, S; Methodik fur Okobilanzen Schriftenreihe Umwelt 1990, 133 (3) Ali, Y; Bioresource Technology 1994, V47, PS131 (4) Ali, Y; Bioresource Technology 1995, V52, PS185 (5) Ali, Y; Bioresource Technology 1995, V53, PS243 (6) Amtliche Sammlung Von Untersuchungsverfahren 35 Lmbg; L 13.00-6: Untersuchung von Lebensmitteln - Bestimmung der Peroxidzahl in Fetten und Olen 1991 (7) Anggraini, A; Energetische Einordnung von AME Zeitschrift Landtechnik 1998, V53(1), PS18 (8) Anggraini, A; Journal of Agriculture in the Tropics and Subtropics "Der Tropenlandwirt", Beiheft 1997, 60 (9) Anggraini, A; Proceedings of 10th European Conference and Technology Exhibition 1998 (10) Apfelbeck, R; Dissertation Technische Universitat Munchen 1989 (11) Backe, W; Rapsolbasische Druckubertragungsmedien; Aufgaben, Anforderungen, Stand der Technik RWTH Aachen 1995 (12) Baldauf, W; Verarbeitung von Pflanzenolen zu Kraftstoffen in Mineralol-Raffinerieprozessen VDI-Berichte 1994, 1126 (13) Barger, E; Tractor and Their Power Units 1963 (14) Batel, W; Grundl Landtechnik 1980, 4, PS40 (15) Batel, W; Grundl Landtechnik 1984, 5, PS205 (16) Becher, S; Biogene Festbrennstoffe als Alternative zu fossilen Brennstoffen - Vergleich anhand von Energie- und Stoffbilanzen 1997, 1828 (17) Beitz, W; Taschenbuch fur den Maschinenbau 1987 (18) Bhattaracharyya, S; J agric Engng Res 1994, V57, PS157 (19) Bockey, D; Bio-Ole:ein Entsorgungsproblem? UFOP 1995 (20) Bockisch, M; Nahrungsfette und Ole 1993 (21) Bokermann, R; Zeitschrift Landtechnik 1998, 1, P53 (22) Brenndorfer, M; Energetische Nutzung von Biomasse KTBL 1994 (23) Bundesministerium Fur Ernahrung Landwirtschaft Und Forsten; Agrarbericht der Bundesregierung 1998 1998 (24) Chaplin, J; Trans of ASAE 1987, V30(3), PS610 (25) Conneman, J; Fat Sci Technologie 1994, V96, PS536 (26) Conzelmann, R; Erfolgsfaktoren der Innovation am Beispiel Pflanzenolmotor,
- (26) Conzelmann, R; Erfolgsfaktoren der Innovation am Beispiel Pflanzenolmotor, Dissertation Europaische Hochschulschriften Reihe V: Volks- und Betriebswirtschaft 1995
- (27) Delitz, M; Agrartechnik 1990, P40
- (28) Deutsche Shell; http://www.deutsche-Shell.de/weltoe/prnzip.htm
- (29) Dgf-Einheitsmethoden; Abteilung F Fettbegleitstoffe 1968, F-I 5a
- (30) Din Deutsches Institut Fur Normung E V; DIN 10264: Bestimmung des Gehaltes

- an freien Fettsauren in Olen 1970
- (31) Din Deutsches Institut Fur Normung E V; DIN 10268: Bestimmung des Wassergehaltes und der fluchtigen Bestandteile 1970
- (32) Din Deutsches Institut Fur Normung E V; DIN 51558 Teil 1: Bestimmung der Neutralisation (Farbindikator-Titration) 1979
- (33) Din Deutsches Institut Fur Normung E V; DIN 51562 Teil 1: Messung der Viskositat mit dem Ubbelohde-Viskosimeter 1983
- (34) Din Deutsches Institut Fur Normung E V; DIN 51603 Teil 1: Mindestanforderungen Heizole EL 1988
- (35) Din Deutsches Institut Fur Normung E V; DIN 51757 Verfahren A: Bestimmung der Dichte 1984
- (36) Din Deutsches Institut Fur Normung E V; DIN 53241 Teil 1: Bestimmung der Jodzahl mit Wijs-Losung 1981
- (37) Din Deutsches Institut Fur Normung E V; DIN EN 28178 Teil 1: Messung der gasformigen Emission und der Partikelemission 1993
- (38) Din Deutsches Institut Fur Normung E V; DIN EN 28178 Teil 4: Prfzyklen fur verschiedene Motoranwendungen 1993
- (39) Din Deutsches Institut Fur Normung E V; DIN EN 590 Dieselkraftstoff:Mindestanforderungen und Prufverfahren 1993
- (40) Din Deutsches Institut Fur Normung E V; DIN ISO 3016: Bestimmung des Pourpoints 1982
- (41) Din Deutsches Institut Fur Normung E V; DIN Vornorm 51606 Dieselkraftstoff aus Fettsauremethylester (FAME): Mindestanforderungen 1997
- (42) Din Deutsches Institut Fur Normung E V; VDI-Richlinie 4600: Kumulierter Energieaufwand - Begriffe, Definitionen, Berechnungsmethoden Entwurf 1995
- (43) Din Deutsches Institut Fur Normung E V Und Buderus Heiztechnik Gmbh; Almanach fur Heizungstechnik DIN 4755 Teil 1: Olfeuerungsanlagen 1994
- (44) Din Deutsches Institut Fur Normung E V Und Buderus Heiztechnik Gmbh; Almanach fur Heizungstechnik DIN 4787 Teil 1: Olzerstaubungsbrenner 1994
- (45) Dinkelbach, W; Entscheidungsmodelle W de G 1982
- (46) Dohne, E; Pflanzenolmotoren KTBL Darmstadt 1989
- (47) Domschke, W; Einfuhrung in Operation Research 1991
- (48) Drake, F; Kumulierte Treibhausgasemissionen zukunftiger Energiesysteme 1996
- (49) Dreger, W; Sonderabfallbeseitigung 1977
- (50) Eichhorn, H; Landtechnik:Landwirtschaftliches Lehrbuch 4 1985
- (51) Engler, C; Liquid Fuels from Renewable Sources 1992
- (52) Frischknecht, R; Nationalen Energie-Forschungs-Fond NEFF 1995
- (53) Gerstenkorn, H; Dissertation Uni Gottingen 1993
- (54) Get-Ufop; Bio-Hydraulikole
- (55) Get-Ufop; Bio-Schmierstoffe
- (56) Get-Ufop; Biodiesel:Umweltauswirkungen 1995
- (57) Gruber, G; Sonnenenergie als Kraftstoff KTBL-Schriftenreihe 1992, 355
- (58) Hantsche, J; Ergebnisse des Anwendungsprojektes Pflanzenol Sachsen-Anhalt VDI-Berichte 1994, 1126
- (59) Hanusch, H; Nutzen-Kosten-Analyse 1994
- (60) Hartmann, H; Energie aus Biomasse 1994, P18
- (61) Hartweg, A; Erfahrungen eines Herstellers Fuchs Petrolub AG Oel + Chemie Mannheim 1995
- (62) Hess, T; FG Agrartechnik 1997
- (63) Heyland, K; Berichte uber Landwirtschaft 1979, VSH 195, PS15
- (64) Ihle, C; Heizungstechnik 1974
- (65) Ishii, Y; Transaction of the ASAE 1987, V30(3), PS2-6
- (66) Ishii, Y; Transaction of the ASAE 1987, V30(1), PS605
- (67) Jeromin, L; Offenlegungsschrift 1986, DE 3515403 A1
- (68) Junek, H; Patentschrift 1987, AT 386222 B
- (69) Jurisch, C; Pflanzenolgeeignete Dieselmotoren deutscher Hersteller VDI-Berichte 1994, 1126
- (70) Jurisch, C; Verwertung von pflanzlichem Altfett als Biogener Kraftstoff Vortrag auf dem 3 Symposium "Im Kreislauf der Natur - Naturstoffe fur die moderne Gesellschaft" 1995
- (71) Kanzler Und Co; Bratfett-Verarbeitung Groalmerode 1997

- (72) Kersting, R; Bericht zur Entsorgung von Fettabscheiderinhalten in Hessen:Situation, Handlungsbedarf Hessische Landesanstalt fur Umwelt Wiesbaden 1995
- (73) Kersting, R; Entsorgung von Altfetten in Hessen:Situation, Handlungsbedarf Hessische Landesanstalt fur Umwelt Wiesbaden 1996
- (74) Kijora, C; Unkonventionelle Futtermittel Proceedings Workshop von FAL Landbauforschung Volkenrode 1996
- (75) KleinhanB, W; Kosten-Nutzenanalyse:Rapsol im Nichtnahrungsmittelbereich Schriftenreihe des Bundesministers fur Ernahrung, Landwirtschaft und Forsten Reihe A: Angewandte Wissenschaft, Heft 10 1992
- (76) Kluppel, H; KEA versus Okoaudit/Okobilanz VDI-Workshop anlalich der Herausgabe von VDI 4600 1998
- (77) Knoepfel, I; Graue Energie: Energiebilanz von Energiesystemen Hochschulverlag AG an der ETH Zurich 1995
- (78) KoBmehl, S; Erfahrungen mit Kraftstoffen aus Rapsol fur Diesel-Personenkraftwagen Forschung Umwelt und Verkehr
- (79) Kohler, W; Biostatistik 1992
- (80) Konig, W; TESSOL der Dieselersatz fur Traktoren? Erste Einsatzerfahrungen aus der landwitschaftlichen Praxis KTBL-Bericht
- (81) Korber, R; Schmierstoffe und Hydraulikflussigkeiten aus Pflanzenolen fur Landmaschinen Forschungsberichte der Bundesanstalt fur Landtechnik Wieselburg 1991
- (82) Korus, R; Proceeding of 1st Biomass Conference of the Americas: Energy, Environment, Agriculture and Industry 1993, V2, P711
- (83) Kossmehl, S; Proceeding of 2nd European Motor Biofuels Forum 1996
- (84) Kraft, G; Lehrbuch der Heizungs-, Luftungs- und Klimatechnik Verlag Theodor Steinkopff 1976
- (85) Krause, R; Journal of Agriculture in the Tropics and Subtropics "Der Tropenlandwirt" 1992
- (86) Kreisel, R; Leistungs- und Emissionsverhalten des Biokraftstoffes Altfettmethylester im Vergleich zu Biodiesel (Pflanzenolmethylester) und zu Dieselkraftstoff Diplomarbeit Fachbereich Maschinenbau 1998
- (87) Kuhn, M; Unkonventionelle Futtermittel Proceedings Workshop von FAL Landbauforschung Volkenrode 1996
- (88) Kurz, A; Diplomarbeit 1987
- (89) Labor- Und Umwelttechnik; Unser Wissen fur die Umwelt Broschuren 1996
- (90) Laforgia, D; Bioresource Technology 1995, V51, PS53
- (91) Leifert, K; Dissertation Europaische Hochschulschriffen Reihe V: Volksund Betriebswirtschaft Peter Lang GmbH 1996
- (92) Lepper, H; Offenlegungsschrift 1984, DE 3319590 A1
- (93) Lepper, H; Offenlegungsschrift 1986, DE 3444893 A1
- (94) Lohrlein, H; Zeitschrift Landtechnik 1998, V53, PS304
- (95) Machold, W; Pilotprojekt Biodiesel 1991
- (96) Matsukura, T; Offenlegungsschrift 1981, DE 3107318 A1
- (97) Maurer, K; Zeitschrift Landtechnik 1991, P46
- (98) MeliB, M; RWE Energie Aktiengesellschaft Tagungsbericht der 16 Hochschultage Energie in Essen 1995
- (99) Meyer-Pittroff, R; Pflanzenole als regenerative Energietrager nationale und weltweite Perspektiven 1994, 1126
- (100) Mittelbach, M; Brennstoff Patentschrift 1989, AT 388743 B
- (101) Mittelbach, M; JAOCS 1988, V65(7), P1185 CAPLUS
- (102) Mittelbach, M; Liquid Fuels from Renewable Sources 1992
- (103) Mittelbach, M; Proceedings of 2nd European Motor Biofuel Forum 1996
- (104) Niehaus, R; Transactions of the ASAE 1986, V29(3), PS683
- (105) Nn; Qualitatsanforderungen an naturbelassene Pflanzenole fur die Verwendung als Kraftstoff Sitzung des LTV-Arbeitskreises "Dezentrale Pflanzenolgewinnung" 1996
- (106) Nn-A; Zeitschrift Landtechnik 1989, 2, P44
- (107) Nn-B; Top Agrar 1989
- (108) Nye, M; Preliminary Tests JAOCS 1983, V60(8), P1598 CAPLUS
- (109) Oechsner, H; Erhohung der Energieproduktion landwirtschaftlicher Biogasanlagen durch Zusatz von Speiseabfallen Tagungsband der Conference

- von CIGR- IV 1995
- (110) Onno, S; UFOP Sonderdruck aus Technische Uberwachung TU 37 1996, 1/2
- (111) Pak, M; Gundl Landtechnik 1987, 4, PS54
- (112) Pardun, H; Analyse der Nahrungsfette 1976
- (113) Patyk, A; Dungemittel Energie und Stoffstrombilanzen Friedr 1997
- (114) Peterson, C; Transaction of ASAE 1986, V29(5), PS1413
- (115) Potsch, E; Sekundarrohstoffe im Stoffkreislauf der Landwirtschaft Kongreband der VDLUFA 1996
- (116) Pudel, F; 1994, 1126
- (117) Reimann, C; Biokonversion von Glycerin zu 1,3-Propandiol mit immobilisierten Zellen Bundesforschungsanstalt fur Landwirtschaft (FAL) 1998
- (118) Reinhardt, G; Energie- und CO2-Bilanzierung nachwachsender Rohstoffe -Theoretische Grundlagen und Fallstudie Raps 2 Aufl 1993
- (119) Reinhardt, G; Ganzheitliche Bilanzierung von Biokraftstoffen im Vergleich zu konventionellen Kraftstoffen Jahrbuch der VDI-Energietechnik 1998
- (120) Reiser, W; Dissertation Universitat Hohenheim 1997
- (121) Richter, W; Energie aus der Landwirtschaft, Reststoffe und speziell produzierte Rohstoffe Tagungsbericht Bayerische Landesanstalt fur Tierzucht 1991
- (122) Sams, T; Tagungsband "1st International Colloqium FUELS, Technische Akademie Esslingen/TAE" 1997, PS391
- (123) Saykowski, F; Verschiedene Bewertungsmethoden im Lichte der ISO 14040 Umweltmanagement - Okobilanz VDI-Workshop anlalich der Herausgabe von VDI 4600 1998
- (124) Scharmer, K; Biodiesel:Energie- und Umweltbilanz Rapsolmethylester UFOP
- (125) Scharmer, K; Proceeding of 2nd European Motor Biofuels Forum 1996
- (126) Scharmer, K; Umwandlung von Pflanzenolen zu Methylund Ethylestern 1994,
- (127) Schliephake, D; BMFT/BML-Verbundprojekt Kraftstoff aus Raps In: VDI-Tagungsband:Pflanzenole als Kraftstoffe fur Fahrzeugmotoren und Blockheizkraftwerke 1994
- (128) Schroder, A; Proceedings Workshop von FAL Landbauforschung Volkenrode 1996
- (129) Schroder, A; Sekundarrohstoffe im Stoffkreislauf der Landwirtschaft Kongreband des VDLUFA 1996
- (130) Schwarzburger, H; Wasser im Sprit 1998, 34
- (131) Severin, K; Sekundarrohstoffe im Stoffkreislauf der Landwirtschaft Kongreband des VDLUFA 1996
- (132) Simon, A; Proceedings Workshop von FAL Landbauforschung Volkenrode 1996
- (133) Sims, R; Trans of ASAE 1985, V28(3), PS716
- (134) Statistisches, B; Mineralolwirtschaftwverband e V (MWV), Mineralol-Zahlen 1997 1998
- (135) Stout, B; Biomass Energy Profils FAO Bulletin 1983
- (136) Suttor, K; Grundl Landtechnik 1986, V11(41), PS468
- (137) Tanaka, Y; Offenlegungsschrift 1980, DE 3020612 A1
- (138) Tegtmeyer, R; Bilanzierung des energetischen In- und Outputs von konventioneller und okologischer Landbewirtschaftung am Beispiel eines Betriebes in der Hildersheimer Borde Diplomarbeit 1985
- (139) Thomas, A; Fette und Ole 1977
- (140) Traulsen, H; Top Agrar H 1 1993, PS88
- (141) Trenckmann, S; Chancen des Einsatzes von Pflanzenol als Kraftstoffsubstitut in Entwicklungslandern Diplomarbeit Universitat Gottingen 1985
- (142) Trent, W; US 2383632 1945 CAPLUS
- (143) Ullman; Enzyklopadie der technischen Chemie 1976
- (144) Umweltbundesamt; UBA Texte 1993
- (145) Umweltbundesamt Uba; UBA Texte 1995
- (146) Vellguth, G; Grundl Landtechnik 1982, 5
- (147) Vellguth, G; Pflanzenol als Dieselkraftstoff-Substitut Landbauforschung Volkenrode, 38 Jahrgang Heft 1 1988, PS12

- (148) Vellguth, G; Pflanzenolester als Kraftstoff fur Dieselmotoren 1990, V794,
- (149) Verein Deutscher Ingenieure Vdi; Kumulierter Energieaufwand 1996, P4600
- (150) Volker, P; Handbuch fur Heizungstechnik Buderus 1994
- (151) Von Bogunslaki, E; Strohdungung und Bodenfruchbarkeit DLG-Verlag Frankfurt 1977
- (152) Von Oheimb, R; Zeitschrift Landtechnik 1986, V2, P41
- (153) Walker, K; Proceeding of 2nd European Motor Biofuels Forum 1996
- (154) Weidmann, K; Einsatz von Kraftstoffen aus nachwachsenden Rohstoffen im VW/Audi Dieselmotor 1992, 1020
- (155) Wenzel, G; Zeitschrift Landtechnik 1996, V51(3), PS134
- (156) Widmann, B; Hydraulikole auf Pflanzenolbasis in Landmaschinen -Betriebserfahrungen und Praxishinweise 1995, 1211, PS251
- (157) Widmann, B; Verwendung von Rapsol zu Motortreibstoff und als Heizolersatz in technischer und umweltbezogener Hinsicht Landtechnik-Bericht Heft 15 1994
- (158) Widmann, B; http://www.tec.agrar.tu-muenchen.de
- (159) Wimmer, T; WO 9200268 1990 CAPLUS
- (160) Winner, C; Zuckerrubenbau 1982
- (161) Wintzer, D; Modellversuch Warme-/Stromerzeugung aus nachwachsenden Rohstoffen - Auswertung von 30 Machbarkeitstudien AFAS -Kernforschungszentrum Karlsruhe 1994
- (162) Wintzer, D; Technikfolgenabschatzung zum Thema Nachwachsende Rohstoffe Schriftenreihe des BML 1993
- (163) Worgetter, M; Pilotprojekt Biodiesel Teil 1 und 2 Forschungsberichte der Bundesanstalt fur Landtechnik 1991
- (164) Zaffaroni, E; Transaction of ASAE 1987, V3(2), PS265
- (165) Zangemeister, C; Nutzwertanalyse in der Systemtechnik 1976
- (166) Zweier, K; Dissertation Universitat Gottingen 1985
- L7 ANSWER 13 OF 56 CAPLUS COPYRIGHT 2002 ACS

- AN 2000:511642 CAPLUS
- DN 133:225280
- TI Characterization of new fuel qualities
- AU Nylund, Nils-Olof; Aakko, Paivi
- CS Technical Research Centre of Finland, Finland
- SO Society of Automotive Engineers, [Special Publication] SP (2000), SP-1545(State of Alternative Fuel Technologies 2000), 97-106 CODEN: SAESA2; ISSN: 0099-5908
- PB Society of Automotive Engineers
- DT Journal
- LA English
- CC 51-9 (Fossil Fuels, Derivatives, and Related Products) Section cross-reference(s): 52
- Many standardized tests for evaluating fuel properties have originally AΒ been designed for screening straight-run hydrocarbon products. In the case of fuels blended with new components or treated with additives, the traditional test methods may give misleading results. The objective of the work was to evaluate the correlation between the results of standardized testing and of the real-life serviceability of new diesel fuel qualities. Combustion properties, properties affecting exhaust emissions, low-temp. performance and diesel fuel lubricity were studied. The test fuel matrix comprised of typical conventional hydrocarbon diesel fuels, low-emission hydrocarbon fuels, rapeseed and tall oil esters and ethanol-blended diesel fuels. The base fuels were blended with a cetane improver additive and some fuels also with a cold flow improver additive. Combustion and emission tests were carried out with a heavy-duty bus engine and a diesel passenger car. A farm tractor engine was used for cold-start testing. The traditional cetane no. measurement described well ignition delay of the heavy-duty engine at low and medium loads, but was more suitable for hydrocarbon

fuels than for alternative diesel fuels. Cetane no. measurement overestimated the effect of cetane improver, esp. for biodiesels. HFRR tests show that esters are effective lubricity additives. The cold startability of blends contg. esters improved with cold flow additives. The ignition properties of ethanol blended diesel fuel improved significantly when ignition improver additive was used. standardized test diesel fuel substitute; rapeseed tall oil ester ST ethanol fuel Diesel fuel substitutes TΤ (biodiesel; characterization of substitute diesel fuel qualities) TΨ Cetane number Combustion Ignition (characterization of substitute diesel fuel qualities) IT Air pollution (exhaust; characterization of substitute diesel fuel qualities) Fatty acids, uses IT RL: NUU (Other use, unclassified); USES (Uses) (rape-oil, Me esters; characterization of substitute diesel **fuel** qualities) Fatty acids, uses TΨ RL: NUU (Other use, unclassified); USES (Uses) (tall-oil, Me esters; characterization of substitute diesel fuel qualities) 64-17-5, Ethanol, uses IT RL: NUU (Other use, unclassified); USES (Uses) (characterization of substitute diesel fuel qualities) 630-08-0, Carbon monoxide, occurrence * TT RL: POL (Pollutant); OCCU (Occurrence) (characterization of substitute diesel fuel qualities) ANSWER 14 OF 56 CAPLUS COPYRIGHT 2002 ACS L7 Full Text 2000:511635 CAPLUS AN DN 133:226873 TI Optimising tractor C1 engines for biodiesel operation Bouche, Thomas; Hinz, Michael; Pittermann, Roland; Herrmann, Martin ΑU WTZ fur Motoren- und Maschinenforschung Rosslau GmbH, Germany CS Society of Automotive Engineers, [Special Publication] SP (2000), SO SP-1545(State of Alternative Fuel Technologies 2000), 57-64 CODEN: SAESA2; ISSN: 0099-5908 Society of Automotive Engineers PΒ DT Journal LA English 59-3 (Air Pollution and Industrial Hygiene) CC Section cross-reference(s): 47, 51 This paper reports on test bed and field studies to adapt and optimize two AΒ John Deere tractor engines for fatty acid Me ester (biodiesel). Emissions were measured according to the international std. DIN EN ISO 8178-4, cycle C1, which is relevant for tractor engines. The results were compared to diesel fuel with and without optimization of the engine for biodiesel. It could be shown that total particulate emissions did not change much with biodiesel but there was a strong increase in the sol. org. fraction while soot strongly decreased simultaneously. Therefore, in order to take full advantage of biodiesel, the engines were also equipped with an oxidn. catalyst. Compared to diesel fuel operation of the engines with an oxidn. catalyst, the emissions of hydrocarbons, carbon monoxide, and particulates could be reduced with biodiesel, whereas

nitrogen oxides increased slightly. During a 600 h durability run and a tractor field test, no **fuel**-related problems occurred, and a final

```
engine inspection showed components still to be in an excellent condition.
    The results of engine oil analyses during both durability tests are
    presented.
    tractor engine optimization biodiesel operation emission control
ST
IT
        (John Deer; optimizing tractor C1 engines for biodiesel operation)
IT
    Fatty acids, uses
    RL: TEM (Technical or engineered material use); USES (Uses)
        (Me esters, biodiesel fuel; optimizing tractor C1 engines for
        biodiesel operation)
    Diesel fuel substitutes
IT
        (biodiesel; optimizing tractor C1 engines for biodiesel operation)
    Air pollution
IT
        (control; optimizing tractor C1 engines for biodiesel operation)
TТ
    Soot
        (emission of; optimizing tractor C1 engines for biodiesel
        operation)
ΙT
    Hydrocarbons, occurrence
     RL: POL (Pollutant); OCCU (Occurrence)
        (emission of; optimizing tractor C1 engines for biodiesel
        operation)
IT
    Air pollution
        (exhaust; optimizing tractor C1 engines for biodiesel operation)
     Standards, legal and permissive
TT
        (for exhaust emissions, compliance with; optimizing tractor
        C1 engines for biodiesel operation)
    Diesel engines
TΤ
     Exhaust particles (engine)
     Optimization
     Oxidation catalysts
        (optimizing tractor C1 engines for biodiesel operation)
     Internal combustion engines
TΤ
        (spark-ignition; optimizing tractor C1 engines for biodiesel
        operation)
                                            11104-93-1, Nitrogen oxide (NOx),
     630-08-0, Carbon monoxide, occurrence
IT
     occurrence
     RL: POL (Pollutant); OCCU (Occurrence)
        (emission of; optimizing tractor C1 engines for biodiesel
        operation)
              THERE ARE 24 CITED REFERENCES AVAILABLE FOR THIS RECORD
RE.CNT 24
(1) Anon; Zahlen aus der Mineralolwirtschaft 1999
(2) Hitchings, G; 1st Int Colloquium Fuels, Proceedings 1997, P213
(3) Kowalewiez, A; 21st CIMAC Congress 1995, Paper D 54
(4) Krahl, J; SAE 961847 1996
(5) Krahl, J; SAE 962096 1996
(6) Last, R; SAE 950054 1995
(7) Lowi, A; SAE 900710 1990
(8) May, H; MTZ 1998, V59, P112
(9) Nikanjam, M; SAE 942014 1994
(10) ORTECH International / Fossean Manufacturing Development; Biodiesel - An
    information kit 1995
(11) Palm, W; Fachtagung Biodiesel: Optimierungspotentiale und Umwelteffekte
    1998
(12) Poitrat, E; 1st Int Colloquium Fuels, Proceedings 1997, P369
(13) Prescher, K; Dieselmotorentechnik 1998, V98
(14) Reinhardt, G; VDI Berichte 1994, 1126, P169
(15) Ryan, T; SAE 941018 1994
(16) Sams, T; 1st Int Colloquium Fuels 1997
(17) Schafer, F; Die Verbrennungskraftmaschine Neue Folge 1997, V7
(18) Scharmer, K; Symposium Kraftstoffe aus Pflanzenol fur Dieselmotoren 1995
(19) Schumacher, L; Fachtagung Biodiesel: Optimierungs potentiale und
```

```
Umwelteffekte 1998
(20) Staat, F; SAE 950053 1995
(21) Strempel, H; MTZ 1994, V55(3), P174
(22) Ullman, T; SAE 941020 1994
(23) Weidmann, K; ATZ 97 1995, V5, P288
(24) Worgetter, M; Forschungsberichte der Bundesanstalt fur Landtechnik
    (LT2/87) 1991
    ANSWER 15 OF 56 CAPLUS COPYRIGHT 2002 ACS
L7
Full Text
    2000:433256 CAPLUS
AN
    133:61158
DN
    Lipid vesicle-based fuel additives and liquid energy sources
TΙ
    containing same
    Mathur, Rajiv
ΤN
    Igen, Inc., USA
PΑ
so
    U.S., 8 pp.
    CODEN: USXXAM
DT
    Patent
LA
    English
    ICM C10L001-14
IC
     ICS C10L001-32
NCL 044301000
    51-7 (Fossil Fuels, Derivatives, and Related Products)
CC
FAN.CNT 1
                  KIND DATE
                                       APPLICATION NO. DATE
     PATENT NO.
     _____
                                       US 1999-252546 19990219
    US 6080211
                    A 20000627
ÞΙ
    WO 2000049108
                    A1 20000824
                                       WO 2000-US4126 20000217
         W: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU,
            CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL,
            IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA,
            MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI,
            SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW, AM, AZ,
            BY, KG, KZ, MD, RU, TJ, TM
         RW: GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW, AT, BE, CH, CY, DE,
            DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, BF, BJ, CF,
            CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG
                     A1 20011205
                                       EP 2000-913511 20000217
     EP 1159377
         R: AT, BE, CH, DE, DK, ES, FR, GB, GR, IT, LI, LU, NL, SE, MC, PT,
            IE, SI, LT, LV, FI, RO
                                         JP 2000-599839
                                                          20000217
     JP 2002537438 T2 20021105
                     B1 20020416
                                                         20000626
                                         US 2000-602732
     US 6371998
                    A
W
PRAI US 1999-252546
                          19990219
                         20000217
     WO 2000-US4126
     Liq. energy sources, e.g., liq. fuels comprising lipid vesicles having
     fuel additives such as water are disclosed herein. The liq. energy
     sources, methods for prepn., and methods of enhancing engine performance
     disclosed herein employing the lipid vesicles result in enhanced fuel
     efficiency and/or lowered engine emissions. The invention further
     relates to liq. energy sources contg. such additives which further
```

comprise a polymeric dispersion assistant, which reduces the interfacial tension and coalescence of vesicles during dispersion process and storage, and thereby provide transparent looks to the liq. energy source. liq fuel lipid vesicle manuf ST

ΙT Fuels

> (alternative; lipid vesicle-based fuel additives and liq. energy sources contg. same)

Diesel fuel substitutes IT

(biodiesel; lipid vesicle-based fuel additives and liq. energy sources contg. same)

IT Fatty acids, uses

```
RL: MOA (Modifier or additive use); USES (Uses)
        (esters; lipid vesicle-based fuel additives and liq.
       energy sources contg. same)
    Alcohols, uses
    RL: MOA (Modifier or additive use); USES (Uses)
        (fatty; lipid vesicle-based fuel additives and liq.
        energy sources contg. same)
IT
    Diesel fuel
    Dispersion (of materials)
      Fuel additives
    Jet aircraft fuel
    Vesicles (colloidal)
    Waters
        (lipid vesicle-based fuel additives and liq. energy
        sources contg. same)
TΨ
    Glycosides
    Lipids, uses
    Phosphatidic acids
    Phosphatidylserines
    Soybean oil
    RL: MOA (Modifier or additive use); USES (Uses)
        (lipid vesicle-based fuel additives and liq. energy
        sources contg. same)
TΤ
    RL: TEM (Technical or engineered material use); USES (Uses)
        (lipid vesicle-based fuel additives and liq. energy
        sources contg. same)
IT
    RL: TEM (Technical or engineered material use); USES (Uses)
        (lipid vesicle-based fuel additives and liq. energy
        sources contg. same)
IT
    Fuels
        (liq.; lipid vesicle-based fuel additives and liq.
        energy sources contg. same)
IT
    Amines, uses
    RL: MOA (Modifier or additive use); USES (Uses)
        (oleylamines and stearylamines; lipid vesicle-based fuel
        additives and liq. energy sources contg. same)
TΤ
     Sterols
     RL: MOA (Modifier or additive use); USES (Uses)
        (phytosterols; lipid vesicle-based fuel additives and liq.
        energy sources contg. same)
     Fatty acids, uses
IT
     RL: MOA (Modifier or additive use); USES (Uses)
        (soya, Me esters; lipid vesicle-based fuel additives and liq.
        energy sources contg. same)
     50-23-7, Hydrocortisone 57-10-3, Palmitic acid, uses 57-11-4, Stearic
IT
     acid, uses 57-88-5, Cholesterol, uses 57-88-5D, Cholesterol, derivs.
     64-17-5, Ethanol, uses 94-13-3, Propyl paraben 99-76-3, Methyl paraben
     108-10-1, Methyl isobutyl ketone 112-80-1, Oleic acid, uses 124-28-7,
     Dimethylstearyl amine 143-02-2, Cetyl sulfate 143-07-7, Lauric acid,
           302-01-2, Hydrazine, uses 1323-39-3, Propylene glycol stearate
     1323-83-7, Glycerol distearate 2197-63-9, Dicetyl phosphate
                                                       25618-55-7,
     Hydrogen peroxide, uses 9005-00-9, STEARETH-10
     Polyglycerol 27195-16-0, Sucrose distearate 27638-00-2, Glyceryl
     dilaurate 106392-12-5, Polyoxyethylene-polyoxypropylene block copolymer
     RL: MOA (Modifier or additive use); USES (Uses)
        (lipid vesicle-based fuel additives and liq. energy
        sources contq. same)
              THERE ARE 22 CITED REFERENCES AVAILABLE FOR THIS RECORD
RE.CNT 22
(1) Crawford; US 5090966 1992 CAPLUS
```

```
(2) Feuerman; US 4158551 1979 CAPLUS
(3) Hayes; US 4666547 1987
(4) Hayes; US 4684372 1987 CAPLUS
(5) Hayes; US 4793826 1988 CAPLUS
(6) Hayes; US 14618348 1990
(7) Krivohlavek; US 5505877 1996 CAPLUS
(8) Mathur; US 5643600 1997 CAPLUS
(9) Mezei; US 4485054 1984 CAPLUS
(10) Redziniak; US 4508703 1985 CAPLUS
(11) Rivas; US 5725609 1998 CAPLUS
(12) Schwab; US 5669938 1997 CAPLUS
(13) Scifoni; US 4499267 1985 CAPLUS
(14) Serres; US 4307012 1981 CAPLUS
(15) Smith; US 4059411 1977 CAPLUS
(16) Song; US 5433757 1995 CAPLUS
(17) Wallach; US 4911928 1990 CAPLUS
(18) Wallach; US 5147723 1992 CAPLUS
(19) Wallach; US 5160669 1992 CAPLUS
(20) Wallach; US 5474848 1995 CAPLUS
(21) Wallach; US 5628936 1997 CAPLUS
(22) Yiournas; US 4895452 1990 CAPLUS
    ANSWER 16 OF 56 CAPLUS COPYRIGHT 2002 ACS
L7
Full Text
     2000:410393 CAPLUS
AN
DN
    133:19936
    Fuel for compression ignition engines
TI
    Andel, Miroslav
IN
PA
    Czech Rep.
SO
    Czech Rep., 24 pp.
     CODEN: CZXXED
DT
    Patent
LA
    Czech
     ICM C10L001-08
     ICS C10L001-18; C10L001-16
     51-9 (Fossil Fuels, Derivatives, and Related Products)
     Section cross-reference(s): 52
FAN.CNT 1
                    KIND DATE
                                         APPLICATION NO. DATE
     PATENT NO.
     PATENT NO.
                                          ______
    CZ 285470
                     B6 19990811
                                         CZ 1994-762
                                                         19940331
PΤ
     Fuel for diesel engines consists of 10-90 (preferably 30-40) rapeseed
AB
     oil Me ester and 10-90 wt.% (preferably 60-70%) petroleum fraction with
     a mean distn. temp. of 200.4° and low contents of S and arom.
     compds. The fuel is bio-degradable and does not generate harmful
     emissions during combustion.
     diesel fuel rape oil methyl ester
st
TT
     Diesel fuel
        (modified with rapeseed oil Me ester)
     Fatty acids, uses
IT
     RL: TEM (Technical or engineered material use); USES (Uses)
        (rape-oil, Me esters; in fuel for compression
        ignition engines)
     ANSWER 17 OF 56 CAPLUS COPYRIGHT 2002 ACS
L7
Full Text
AN 2000:400052 CAPLUS
DN
     133:47990
     Energy consumption and exhaust emissions in mechanized timber
ΤI
     harvesting operations in Sweden
ΑU
     Athanassiadis, D.
     Department of Silviculture, Faculty of Forestry, Division of Forest
CS
```

Technology, Swedish University of Agricultural Sciences, Umea, 90183,

- SO Science of the Total Environment (2000), 255(1-3), 135-143 CODEN: STENDL; ISSN: 0048-9697
- PB Elsevier Science Ireland Ltd.
- DT Journal
- LA English
- CC 59-2 (Air Pollution and Industrial Hygiene)
- The study presents an estn. of the energy input and the amt. of AB emissions to air due to fuel, chainsaw and hydraulic oil consumption by heavy duty diesel engine vehicles operating in forest logging operations in Sweden. Exhaust concns. are given for carbon dioxide, carbon monoxide, nitrogen oxides, hydrocarbons and particulate matter. Three fuel types (rapeseed Me ester, environmental class 1 and environmental class 3 diesel fuels) and two types of lubricating base oil (mineral- and vegetable-based) were examd. Energy input per unit of timber prodn. (m3ub) was 82 MJ, 11% of which was due to energy consumption during the prodn. phase of the fuel. Emissions during the whole life cycle of the fuels and the base oils are included in the study. The highest CO2 and NOx emissions occurred when rapeseed Me ester was used as fuel together with rapeseed as base oil for chainsaw and hydraulic oil. The highest HC and CO emissions occurred when environmental class 3 diesel fuel was used.
- ST timber harvesting energy consumption exhaust emission
- IT Exhaust gases (engine)

(diesel; energy consumption and exhaust emissions

in mechanized timber harvesting in Sweden)

IT Diesel fuel

Energy

Lubricating oils

Wood

(energy consumption and exhaust emissions in mechanized timber harvesting in Sweden)

IT Hydrocarbons, occurrence

RL: POL (Pollutant); OCCU (Occurrence)

(energy consumption and exhaust emissions in mechanized timber harvesting in Sweden)

IT Fatty acids, uses

RL: NUU (Other use, unclassified); USES (Uses)

(rape-oil, Me esters; energy consumption and

exhaust **emissions** in mechanized timber harvesting in Sweden)
IT 124-38-9, Carbon dioxide, occurrence 630-08-0, Carbon monoxide,

occurrence 11104-93-1, Nitrogen oxide, occurrence

RL: POL (Pollutant); OCCU (Occurrence)

(energy consumption and exhaust emissions in mechanized timber harvesting in Sweden)

RE.CNT 34 THERE ARE 34 CITED REFERENCES AVAILABLE FOR THIS RECORD RE

- (1) Almqvist, A; Fakta-Teknik 1985, V13, P1
- (2) Anon; Luftfororeningar fran arbetsfordon. Handlingslinjer Rapport 3756 [in Swedish] 1990, P52
- (3) Anon; Skogsstatistisk arsbok. (Yearbook of forestry) [in Swedish, with English abstract] 1999, P348
- (4) Arnas, P; Livscykelanalys av drivmedel [in Swedish, with English abstract] 1997, V5, P89
- (5) Athanassiadis, D; J Forest Eng 1999, V10(1), P59
- (6) Axelsson, S; Int J Indust Ergon 1990, V5, P267
- (7) Bartz, W; Tribol Int 1998, V31(1-3), P35 CAPLUS
- (8) Berg, S; EFI Proceedings No 8 1995, P53
- (9) Boustead, I; Report for the European Centre for Plastics in the Environment
- (10) Braddock, J; International Congress and Exposition, Society of Automotive

Engineers 1986, P39

- (11) Burrows, C; The Sixth Scandinavian International Conference on Fluid Power, SICFP '99 1999
- (12) Eavis, R; Industrial Crops and Products Conference 1999
- (13) Ekelund, M; Projektrapporter ALTD-92/4 1992, P179
- (14) Furuholt, E; Resour Conserv Recyc 1995, V14, P251
- (15) Gragg, K; MTC Report 98/9 1998, P26
- (16) Gragg, K; Report 6806 1999, P14
- (17) Gragg, K; Report 9209B 1994, P44
- (18) Hansson, P; Int J LCA 1999, V4(4), P202 CAPLUS
- (19) Karjalainen, T; Forestry 1996, V69(3), P215
- (20) Kassfeldt, E; Wear 1997, V207, P41 CAPLUS
- (21) Lauhanen, R; Teho 1998, V4, P32
- (22) Lenner, M; Meddelande Nr 718 [in Swedish] 1993, P48
- (23) Marby, A; KTH-Ingenjorsskolan [in Swedish, with English abstract] 1999, P35
- (24) Peterson, C; Biomass Bioenerg 1998, V14(2-3), P91
- (25) Puranen, A; Environ Int 1992, V18, P467 CAPLUS
- (26) Ragnarsson, J; Report M4720301.122 [in Swedish] 1994, P102
- (27) Remmele, E; Landtechnik 1997, V52(3), P136
- (28) Rosner, G; Diesel fuel and exhaust emissions. Environmental health criteria 171 1996, P389
- (29) Sambo, S; Technical note TN-259 1997, P4
- (30) Schumacher, L; Fueling diesel engines with esterified soybean oil project update 1993, ASAE paper no MC93-101, P49085
- (31) Statistics Sweden; Statistiska meddelanden, Mi 18 SM 9901 [in Swedish, with English abstract] 1999, P24
- (32) Stripple, H; En studie av Ecrisprojektet, Rapport B1251 [in Swedish, with English abstract] 1997, P52
- (33) Viktor, T; Rapport B1267 [in Swedish] 1997, P17
- (34) Wightman, P; Second International Conference. LCA in Agriculture, Agro-Industry and Forestry 1998, P35

L7 ANSWER 18 OF 56 CAPLUS COPYRIGHT 2002 ACS

- AN 1999:792645 CAPLUS
- DN 132:66380
- TI Sunflower methyl ester as a fuel for automobile diesel engines
- AU Moreno, F.; Munoz, M.; Morea-Roy, J.
- CS Laboratorio de Motores, Departamento de Ingenieria Mecanica, Centro Politecnico Superior, Universidad de Zaragoza, Maria de Luna, Zaragoza, 50015, Spain
- SO Transactions of the ASAE (1999), 42(5), 1181-1185 CODEN: TAAEAJ; ISSN: 0001-2351
- PB American Society of Agricultural Engineers
- DT Journal
- LA English
- CC 51-9 (Fossil Fuels, Derivatives, and Related Products) Section cross-reference(s): 45, 52, 59
- Results were presented for tests on an automobile diesel engine running on sunflower oil Me ester (SME), either pure and mixed (25-75 wt.%) with diesel fuel. Engine test bench studies were carried out in order to obtain comparison measurements of torque, power, specific fuel consumption, and pollutant emissions. No noticeable power loss was obsd., compared with pure diesel fuel, for fuel mixts. contg. 25-75 wt.% SME, although a slight loss (1.5%) of power was obsd. with pure SME. Emissions of unburned hydrocarbons decreased when using pure SME or SME mixts.; the NOx emissions decreased when using SME-diesel fuel mixts. up to 85% SME. NOx emissions were 5% higher (compared with pure diesel fuel) when pure SME was used.
- ST sunflower oil methyl ester diesel fuel; hydrocarbon emission sunflower oil methyl ester diesel; nitrogen oxide sunflower oil methyl

ester diesel

IT Hydrocarbons, occurrence

RL: POL (Pollutant); OCCU (Occurrence)

(emissions; engine test bench studies of automobile diesel engines burning sunflower oil Me ester substitute)

IT Diesel fuel substitutes

(engine test bench studies of automobile diesel engines burning sunflower oil Me ester substitute)

IT Combustion

(of sunflower oil Me esters; engine test bench studies of automobile diesel engines burning sunflower oil Me ester substitute)

IT Fatty acids, uses

RL: NUU (Other use, unclassified); RCT (Reactant); RACT (Reactant or reagent); USES (Uses)

(sunflower-oil, Me esters, diesel fuel substitute; engine test bench studies of automobile diesel engines burning sunflower oil Me ester substitute)

IT 630-08-0, Carbon monoxide, occurrence 11104-93-1, Nitrogen oxide (NOx), occurrence

RL: POL (Pollutant); OCCU (Occurrence)

(emissions; engine test bench studies of automobile diesel engines burning sunflower oil Me ester substitute)

RE.CNT 10 THERE ARE 10 CITED REFERENCES AVAILABLE FOR THIS RECORD RE

- (1) Anon; Official J European Union 1980, L 375/36
- (2) Anon; Official J European Union 1987, L 36/33-61
- (3) Anon; Official J European Union 1988, L 92/50-58
- (4) Devel, J; Comptes rendus de L'academe D'agriculture de France 1992, V78(3), P3 CAPLUS
- (5) Graboski, M; Prog Energy Combust Sci 1998, V24(2), P125 CAPLUS
- (6) Guibet, J; Carburants et Moteurs 1987
- (7) Kaufman, K; Transactions of the ASAE 1984, V27(6), P1626 CAPLUS
- (8) Maxwell, T; SAE Book 1995
- (9) Schumacher, L; Proc 3rd Liquid Fuel Conference 1996
- (10) Zhang, Q; ASAE Paper No 88-1562 1988
- L7 ANSWER 19 OF 56 CAPLUS COPYRIGHT 2002 ACS

- AN 1999:630353 CAPLUS
- DN 131:261738
- TI Vegetable oils for biofuels versus surfactants. An ecological comparison for energy and greenhouse gases
- AU Patel, Martin; Reinhardt, Guido A.; Zemanek, Guido
- CS Fraunhofer Institute Systems Innovation Research, Karlsruhe, D-76139, Germany
- SO Fett/Lipid (1999), 101(9), 314-320 CODEN: FELIFX; ISSN: 0931-5985
- PB Wiley-VCH Verlag GmbH
- DT Journal
- LA English
- CC 59-2 (Air Pollution and Industrial Hygiene)
 Section cross-reference(s): 46, 52
- The use of vegetable oils as energy carriers and for the prodn. of chems. is compared. The bio-based energy carriers analyzed are rapeseed oil, rapeseed oil Me ester, and palm oil Me ester, all of which can be used as substitutes for diesel fuel. The chems. studied are surfactants. Surfactants can be produced from plant-based feedstocks (oleochem. surfactants) and from petrochems. The various options are studied with regard to two ecol. indicators, i.e. the consumption of finite energy resources and the global warming potential. Plant-based sources show clear advantages when compared with their fossil

```
counterparts. The transesterified types of biofuels are more advantageous
     than pure vegetable oils. The conservation of finite energy and redn.
     in emissions of greenhouse gases are higher if vegetable oils are used
     as a feedstock to produce oleochem. surfactants compared to their use as
     biofuels. Comprehensive life-cycle analyses must be carried out in order
     to det. whether these results can also be applied to other ecol.
     indicators. The results support developing strategic goals for bio-based
     feedstocks, including quantity and cost targets.
     environmental impact vegetable oil biofuel comparison surfactant;
ST
     energy conservation greenhouse effect vegetable oil biofuel surfactant
IT
     Sulfonates
     RL: NUU (Other use, unclassified); PRP (Properties); USES (Uses)
        (alkanesulfonates, secondary; ecol. comparison of vegetable
        oils for biofuels vs. surfactants regarding energy
        conservation and greenhouse gases)
TΨ
     Fuels
        (biofuels; ecol. comparison of vegetable oils for biofuels
        vs. surfactants regarding energy conservation and greenhouse
        gases)
     Diesel fuel substitutes
ΙT
       Energy conservation
     Greenhouse gases
     Surfactants
        (ecol. comparison of vegetable oils for biofuels vs.
        surfactants regarding energy conservation and greenhouse
        gases)
IT
     Sulfates, uses
     RL: NUU (Other use, unclassified); PRP (Properties); USES (Uses)
        (ecol. comparison of vegetable oils for biofuels vs.
        surfactants regarding energy conservation and greenhouse
        gases)
IT
     Rape oil
     RL: PRP (Properties); TEM (Technical or engineered material use); USES
        (ecol. comparison of vegetable oils for biofuels vs.
        surfactants regarding energy conservation and greenhouse
        gases)
TT
     Fatty acids, uses
     RL: PRP (Properties); TEM (Technical or engineered material use); USES
        (esters, palm oil, Me esters; ecol. comparison of vegetable
        oils for biofuels vs. surfactants regarding energy
        conservation and greenhouse gases)
     Alcohols, uses
IT
     RL: NUU (Other use, unclassified); PRP (Properties); USES (Uses)
        (ethoxylated; ecol. comparison of vegetable oils for biofuels
        vs. surfactants regarding energy conservation and greenhouse
        gases)
IT
     Climate
        (greenhouse effect; ecol. comparison of vegetable oils for
        biofuels vs. surfactants regarding energy conservation and
        greenhouse gases)
     Fats and Glyceridic oils, uses
TT
     RL: PRP (Properties); TEM (Technical or engineered material use); USES
        (vegetable; ecol. comparison of vegetable oils for biofuels
        vs. surfactants regarding energy conservation and greenhouse
     98-11-3D, Benzenesulfonic acid, alkyl derivs., linear, uses
     RL: NUU (Other use, unclassified); PRP (Properties); USES (Uses)
        (ecol. comparison of vegetable oils for biofuels vs.
        surfactants regarding energy conservation and greenhouse
```

gases)

IT 74-82-8, Methane, occurrence 124-38-9, Carbon dioxide, occurrence
10024-97-2, Nitrogen oxide (N2O), occurrence

RL: POL (Pollutant); OCCU (Occurrence)

(ecol. comparison of vegetable oils for biofuels vs.

surfactants regarding **energy** conservation and greenhouse gases)

IT 192391-56-3, RME

RL: PRP (Properties); TEM (Technical or engineered material use); USES (Uses)

(ecol. comparison of vegetable **oils** for biofuels vs. surfactants regarding **energy** conservation and greenhouse gases)

RE.CNT 21 THERE ARE 21 CITED REFERENCES AVAILABLE FOR THIS RECORD

- (1) Anon; Personliche Mitteilung vom P Ungeheuer 1998
- (2) Anon; Personliche Mitteilung von Dr Hirsinger 1999
- (3) Ast, A; Einsatz von gentechnisch veranderten Organismen zur Verringerung von Umweltbelastungen 1998
- (4) Blachownia Institute of Heavy Organic Synthesis (ICSO); http://www.eureka.be/cgi-bin/query20.sh
- (5) Borken, J; Basisdaten zur okologischen Bilanzierung: Einsatz von Nutzfahrzeugen in Transport 1999
- (6) Dierker, M; 52nd International Congress and Expo 1998, V100(8), P371
- (7) European Commission; Communication from the Commission (COM (97) 599 final)
- (8) Hirsinger, F; Tenside Surf Det 1995, V32(2), P84
- (9) Houghton, J; Climate Change 1995. The Science of Climate Change 1996
- (10) Kaltschmitt, M; Nachwachsende Energietrager: Grundlagen, Verfahren, Okologische Bilanzierung 1997
- (11) Kopf, N; Seminararbeit am Engler-Bunte-Institut (Bereich Gas, Erdol und Kohle) 1999
- (12) Menrad, K; 5 Freisinger Forum: Zwischen Tradition und Fortschritt Was bringt die Biotechnologie fur die stoffliche Verwertung der Biomassse? 1998
- (13) Patel, M; Angenommen von Resources, Conservation and Recycling 1998
- (14) Patyk, A; 20 Jahre ifeu-Institut 1998
- (15) Patyk, A; Dungemittel Energie- und Stoffstrombilanzen 1997
- (16) Reinhardt, G; 20 Jahre ifeu-Institut 1998
- (17) Reinhardt, G; Energie-und CO2-Bilanzierung nachwachsender Rohstoffe: Theoretische Grundlagen und Fallstudie Raps. 2 Aufl 1993
- (18) Schwarzburger, H; Rohstoffe liefert der Acker Chemie: Ole heimischer Pflanzen als Grundstoff fur Tenside 1998, 40, P31
- (19) Stalmans, M; Tenside Surf Det 1995, V32(5), P84
- (20) Theiss, A; Analysis of the material flows and CO2 emissions associated with surfactant production in Germany 1997
- (21) US Department of Energy (DOE); DOE/GO-10098-3385 1998

L7 ANSWER 20 OF 56 CAPLUS COPYRIGHT 2002 ACS

- AN 1999:352381 CAPLUS
- DN 131:90083
- TI Conversion of vegetable oils to diesel fuel
- AU Kotowski, Wlodzimierz; Fechner, Wolfgang
- CS Inst. Ciezkiej Syntezy Org., Politech. Opolska, Kedzierzyn-Kozle, Pol.
- SO Karbo (1999), 44(2), 69-74 CODEN: KARBFZ
- PB Wiadomosci Gornicze Sp. z o.o.
- DT Journal
- LA Polish
- CC 52-1 (Electrochemical, Radiational, and Thermal Energy Technology) Section cross-reference(s): 45
- AB A technol. for processing rape oil into an ecol. oil for Otto engines

has been described. It was characterized several operations concerning the processing of gas oil of petroleum origin as well as the processing of vegeteable oil into an ecol. engine fuel. Energy balances for these processes and accompanied emissions of toxic substances into atm. have been presented. rape oil transesterification methanol diesel fuel; vegeteable oil

ST transesterification methanol diesel fuel

Transesterification IT

(Me; conversion of vegetable oils to diesel fuel)

Diesel fuel substitutes IT

(biodiesel; conversion of vegetable oils to diesel fuel)

Diesel fuel IT

(conversion of vegetable oils to diesel fuel)

Fatty acids, uses TΤ

RL: NUU (Other use, unclassified); PNU (Preparation, unclassified); PREP (Preparation); USES (Uses)

(rape-oil, Me esters; conversion of vegetable oils to diesel fuel)

IT

RL: PEP (Physical, engineering or chemical process); PROC (Process) (transesterification of; conversion of vegetable oils to diesel fuel)

Fats and Glyceridic oils, processes TT

RL: PEP (Physical, engineering or chemical process); PROC (Process) (vegetable, transesterification of; conversion of vegetable oils to diesel fuel)

TТ Fatty acids, uses

RL: NUU (Other use, unclassified); PNU (Preparation, unclassified); PREP (Preparation); USES (Uses)

(vegetable-oil, Me esters; conversion of vegetable oils to diesel fuel)

67-56-1, Methanol, uses

RL: NUU (Other use, unclassified); USES (Uses) (transesterification with; conversion of vegetable oils to diesel fuel)

ANSWER 21 OF 56 CAPLUS COPYRIGHT 2002 ACS L7

- AN 1999:327609 CAPLUS
- 131:48436 DN
- Effects of rapeseed oil fuel properties on exhaust emissions of a TΙ swirl-chamber diesel engine
- Hamasaki, Kazunori; Ohsako, Takanobu; Kinoshita, Eiji; Takasaki, Koji ΑU
- Faculty of Engineering, Kagoshima University, Kagoshima-shi, Korimoto, 890-0065, Japan
- Nippon Kikai Gakkai Ronbunshu, B-hen (1999), 65(631), 1146-1151 SO CODEN: NKGBDD; ISSN: 0387-5016
- Nippon Kikai Gakkai PB
- DTJournal
- Japanese LA
- 59-3 (Air Pollution and Industrial Hygiene) CC Section cross-reference(s): 45
- Due to the increasing interest in the CO2 problem, the request for AΒ alternative fuels from regenerated vegetable energy sources is increasing. The present work describes the results of expts. using rapeseed oil, emulsified rapeseed oil, rapeseed oil Me ester, and gas oil in a swirl-chamber diesel engine. The results show that the viscosity of rapeseed oil Me ester is a little higher than that of gas oil and that the smoke concn. with rapeseed oil Me ester is about 50% lower than that with gas oil. Furthermore, NOx and smoke concns. with emulsified rapeseed oil are lower than those with gas oil and energy

```
consumption is similar to that in the case of operation with gas oil and
    rapeseed oil Me ester.
    diesel engine exhaust fuel rapeseed oil Me ester
ST
TT
    Exhaust gases (engine)
        (diesel; effects of rapeseed oil fuel properties on
        exhaust emissions of a swirl-chamber diesel engine)
TT
    Diesel fuel
    Exhaust particles (engine)
    Gas oils
        (effects of rapeseed oil fuel properties on exhaust
        emissions of a swirl-chamber diesel engine)
ፐጥ
    Rape oil
    RL: NUU (Other use, unclassified); PRP (Properties); TEM (Technical or
     engineered material use); USES (Uses)
        (effects of rapeseed oil fuel properties on exhaust
        emissions of a swirl-chamber diesel engine)
    Fatty acids, uses
IT
     RL: NUU (Other use, unclassified); PRP (Properties); TEM (Technical or
     engineered material use); USES (Uses)
        (rape-oil, Me esters; effects of rapeseed oil
        fuel properties on exhaust emissions of a
        swirl-chamber diesel engine)
     124-38-9, Carbon dioxide, formation (nonpreparative)
     Nitrogen oxide, formation (nonpreparative)
     RL: FMU (Formation, unclassified); POL (Pollutant); FORM (Formation,
     nonpreparative); OCCU (Occurrence)
        (effects of rapeseed oil fuel properties on exhaust
        emissions of a swirl-chamber diesel engine)
    ANSWER 22 OF 56 CAPLUS COPYRIGHT 2002 ACS
L7
Full Text
AN 1999:318266 CAPLUS
   130:340543
DN
    Methyl esters of sunflower oil as fuels. Alternative to
     petroleum-derived diesel fuel
     Vicente, G.; Martinez, M.; Aracil, J.
ΑU
     Dpto. de Ingenieria Quimica. Facultad de Ciencias Quimicas. Universidad
CS
     Complutense de Madrid, Spain
     Ingenieria Quimica (Madrid) (1999), 31(355), 153-159
SO
     CODEN: INQUDI; ISSN: 0210-2064
PB
     Ingenieria Quimica, S.A.
DT
     Journal
LA
     Spanish
     52-1 (Electrochemical, Radiational, and Thermal Energy Technology)
     Section cross-reference(s): 51, 59
     The properties, combustion characteristics, advantages, and prodn.
AΒ
     technologies involved in the use of Me esters of sunflower oil fatty
     acids as alternatives to diesel fuel are discussed. The oil is
     extd. from the seeds, refined and subjected to transesterification. The
     combustion properties of the biodiesel are compared to those of diesel
     fuels. Exhaust emissions show reduced levels of CO, SO2, particles,
     aroms., hydrocarbons, and increased levels of aldehydes.
     sunflower oil Me ester biodiesel
ST
     Diesel fuel substitutes
IT
     Diesel fuel substitutes
        (biodiesel; sunflower oil Me esters as alternative
        fuels to petroleum-derived diesel fuel)
     Cetane number
     Combustion enthalpy
     Density
     Exhaust gases (engine)
     Exhaust particles (engine)
```

```
Ignition point
    Transesterification
    Viscosity
        (sunflower oil Me esters as alternative fuels to
       petroleum-derived diesel fuel)
    Aldehydes, occurrence
TΨ
    Aromatic hydrocarbons, occurrence
    Hydrocarbons, occurrence
    RL: POL (Pollutant); OCCU (Occurrence)
        (sunflower oil Me esters as alternative fuels to
        petroleum-derived diesel fuel)
TТ
    Fatty acids, uses
    RL: IMF (Industrial manufacture); PRP (Properties); TEM (Technical or
     engineered material use); PREP (Preparation); USES (Uses)
        (sunflower-oil, Me esters; sunflower oil Me esters
        as alternative fuels to petroleum-derived diesel fuel
                                             7446-09-5, Sulfur dioxide,
     630-08-0, Carbon monoxide, occurrence
IT
    occurrence 11104-93-1, Nitrogen oxide, occurrence
     RL: POL (Pollutant); OCCU (Occurrence)
        (sunflower oil Me esters as alternative fuels to
        petroleum-derived diesel fuel)
              THERE ARE 12 CITED REFERENCES AVAILABLE FOR THIS RECORD
RE.CNT 12
(1) Andres Martinez, J; Ingenieria Quimica 1995, 5, P75
(2) Anon; Biodiesel: una energia alternativa para el transporte
(3) Clark, S; JAOCS 1984, V61(10), P1632 CAPLUS
(4) International Energy Agency; Ieas statistics: oil information 1996 donnees
    sur le petrole 1997
(5) Murayama, T; Inform 1994, V5, P1138
(6) Pryde, E; JACOS 1984, V61, P1609
(7) Ryan, T; JAOCS 1984, V61(10), P1610 CAPLUS
(8) Schwab, A; Fuel 1987, V66(10), P1372 CAPLUS
(9) Staat, F; Chemistry Industry 1994, P863 CAPLUS
(10) Tao, T; Chemistry Industry 1994, P906
(11) Varese, R; Inform 1996, V7(8), P816
(12) Vermeersch, G; Etude et Recherche 1993, V29/10, P301
     ANSWER 23 OF 56 CAPLUS COPYRIGHT 2002 ACS
L7
Full Text
     1999:302394 CAPLUS
AN
DN
     131:21253
     Recent advances in the development of alternative diesel fuel from
TΙ
     vegetable oils and animal fats
     Dunn, R. O.; Knothe, G.; Bagby, M. O.
ΑU
     Oil Chemical Research, National Center for Agricultural Utilization
     Research, U.S. Department of Agriculture, Agricultural Research Service,
     Peoria, IL, 61604, USA
     Recent Research Developments in Oil Chemistry (1997), 1, 31-56
     CODEN: RROCFF
     Transworld Research Network
PB
     Journal; General Review
DT
LA
     English
     52-0 (Electrochemical, Radiational, and Thermal Energy Technology)
CC
     Section cross-reference(s): 17, 51, 59
     Interest in utilizing vegetable oils and animal fats (triglycerides)
     as alternative fuels for compression-ignition (diesel) engines has
     increased in the past 10 to 15 yr. Triglycerides have many fuel
     properties including heat of combustion, cetane no., high flash temp. and
     good lubricity that make them attractive as fuels or extenders.
     Triglycerides are renewable, biodegradable and cleaner burning than
     conventional diesel fuels. However, engine tests have shown that
```

extended use of triglycerides as diesel fuels leads to problems such as injector coking, ring carbonization and crankcase lubricant contamination. These problems were attributable to incomplete combustion and poor fuel atomization, conditions directly related to the relatively high viscosity of triglycerides. Diln. with conventional diesel fuel, transesterification with alc., emulsification or co-solvent blending and pyrolyzation have been examd. as methods for reducing viscosity. At present, transesterification has made the most progress towards commercialization. As a result, mono-alkyl esters of fatty acids from transesterified vegetable oils or animal fats are defined as biodiesel in the US. This work reviews, with 119 refs., development of alternative diesel fuels and extenders from triglycerides. Recent advances in improving low-temp. flow properties, fuel ignition quality and exhaust emissions are discussed.

- review alternative diesel fuel vegetable oil; animal fat alternative ST diesel review; biodiesel vegetable oil animal fat review
- Fats and Glyceridic oils, reactions
 - RL: RCT (Reactant); RACT (Reactant or reagent)

(animal; recent advances in development of alternative diesel

fuel from vegetable oils and animal fats)

TT Diesel fuel substitutes

(biodiesel; recent advances in development of alternative diesel fuel from vegetable oils and animal fats)

Glycerides, reactions TΨ

RL: RCT (Reactant); RACT (Reactant or reagent)

(recent advances in development of alternative diesel fuel

from vegetable oils and animal fats)

Fats and Glyceridic oils, reactions IT

RL: RCT (Reactant); RACT (Reactant or reagent)

(vegetable; recent advances in development of alternative diesel fuel from vegetable oils and animal fats)

119 THERE ARE 119 CITED REFERENCES AVAILABLE FOR THIS RECORD

- (1) ASTM; Annual Book of ASTM Standards 1991
- (2) ASTM; Annual Book of ASTM Standards 1991, V05.04
- (3) ASTM; Annual Book of ASTM Standards 1991, V05.03
- (4) ASTM; Annual Book of ASTM Standards 1991, V05.02
- (5) Aaltonen, O; CHEMTECH 1991, V21, P240 CAPLUS
- (6) Adams, C; J Am Oil Chem Soc 1983, V60, P1574 CAPLUS
- (7) Ali, Y; Bioresource Technol 1995, V52, P185 CAPLUS
- (8) Ali, Y; Bioresource Technol 1995, V52, P237 CAPLUS
- (9) Ali, Y; J Am Oil Chem Soc 1995, V72, P1557 CAPLUS
- (10) Anon; Diesel Engine Reference Book 1984, P18/9
- (11) Anon; Diesel Engine Reference Book 1984, P22/9
- (12) Bagby, M; proceedings of the 9th International Conference on Jojoba Uses 3rd International Conference on New Industrial Crops Production 1996, P220
- (13) Bailey, A; Melting and Solidification of Fats 1950, P343
- (14) Baranescu, R; proceedings of the International Conference on Plant and Vegetable Oils as Fuels 1982, ASAE Spec Publ No SP 4-82, P312
- (15) Beiny, D; J Crystal Growth 1990, V102, P801 CAPLUS
- (16) Bondioli, P; J Am Oil Chem Soc 1995, V72, P699 CAPLUS
- (17) Borgelt, S; proceedings of the International Conference on Plant and Vegetable Oils as Fuels 1982, ASAE Spec Publ No SP 4-82, P364
- (18) Brown, G; Erdole und Kohle-Erdgas Petrochemie 1990, V43, P196 CAPLUS
- (19) Brown, G; SAE Technical Paper Series 1989
- (20) Chandler, J; SAE Technical Paper Series 1992
- (21) Clark, S; J Am Oil Chem Soc 1984, V61, P1632 CAPLUS
- (22) Clark, S; final report for project 5980, Soybean Oil Esters as a Renewable Fuel for Diesel Engines under contract 59-2201-1-6-0-059-0 1983
- (23) Coley, T; Critical Reports on Applied Chemistry, Vol 25: Gasoline and Diesel Fuel Additives 1989, P105 CAPLUS
- (24) Crookes, R; Archivum Combustionis 1993, V13, P57 CAPLUS

- (25) Crookes, R; SAE Technical Paper Series 1992
- (26) Damin, B; SAE Technical Paper Series 1986
- (27) De Filippis, P; J Am Oil Chem Soc 1995, V72, P1399 CAPLUS
- (28) Denis, J; Reveue de L'Institut Français du Petrole 1991, V46, P637 CAPLUS
- (29) Du Plessis, L; J Am Oil Chem Soc 1985, V62, P748 CAPLUS
- (30) Duff, H; Introduction to Fats and Oils Technology 1991, P105
- (31) Dunn, R; J Am Oil Chem Soc 1994, V71, P101 CAPLUS (32) Dunn, R; J Am Oil Chem Soc 1995, V72, P123 CAPLUS
- (33) Dunn, R; J Am Oil Chem Soc 1995, V72, P895 CAPLUS
- (34) Dunn, R; J Am Oil Chem Soc 1996, V73, P1719 CAPLUS
- (35) Dunn, R; J Dispersion Sci Technol 1992, V13, P77 CAPLUS
- (36) Dunn, R; J Dispersion Sci Technol 1993, V14, P1 CAPLUS
- (37) Dunn, R; proceedings of the Third Liquid Fuel Conference: Liquid Fuel and Industrial Products from Renewable Resources 1996, P95 CAPLUS
- (38) Dykstra, G; (MS Thesis), University of Illinois 1985
- (39) Einfalt, J; Trans ASAE 1985, V28, P70 CAPLUS
- (40) Engler, C; J Am Oil Chem Soc 1983, V60, P1592 CAPLUS
- (41) Ervin, C; Federal Registar 60,38976 1995
- (42) Foglia, T; J Am Oil Chem Soc (submitted)
- (43) Formo, M; Bailey's Industrial Oil and Fat Production, fourth edition 1979, V1, P214
- (44) Freedman, B; J Am Oil Chem Soc 1984, V61, P1638 CAPLUS
- (45) Freedman, B; J Am Oil Chem Soc 1986, V63, P1370 CAPLUS
- (46) Freedman, B; J Am Oil Chem Soc 1986, V63, P1375 CAPLUS
- (47) Freedman, B; J Am Oil Chem Soc 1990, V67, P565 CAPLUS
- (48) Freedman, B; SAE Technical Paper Series 1990
- (49) Friberg, S; J Am Oil Chem Soc 1971, V48, P578 CAPLUS
- (50) Goering, C; J Am Oil Chem Soc 1984, V61, P1627 CAPLUS
- (51) Goering, C; Trans ASAE 1982, V25, P1472 CAPLUS
- (52) Goering, C; Trans ASAE 1983, V26, P1602 CAPLUS
- (53) Goering, C; final report for project on Effect of Nonpetroleum Fuels on Durability of Direct-Injection Diesel Engines under contract 59-2171-1-6-057-0 1984
- (54) Goering, C; proceedings of the 1987 International Winter Meeting of the American Society of Agricultural Engineers 1987
- (55) Goodrum, J; Vegetable Oil as Diesel Fuel, Seminar III, ARM-NC-28 1983, P112
- (56) Gunstone, F; Lipid Handbook second edition 1994, P82
- (57) Gunstone, F; Lipid Handbook second edition 1994, P97
- (58) Harrington, K; Biomass 1986, V9, P1 CAPLUS
- (59) Heraud, A; J Colloid Interface Sci 1992, V153, P378 CAPLUS
- (60) Ito, K; J Colloid Sci 1964, V19, P152 CAPLUS
- (61) Kato, M; Sekiyu Gakkaishi 1992, V35, P115 CAPLUS,
- (62) Kesling, H; ACS Fuel Chemistry Div Preprints 1994, V39(2), P322 CAPLUS
- (63) Klopfenstein, W; J Am Oil Chem Soc 1985, V62, P1029 CAPLUS
- (64) Knothe, G; ACS Symp Ser, to be published 1996
- (65) Knothe, G; INFORM 1996, V7, P827
- (66) Knothe, G; J Am Oil Chem Soc 1991, V68, P259 CAPLUS
- (67) Knothe, G; SAE Spec Publ SP-900: Alternative Fuels for CI and SI Engines 1992, P37
- (68) Knothe, G; proceedings of the Third Liquid Fuel Conference: Liquid Fuel and Industrial Products from Renewable Resources 1996, P54 CAPLUS
- (69) Krahl, J; proceedings of the Third Liquid Fuel Conference: Liquid Fuel and Industrial Products from Renewable Resources 1996, P136 CAPLUS
- (70) Krahl, J; proceedings of the Third Liquid Fuel Conference: Liquid Fuel and Industrial Products from Renewable Resources 1996, P149 CAPLUS
- (71) Krawczyk, T; INFORM 1996, V7, P800
- (72) Ladommatos, N; FUEL 1995, V74, P1083 CAPLUS
- (73) Lee, I; J Am Oil Chem Soc 1995, V72, P1155 CAPLUS
- (74) Lee, I; J Am Oil Chem Soc 1996, V73, P631 CAPLUS
- (75) Lewtas, K; Advances in Industrial Crystallization 1991, P166 CAPLUS
- (76) Mackay, R; Surfactant Science Series Vol 23, Nonionic Surfactants:

- Physical Chemistry 1987, P297 CAPLUS
- (77) Masjuki, H; proceedings of the 2nd Institute of Mechanical Engineers
 Seminar: Fuels for Automotive and Industrial Diesel Engines 1993, P129
 CAPLIE
- (78) Matthaus, B; J Am Oil Chem Soc 1996, V73, P1039 CAPLUS
- (79) McBain, M; Solubilization and Related Phenomena 1955, P179
- (80) McDonald, J; SAE Technical Paper Series 1995
- (81) McMillan, M; SAE Technical Paper Series 1983
- (82) Mills, G; J Instit Energy 1983, V56, P131 CAPLUS
- (83) Morrison, W; Developments in Oils and Fats 1995, P147
- (84) Mukerjee, P; Solution Chemistry of Surfactants 1979, V1, P153 CAPLUS
- (85) Nakamura, K; Trends Biotechnol 1990, V8, P288 CAPLUS
- (86) National Biodiesel Board; Biodiesel Report 1996
- (87) Nelson, L; J Am Oil Chem Soc 1996, V73, P1191 CAPLUS
- (88) Nitschke, W; Rudolf Diesel: Pioneer of the Age of Power 1965, P139
- (89) Owen, K; Automotive Fuels Handbook 1990, P292
- (90) Owen, K; Automotive Fuels Handbook 1990, P353
- (91) Peterson, C; J Am Oil Chem Soc 1983, V60, P1579 CAPLUS
- (92) Peterson, C; Trans ASAE 1987, V30, P28 CAPLUS
- (93) Plank, C; J Chromatogr A 1995, V697, P461 CAPLUS
- (94) Prankl, H; proceedings of the Third Liquid Fuel Conference: Liquid Fuel and Industrial Products from Renewable Resources 1996, P191 CAPLUS
- (95) Pryde, E; Vegetable Oil as Diesel Fuel, Seminar III, ARM-NC-28 1983, P90
- (96) Purcell, D; J Am Oil Chem Soc 1996, V73, P381 CAPLUS
- (97) Roscoe, R; Brit J Appl Phys 1952, V3, P267
- (98) Rosen, M; Surfactants and Interfacial Phenomena second edition 1989, P322
- (99) Ryan, T; J Am Oil Chem Soc 1984, V61, P1610 CAPLUS
- (100) Ryan, T; SAE Spec Publ SP-958: New Developments in Alternative Fuels and Gasolines for SI and CI Engines 1993, P201 CAPLUS
- (101) Ryan, T; final report on project on Development of a Preliminary Specification for Vegetable Oil Fuels for Diesel Engines under USDA Grant No 59-2489-1-6-060-0 1983
- (102) Scholl, K; SAE Technical Paper Series 1993
- (103) Schon, S; US 5004479 1991 CAPLUS
- (104) Schwab, A; ACS Symp Ser No 311: Phenomena in Mixed Surfactant Systems 1986, P283 CAPLUS
- (105) Schwab, A; Fuel 1987, V66, P1372 CAPLUS
- (106) Schwab, A; J Am Oil Chem Soc 1988, V65, P1781 CAPLUS
- (107) Schwab, A; J Dispersion Sci Technol 1983, V4, P1 CAPLUS
- (108) Schwab, A; J Dispersion Sci Technol 1985, V6, P563 CAPLUS
- (109) Sexton, M; EP 0475620 A2 1992 CAPLUS
- (110) Sii, H; J Am Oil Chem Soc 1995, V72, P905 CAPLUS
- (111) Sims, R; Trans ASAE 1985, V28, P716 CAPLUS
- (112) Temelli, F; J Am Oil Chem Soc 1996, V73, P699 CAPLUS
- (113) Umano, K; J Agric Food Chem 1987, V35, P909 CAPLUS
- (114) Ziejewski, M; J Am Oil Chem Soc 1983, V60, P1567 CAPLUS
- (115) Ziejewski, M; J Am Oil Chem Soc 1984, V61, P1620 CAPLUS
- (116) Ziejewski, M; SAE Spec Publ SP-900: Alternative Fuels for CI and SI Engines 1992, P65
- (117) Ziejewski, M; SAE Technical Paper Series 1986
- (118) Ziejewski, M; SAE Technical Paper Series 1986
- (119) Ziejewski, M; SAE Technical Paper Series 1991
- L7 ANSWER 24 OF 56 CAPLUS COPYRIGHT 2002 ACS

- AN 1999:150233 CAPLUS
- DN 130:256284
- TI Biodiesel exhaust emissions and determination of their environmental and health effects
- AU Krahl, Jurgen; Bunger, Jurgen; Munack, Axel
- CS Bundesforschungsanstalt fur Landwirtschaft Braunschweig-Volkenrode (FAL), Braunschweig, 38116, Germany

```
Plant Oils as Fuels: Present State of Science and Future Developments,
     Proceedings of the Symposium, Potsdam, Feb. 16-18, 1997 (1998), Meeting
     Date 1997, 104-122. Editor(s): Martini, Norbert; Schell, Jozef S.
     Publisher: Springer, Berlin, Germany.
     CODEN: 67HXAP
DT
    Conference; General Review
LA
    English
    59-0 (Air Pollution and Industrial Hygiene)
CC
    Section cross-reference(s): 4, 52
    A review with 34 refs. In Europe, the use of rapeseed oil fuels in
AB
     diesel engines has been intensively investigated since the energy crisis
     of the early 1970s. In the beginning, the emphasis was placed on the
     tech. possibilities assocd. with the use of rapeseed oil as a fuel.
     However, research has shown that pure rapeseed oil can only be used in
     specially designed engines. Research that followed indicated that
     rapeseed oil Me ester (RME) was a suitable replacement for petroleum
     diesel fuel (DF). After this discovery, research has focused on the
     engine exhaust emissions that result when fueling with both unmodified
     rapeseed oil and RME. In the USA, research has focused on soybean oil
     Me ester (SME). Both RME and SME are called biodiesel. In Germany
     biodiesel must fulfill the std. DIN V 51606. Initially, environmental
     related research concd. on the federally regulated hydrocarbons (HCs),
     carbon monoxide, and NOx exhaust gas emission. In addn., a series of
     current publications compare the environmentally important but
     nonregulated polycyclic arom. hydrocarbons (PAHs), aldehydes, ketones,
     and, in some cases, the arom. compds.
     review biodiesel exhaust health environmental hazard
ST
     Polycyclic compounds
     RL: ADV (Adverse effect, including toxicity); POL (Pollutant); BIOL
     (Biological study); OCCU (Occurrence)
        (arom. hydrocarbons; biodiesel exhaust gas emissions and
        detn. of their environmental and health effects)
TΤ
     Air pollution
        (biodiesel exhaust gas emissions and detn. of their
        environmental and health effects)
     Aldehydes, biological studies
ΙT
     Aromatic compounds
     Hydrocarbons, biological studies
     Ketones, biological studies
     RL: ADV (Adverse effect, including toxicity); POL (Pollutant); BIOL
     (Biological study); OCCU (Occurrence)
        (biodiesel exhaust gas emissions and detn. of their
        environmental and health effects)
     Exhaust particles (engine)
IT
       Fuels
     Soot
        (biodiesel; biodiesel exhaust gas emissions and detn. of
        their environmental and health effects)
IT
     Air pollution
        (exhaust, biodiesel; biodiesel exhaust gas emissions and
        detn. of their environmental and health effects)
     Aromatic hydrocarbons, biological studies
TΤ
     RL: ADV (Adverse effect, including toxicity); POL (Pollutant); BIOL
     (Biological study); OCCU (Occurrence)
        (polycyclic; biodiesel exhaust gas emissions and detn. of
        their environmental and health effects)
     Fatty acids, miscellaneous
     RL: MSC (Miscellaneous)
        (rape-oil, Me esters, biodiesel fuel; biodiesel
        exhaust gas emissions and detn. of their environmental and
        health effects)
     630-08-0, Carbon monoxide, biological studies 11104-93-1, Nitrogen oxide
IT
```

- (NOx), biological studies
- RL: ADV (Adverse effect, including toxicity); POL (Pollutant); BIOL (Biological study); OCCU (Occurrence)
 - (biodiesel exhaust gas emissions and detn. of their environmental and health effects)
- RE.CNT 34 THERE ARE 34 CITED REFERENCES AVAILABLE FOR THIS RECORD
- (1) Ames, B; Mutation Research 1975, V31, P347 CAPLUS
- (2) Anon; Sachverstandigenrat fur Umweltfragen Umweltgutachten 1994 1994
- (3) Belisario, M; Mutation Research 1984, V135, P1 CAPLUS
- (4) Clark, C; Toxicology and Applied Pharmacology 1980, V56, P100
- (5) Claxton, L; Environmental Mutagenesis 1983, V5, P609 CAPLUS
- (6) Frankle, G; Automobiltechn Zeitschrift 1988, V90, P13
- (7) Garshick, E; American Review of Respiratory Diseases 1988, V137, P820 MEDLINE
- (8) Gustavsson, P; Scandinavian Journal of Work and Environmental Health 1990, V16, P348 CAPLUS
- (9) Hartung, A; Personal Information 1993
- (10) Heinrich, U; Proceedings:Emissionen von Pflanzenolkraftstoffen und ihre Umweltwirkungen 1994, P19
- (11) Huisingh, J; Application of short-term bioassay in the fractionation and analysis of complex environmental mixtures 1978, P383
- (12) International Agency For Research On Cancer; IARC Monographs 1989, V46, P41
- (13) Irmscher, I; Aspekte des motorischen Verhaltens von Kraftstoffen aus pflanzlichen Olen - Stand der internationalen Forschung Final report:Verein fur Innovative Verkehrstechnik 1994
- (14) Krahl, J; SAE Paper 961847 1996
- (15) Krahl, J; Ubersicht von Arbeiten zum Einsatz von Rapsol und Rapsolmethylester als Kraftstoffe unter Berucksichtigung umweltrelevanter Auswirkungen Final-report 1994
- (16) Krausgrill, C; Abschlubericht RME-Projekt Stadt Fulda Final report 1993
- (17) Levin, D; Mutation Res 1982, V94, P315 CAPLUS
- (18) Levin, D; Proc Natl Acad Sci U S A 1982, V79, P7445 CAPLUS
- (19) Maron, D; Mutation Research 1983, V113, P173 CAPLUS
- (20) Matsushima, T; A safe substitute for polychlorinated biphenyls as an inducer of metabolic activation system 1976, P85 CAPLUS
- (21) Mauderly, J; Environmental Health Perspectives 1994, V102(Suppl 4), P165
- (22) Muscat, J; Journal of clinical epidemiology 1996, V49, P891 MEDLINE
- (23) Pfluger, D; Sozial- und Praventivmedizin 1994, V39, P372 MEDLINE
- (24) Schafe, F; Motortechn Zeitschrift 1991, V52, P346
- (25) Scharmer, K; Standardanforderungen an Rapsolmethylester als
 Motorenkraftstoff Teil I: Stand der Technik Report:Gesellschaft fur
 Entwicklungstechnologie 1993
- (26) Stalder, K; Proceedings: Emissionen von Pflanzenokraftstoffen und ihre Umweltwirkungen 1994, P30
- (27) Stalder, K; Verhandlungen der Deutschen Gesellschaft fur Arbeits- und Umweltmedizin 1993, V33, P75
- (28) Steenland, N; American Journal of Public Health 1990, V80, P670 MEDLINE
- (29) Stober, W; International Archives of Occupational and Environmental Health 1996, V68(Suppl), P3
- (30) Vellguth, G; Grandl Landtechnik 1982, V32, P17
- (31) Vellguth, G; Grundl Landtechnik 1987, V37, P207
- (32) Welschof, G; Der Ackerschlepper Mittelpunkt der Landtechnik 1981, Pl1
- (33) Wolfensberger, U; Raps 1994, V12(1), P12
- (34) Wurst, F; Emissionen beim Einsatz von Rapsolmethylester an einem Prufstandsmotor Forschungsberichte der Bundesanstalt für Landtechnik 1990,
- L7 ANSWER 25 OF 56 CAPLUS COPYRIGHT 2002 ACS

Full Text

AN 1998:753035 CAPLUS

```
DN
     130:85189
     Exhaust emissions of waste plant oil methylester as diesel fuel
ΤI
    Nakazawa, Makoto; Sagiyama, Takashi; Suzuki, Masaaki; Hasegawa, Atsuko
ΑU
     Air Quarity Division, Kanagawa Environmental Research Center, Japan
CS
     Kanagawa-ken Kankyo Kagaku Senta Kenkyu Hokoku (1997), 20, 15-19
so
     CODEN: KKHOEP; ISSN: 0917-8279
     Kanagawa-ken Kankyo Kagaku Senta
PB
DT
     Journal
LA
     Japanese
     59-3 (Air Pollution and Industrial Hygiene)
CC
     Section cross-reference(s): 17, 51, 60
     Exhaust emissions from diesel engines burning waste vegetable oil
AB
     methylester as fuels are characterized by lower black smoke and
     hydrocarbon emissions, as compared to burning light oils. Nitrogen
     oxides and carbon dioxide emissions were slightly higher. HCHO
     emission was slightly higher before engine warm-up; but lower after the
     warm-up. Particulate emissions were higher.
     waste plant oil methylester diesel engine; vegetable oil methylester
ST
     fuel diesel exhaust
     Diesel engines
     Exhaust gases (engine)
       Fuel oil
        (exhaust emissions of waste plant oil methylester
        as diesel fuel)
IT
     Wastes
        (vegetable oil methylester; exhaust emissions of
        waste plant oil methylester as diesel fuel)
     Fatty acids, uses
ΤT
     RL: NUU (Other use, unclassified); PRP (Properties); USES (Uses)
        (vegetable-oil, Me esters; exhaust emissions of
        waste plant oil methylester as diesel fuel)
     ANSWER 26 OF 56 CAPLUS COPYRIGHT 2002 ACS
L7
     1998:697607 CAPLUS
AN
     130:27002
DN
     Development of FA-1 universal ashless energy-saving additive for fuel oil
ΤI
     Tang, Xiaodong; Xu, Rong; Yin, Daiyi; Li, Yongjie; Yang, Xiuzhong; Ren,
ΑU
     Zhenghua
     Dept. Chem. Eng., SWPI, Sichuan, 637001, Peop. Rep. China
CS
     Xinan Shiyou Xueyuan Xuebao (1998), 20(3), 64-67
SO
     CODEN: XSXUEG; ISSN: 1000-2634
     Xinan Shiyou Xueyuan Xuebao Bianjibu
PΒ
DΤ
     Journal
LA
     Chinese
     51-9 (Fossil Fuels, Derivatives, and Related Products)
CC
     Ashless energy-saving additives not only can save energy and eliminate
AB
     soot but also cause no secondary pollution to the atm., and therefore,
     they represent the trend of development of energy-saving additives for
     fuel oil. FA-1 universal ashless energy-saving additive has been
     developed in accordance with this trend. The optimum amt. of FA-1 is
     about 0.1% (vol.), the efficiency of saving of oil is 4.7 on bench test
     and the av. efficiency of saving of oil is 15-20% (no less than 10% for
     new motor vehicles) on road test. FA-1 also has many other functions,
     such as supporting combustion, eliminating soot, reducing HC and CO2
     emission, lessening carbon deposit, reducing engine noise and enhancing
```

mech. horsepower, etc. After analyzing these test results, it is proposed that the mechanism of FA-1 lies in the improvement of the spray quality of

fuel oil and the chain reaction of three mols. occurring between

- ST fuel oil multifunctional additive
- IT Fuel oil additives

oxygen and FA-1.

(multifunctional; FA-1 universal ashless energy-saving additive for fuel oil)

IT Fatty acids, uses

RL: MOA (Modifier or additive use); USES (Uses)
 (tall-oil; FA-1 universal ashless energy-saving
 additive for fuel oil)

L7 ANSWER 27 OF 56 CAPLUS COPYRIGHT 2002 ACS

Full Text

- AN 1998:514854 CAPLUS
- DN 129:163813
- TI Assessing the viability of using rape methyl ester (RME) as an alternative to mineral diesel **fuel** for powering road vehicles in the UK
- AU Williamson, Ann-Marie; Badr, Ossama
- CS Department of Applied Energy, Cranfield University, Bedfordshire, MK430AL,
- SO Applied Energy (1998), 59(2/3), 187-214 CODEN: APENDX; ISSN: 0306-2619
- PB Elsevier Science Ltd.
- DT Journal; General Review
- LA English
- CC 52-0 (Electrochemical, Radiational, and Thermal Energy Technology)
 Section cross-reference(s): 59
- AP Review with 53 refs. Rape Me ester (RME) is a suitable substitute for mineral diesel in existing compression-ignition engines. Its use as an alternative transport fuel will result in decreased emissions of atm. pollutants (particularly SO2, hydrocarbons and smoke) from this source. However, to encourage such a trend in the UK, the Government needs to adopt the European Union's recommendation of a redn. of excise duties on biofuels to 10% of the rate applied to lead-free petrol to ensure its economic short-term competitiveness in the UK market. Such a subsidy will not be required by the year 2004. The available resource base for rape-seed oil in the UK limits the prodn. of RME, so it could satisfy only up to 4% of demand on fuel by road vehicles powered by diesel engines in the UK. This suggests that it should be used preferentially in urban areas and waterways where its environmental benefits would be maximized.
- ST rape methyl ester diesel fuel review
- IT Diesel engines

(assessing the viability of using rape Me ester as an alternative to mineral diesel **fuel** for powering road vehicles in UK)

IT Diesel fuel substitutes

Diesel fuel substitutes

(biodiesel; assessing the viability of using rape Me ester as an alternative to mineral diesel **fuel** for powering road vehicles in UK)

IT Air pollution

(control; assessing the viability of using rape Me ester as an alternative to mineral diesel **fuel** for powering road vehicles in UK)

IT Fatty acids, uses

RL: PRP (Properties); TEM (Technical or engineered material use); USES (Uses)

(rape-oil, Me esters; assessing the viability of using rape Me ester as an alternative to mineral diesel fuel for powering road vehicles in UK)

L7 ANSWER 28 OF 56 CAPLUS COPYRIGHT 2002 ACS

- AN 1998:313092 CAPLUS
- DN 128:323957
- TI Combustion of fat and vegetable oil derived fuels in diesel engines

- AU Graboski, Michael S.; Mccormick, Robert L.
- CS Colorado Institute for Fuels and High Altitude Engine Research and Department of Chemical Engineering and Petroleum Refining, Colorado School of Mines, Golden, CO, 80401-1887, USA
- SO Progress in Energy and Combustion Science (1998), 24(2), 125-164 CODEN: PECSDO; ISSN: 0360-1285
- PB Elsevier Science Ltd.
- DT Journal; General Review
- LA English
- CC 52-0 (Electrochemical, Radiational, and Thermal Energy Technology) Section cross-reference(s): 45
- A review with 108 refs. of the status of fat and oil derived diesel AB fuels with respect to fuel properties, engine performance, and emissions is reviewed. The fuels considered are primarily the Me esters of fatty acids derived from a variety of vegetable oils and animal fats, and referred to as biodiesel. The major obstacle to widespread use of biodiesel is the high cost relative to petroleum. Economics of biodiesel prodn. are discussed, and it is concluded that the price of the feedstock fat or oil is the major factor detg. biodiesel price. Biodiesel is completely miscible with petroleum diesel fuel, and is generally tested as a blend. The use of biodiesel in neat or blended form has no effect on the energy based engine fuel economy. The lubricity of these fuels is superior to conventional diesel, and this property is imparted to blends at levels above 20 vol%. Emissions of PM can be reduced dramatically through use of biodiesel in engines that are not high lube oil emitters. Emissions of NOx increase significantly for both neat and blended fuels in both two- and four-stroke engines. The increase may be lower in newer, lower NOx emitting four-strokes, but addnl. data are needed to confirm this conclusion. A discussion of available data on unregulated air toxins is presented, and it is concluded that definitive studies have yet to be performed in this area. A detailed discussion of important biodiesel properties and recommendations for future research is presented. Among the most important recommendations is the need for all future studies to employ biodiesel of well-known compn. and purity, and to report detailed analyses. The purity levels necessary for achieving adequate engine endurance, compatibility with coatings and elastomers, cold flow properties, stability, and emissions performance must be better defined.
- ST review diesel fuel vegetable oil fat
- IT Fats and Glyceridic oils, uses

RL: NUU (Other use, unclassified); USES (Uses) (combustion of fat and vegetable oil derived

fuels in diesel engines)

IT Combustion

(of fat and vegetable oil derived fuels
in diesel engines)

IT Fats and Glyceridic oils, uses

RL: NUU (Other use, unclassified); USES (Uses)
(vegetable; combustion of fat and vegetable oil
derived fuels in diesel engines)

L7 ANSWER 29 OF 56 CAPLUS COPYRIGHT 2002 ACS

- AN 1998:144538 CAPLUS
- DN 128:182348
- TI Thermal preparation of liquid fuels for low-pollutant premixed combustion
- AU Stoffel, Beat
- CS VDI Verlag GmbH, Duesseldorf, Germany
- SO Fortschritt-Berichte VDI, Reihe 15: Umwelttechnik (1996), 151, 1-190 CODEN: FRUMFB; ISSN: 0178-9589
- PB VDI Verlag GmbH
- DT Journal

```
STN Columbus
LA
    German
    51-12 (Fossil Fuels, Derivatives, and Related Products)
CC
    Liq. fuels can be burned with low pollutant emissions comparable to
     those attained with gaseous fuels if the liq. fuels can be converted
     to gaseous fuels and mixed homogeneously with combustion air before
     entering the combustion zone. Using a complete temporal and spatial sepn.
     of the three major steps of liq. fuel combustion (e.g., vaporization of
     finely atomized liq. fuel, homogeneous mixing of fuel and air before
     combustion, and combustion reaction at controlled temp. and residence time
     in the range of milliseconds), very low pollutant emissions (esp. NOx,
     CO, and soot) in the exhaust gas are possible. The concept was named VPL
     (vaporized premixed lean combustion). Exptl. investigations were carried
     out in a lab. scale test rig with a variable fuel mass flow of 0.5-2
     kg/h. A multitude of liq. fuels were mixed with water at different
     ratios (water/fuel mass ratio 0.1-0.5:1) and converted to a gaseous
     fuel at 1-6 bar in a tube vaporizer heated externally by hot combustion
     exhaust gases. Depending on temp. and mean residence time in the
     vaporizer, different amts. of liq. fuels were thermally cracked (e.g.,
     to ethylene, propene and methane). For the less volatile fuels (e.g.,
     light fuel oil, unleaded gasoline, and rapeseed oil Me esters),
     coinjection of steam into the vaporizer was necessary. The generated
     gaseous fuels were mixed homogeneously with preheated combustion air in
     a tubular mixing zone equipped with static baffles and burned at atm.
     pressure in a new Pyrocore ceramic-fiber radiant burner with 15 kW
     thermal power installed in a water-cooled test boiler.
     premixed combustion liq fuel; pyrolysis liq fuel premixed combustion;
ST
     steam cracking liq fuel premixed combustion; radiant burner liq fuel
     premixed combustion
TТ
     Synthetic fibers
     RL: DEV (Device component use); USES (Uses)
        (ceramic, burners; pyrolysis and steam cracking pre-treatment
        in premixed lean combustion with low pollutant emissions)
TΤ
     Ceramics
     RL: DEV (Device component use); USES (Uses)
        (fibers, burners; pyrolysis and steam cracking pre-treatment
        in premixed lean combustion with low pollutant emissions)
IT
     Soot
        (formation and emission of; pyrolysis and steam cracking
        pre-treatment in premixed lean combustion with low pollutant
        emissions)
IT
     Combustion
        (premixed; pyrolysis and steam cracking pre-treatment in premixed lean
        combustion with low pollutant emissions)
     Thermal decomposition
IT
        (pyrolysis and steam cracking pre-treatment in premixed lean combustion
        with low pollutant emissions)
```

IT Burners

(radiant; pyrolysis and steam cracking pre-treatment in premixed lean combustion with low pollutant emissions)

Fatty acids, reactions IT

RL: RCT (Reactant); RACT (Reactant or reagent) (rape-oil, Me esters, combustion of; pyrolysis and steam cracking pre-treatment in premixed lean combustion with low pollutant emissions)

Cracking (reaction)

RL: RCT (Reactant); RACT (Reactant or reagent) (steam; pyrolysis and steam cracking pre-treatment in premixed lean combustion with low pollutant emissions)

64-17-5, Ethanol, reactions 67-56-1, Methanol, reactions 142-82-5, Heptane, reactions

RL: RCT (Reactant); RACT (Reactant or reagent) (combustion of; pyrolysis and steam cracking pre-treatment in premixed

lean combustion with low pollutant emissions)

IT 630-08-0, Carbon monoxide, formation (nonpreparative) 11104-93-1, Nitrogen oxide (NOx), formation (nonpreparative) RL: FMU (Formation, unclassified); POL (Pollutant); FORM (Formation, nonpreparative); OCCU (Occurrence)

(formation and emission of; pyrolysis and steam cracking pre-treatment in premixed lean combustion with low pollutant emissions)

IT 74-82-8, Methane, reactions 74-85-1, Ethene, reactions 115-07-1, 1-Propene, reactions

RL: FMU (Formation, unclassified); RCT (Reactant); FORM (Formation, nonpreparative); RACT (Reactant or reagent)

(in-situ formation and combustion of; pyrolysis and steam cracking pre-treatment in premixed lean combustion with low pollutant emissions)

L7 ANSWER 30 OF 56 CAPLUS COPYRIGHT 2002 ACS

Full Text

- AN 1998:135237 CAPLUS
- DN 128:182437
- TI Pilot production of biodiesel on the Nez Perce Tribe reservation
- AU Cruz, Rico O.; Stanfill, John; Powaukee, Bart
- CS Nez Perce Tribe, Department of Environmental Restoration and Waste Management, Lapwai, ID, 83540, USA
- SO Bioenergy '96: Partnerships to Develop and Apply Biomass Technologies, Proceedings of the National Bioenergy Conference, 7th, Nashville, Sept. 15-20, 1996 (1996), Volume 1, 364-371 Publisher: Tennessee Valley Authority, Muscle Shoals, Ala. CODEN: 65SBAY
- DT Conference
- LA English
- CC 52-1 (Electrochemical, Radiational, and Thermal Energy Technology)
 Section cross-reference(s): 17, 51, 60
- The pilot project located at Lapwai, Idaho, relates to a renewable fuel from vegetable oil or animal fat and alc. The fuel, termed as biodiesel, is produced through a modified transesterification process. Biodiesel is comparable to diesel fuel with respect to chem. and phys. attributes, and combustion characteristics. Biodiesel is also, biodegradable, cleaner burning and safer, and has environmentally friendly attributes. The unit produces up to 1150 L of biodiesel per batch, with initial batches of methanol and used cooking oil as raw materials. For demonstration purposes, both biodiesel and diesel are used in diesel powered vehicles and small engines. The raw materials and biodiesel are analyzed, and the vehicles/engines are tested for emissions and performance.
- ST biodiesel transesterification methanol used cooking oil
- IT Diesel fuel substitutes

(biodiesel; pilot prodn. of biodiesel on the Nez Perce Tribe reservation)

- IT Diesel fuel substitutes
 - RL: PRP (Properties); SPN (Synthetic preparation); PREP (Preparation) (biodiesel; pilot prodn. of biodiesel on the Nez Perce Tribe reservation)
- IT Fatty acids, preparation

RL: PRP (Properties); SPN (Synthetic preparation); PREP (Preparation) (coco, Me esters; pilot prodn. of biodiesel on the Nez Perce Tribe reservation)

- IT Fatty acids, preparation
 - RL: PRP (Properties); SPN (Synthetic preparation); PREP (Preparation) (coco, esters, Et ester; pilot prodn. of biodiesel on the Nez Perce Tribe reservation)
- IT Wastes

- RL: RCT (Reactant); RACT (Reactant or reagent) (cooking oil; pilot prodn. of biodiesel on the Nez Perce Tribe reservation)
- IT Transesterification

(pilot prodn. of biodiesel on the Nez Perce Tribe reservation)

IT Glycerides, reactions

RL: RCT (Reactant); RACT (Reactant or reagent)
(pilot prodn. of biodiesel on the Nez Perce Tribe reservation)

IT Fatty acids, preparation

RL: PRP (Properties); SPN (Synthetic preparation); PREP (Preparation) (rape-oil, Et esters; pilot prodn. of biodiesel on the Nez Perce Tribe reservation)

IT Fatty acids, preparation

RL: PRP (Properties); SPN (Synthetic preparation); PREP (Preparation) (soya, Me esters; pilot prodn. of biodiesel on the Nez Perce Tribe reservation)

IT Fatty acids, preparation

RL: PRP (Properties); SPN (Synthetic preparation); PREP (Preparation) (soya, esters, Et ester; pilot prodn. of biodiesel on the Nez Perce Tribe reservation)

IT Diesel fuel substitutes

(synthetic; pilot prodn. of biodiesel on the Nez Perce Tribe reservation)

IT 67-56-1, Methanol, reactions

RL: RCT (Reactant); RACT (Reactant or reagent)
(pilot prodn. of biodiesel on the Nez Perce Tribe reservation)

L7 ANSWER 31 OF 56 CAPLUS COPYRIGHT 2002 ACS

Full Text

- AN 1997:672400 CAPLUS
- DN 127:333970
- TI Rapeseed oil fuel properties for diesel engines
- AU Hamasaki, Kazunori; Kinoshita, Eiji; Nakamura, Takuya; Kameda, Akio; Oyama, Takayuki
- CS Fac. Eng., Kagoshima Univ., Kagoshima, 890, Japan
- SO Kagoshima Daigaku Kogakubu Kenkyu Hokoku (1997), 39, 23-28 CODEN: KDKKBA; ISSN: 0451-212X
- PB Kagoshima Daigaku Kogakubu
- DT Journal
- LA Japanese
- CC 52-1 (Electrochemical, Radiational, and Thermal Energy Technology)
 Section cross-reference(s): 45
- Due to the increasing interest in the CO2 problem, the request for alternative fuels from regenerated vegetable energy sources is increasing. The present work describes the results of expts. using rapeseed oil, emulsified rapeseed oil, rapeseed Me ester, and gas oil in a swirl-chamber diesel engine. The results show that the viscosity of rapeseed Me ester is a little higher than that of gas oil, and that the smoke concn. for rapeseed Me ester is about 50% lower than that of gas oil. Furthermore, NOx and smoke concns. for emulsified rapeseed oil are lower than those of gas oil and energy consumption is similar to that in the case of operation with gas oil and rapeseed Me ester.
- ST rapeseed oil emulsified diesel fuel; Me ester rapeseed diesel fuel; exhaust diesel smoke nitrogen oxide emission; air pollution control diesel exhaust
- IT Air pollution

(control; rapeseed oil fuel properties for diesel engines)

IT Fatty acids, uses

RL: NUU (Other use, unclassified); USES (Uses) (esters, rape-oil, Me esters; rapeseed oil

```
fuel properties for diesel engines)
TT
    Air pollution
        (exhaust, diesel; rapeseed oil fuel properties for
        diesel engines)
    Diesel fuel
IΤ
    Smoke
        (rapeseed oil fuel properties for diesel engines)
IΤ
    Rape oil
    RL: NUU (Other use, unclassified); USES (Uses)
        (rapeseed oil fuel properties for diesel engines)
    124-38-9, Carbon dioxide, occurrence 11104-93-1, Nitrogen oxide nox,
IT
    occurrence
    RL: POL (Pollutant); OCCU (Occurrence)
        (rapeseed oil fuel properties for diesel engines)
    ANSWER 32 OF 56 CAPLUS COPYRIGHT 2002 ACS
1.7
Full Text
    1997:615690 CAPLUS
AN
    127:280645
DN
    Cetane numbers of fatty compounds: influence of compound structure and of
ΤI
    various potential cetane improvers
    Knothe, Gerhard; Bagby, Marvin O.; Ryan, Thomas W., III
ΑU
    U.S. Dept. of Agriculture, USA
CS
    Society of Automotive Engineers, [Special Publication] SP (1997),
SO
    SP-1274(State of Alternative Fuel Technologies), 127-132
    CODEN: SAESA2; ISSN: 0099-5908
    Society of Automotive Engineers
PB
    Journal
DТ
     English
LA
     52-1 (Electrochemical, Radiational, and Thermal Energy Technology)
CC
     Section cross-reference(s): 59
     Biodiesel is a mixt. of esters (usually Me esters) of fatty acids
AΒ
     found in the triglycerides of vegetable oils. The different fatty
     compds. comprising biodiesel possess different ignition properties.
     investigate and potentially improve these properties, the cetane nos. of
     various fatty acids and esters were detd. in a const. vol. combustion
     app. The cetane nos. range from 20.4 for linolenic acid to 80.1 for Bu
     stearate. The cetane nos. depend on the no. of CH2 groups as well as the
     no. of double bonds and other factors. Various oxygenated compds. were
     studied for their potential of improving the cetane nos. of fatty compds.
     Several potential cetane improvers with ignition delay properties giving
     calcd. cetane nos. over 100 were identified. The effect of these cetane
     improvers depended on their concn. and also on the fatty material
     investigated. In one case, the cetane no. of the acid was increased more
     than that of the corresponding esters. The effect also depends on the
     nature of the ester. These results offer the possibility of tailoring
     cetane improvers to the nature of component fatty compds. in biodiesel.
     The cetane improving-additives are a potential route for reducing the
     exhaust emissions of biodiesel, for example NOx.
     biodiesel fatty acid ester cetane no; fatty acid ester structure cetane no
ST
     Fuels
ΙT
        (biofuels, biodiesel; influence of compd. structure and of various
        potential cetane improvers on cetane nos. of fatty compds.)
IT
     Fatty acids, properties
     RL: PRP (Properties)
        (esters; influence of compd. structure and of various potential cetane
        improvers on cetane nos. of fatty compds.)
IT
     Air pollution
     Cetane number
       Ignition
        (influence of compd. structure and of various potential cetane
```

improvers on cetane nos. of fatty compds.)

- IT 11104-93-1, Nitrogen oxide, occurrence
 RL: POL (Pollutant); OCCU (Occurrence)
 (influence of compd. structure and of various potential cetane
 improvers on cetane nos. of fatty compds.)
- IT 57-11-4, Stearic acid, properties 60-33-3, Linoleic acid, properties 111-59-1, Propyl oleate 111-61-5, Ethyl stearate 111-62-6, Ethyl oleate 112-61-8, Methyl stearate 112-62-9, Methyl oleate 112-63-0, Methyl linoleate 112-80-1, Oleic acid, properties 123-95-5, Butyl stearate 142-77-8, Butyl oleate 301-00-8, Methyl linolenate 463-40-1, Linolenic acid 544-35-4, Ethyl linoleate 1191-41-9, Ethyl linolenate 2634-45-9, Butyl linoleate 3634-92-2, Propyl stearate 38370-68-2, Butyl linolenate 38433-95-3, Propyl linoleate 106196-77-4 RL: PRP (Properties)

(influence of compd. structure and of various potential cetane improvers on cetane nos. of fatty compds.)

L7 ANSWER 33 OF 56 CAPLUS COPYRIGHT 2002 ACS

Full Text

- AN 1997:558532 CAPLUS
- DN 127:139458
- TI Sources of Fine Organic Aerosol. 8. Boilers Burning No. 2 Distillate Fuel Oil
- AU Rogge, Wolfgang F.; Hildemann, Lynn M.; Mazurek, Monica A.; Cass, Glen R.; Simoneit, Bernd R. T.
- CS Environmental Engineering Science Department, California Institute of Technology, Pasadena, CA, 91125, USA
- SO Environmental Science and Technology (1997), 31(10), 2731-2737 CODEN: ESTHAG; ISSN: 0013-936X
- PB American Chemical Society
- DT Journal
- LA English
- CC 59-2 (Air Pollution and Industrial Hygiene)
 Section cross-reference(s): 51
- Fine org. particulate matter emitted from an industrial-scale boiler AΒ burning no. 2 distillate fuel oil has been characterized on a mol. basis using GC/MS techniques. Most of the identified compd. mass consists of n-alkanoic acids (42.0-51.5%), arom. acids (5.8-22.6%), and n-alkanes (6.7-25.0%). Polycyclic arom. hydrocarbons (PAH) and oxygenated PAH (oxy-PAH) together comprise 3.1-8.6% of the identifiable mass and together with chlorinated compds. (5.8-16.4%) show the largest variations in emission rates between the two expts. reported here. An increase in chlorinated compd. emissions between tests is accompanied by a similar increase in elemental carbon (i.e., soot) and PAH emissions, which may follow the results of lab. expts. that suggest that the presence of chlorinated compds. can enhance both soot and PAH formation. Differences between the hopanes distribution in the boiler exhaust vs. that found in both vehicle exhaust and in the southern California atm. suggest that the oil-fired boiler exhaust is at most a minor contributor to the atm. aerosol, which is consistent with inferences drawn from local emission inventories.
- org particulate flue gas air pollution; fuel oil org particulate emission; alkanoate arom acid alkane particulate emission; polycyclic arom hydrocarbon emission; boiler distillate fuel oil soot emission
- IT Polycyclic compounds
 - RL: POL (Pollutant); OCCU (Occurrence)

(arom. hydrocarbons; compn. of org. particulate matter emitted from an industrial-scale boiler **burning** no. 2 distillate **fuel** oil)

- IT Carboxylic acids, occurrence
 - RL: POL (Pollutant); OCCU (Occurrence)

(arom.; compn. of org. particulate matter emitted from an industrial-scale boiler burning no. 2 distillate fuel

oil)

IT Atmospheric aerosols

Flue gases

Fuel oil

Soot

(compn. of org. particulate matter emitted from an industrial-scale boiler burning no. 2 distillate fuel oil)

IT Alkanes, occurrence

Fatty acids, occurrence

RL: POL (Pollutant); OCCU (Occurrence)

(compn. of org. particulate matter emitted from an industrial-scale boiler burning no. 2 distillate fuel oil)

IT Triterpenes

RL: POL (Pollutant); OCCU (Occurrence)

(hopane; compn. of org. particulate matter emitted from an industrial-scale boiler burning no. 2 distillate fuel oil)

IT Air pollution

(particulate; compn. of org. particulate matter emitted from an industrial-scale boiler burning no. 2 distillate fuel oil)

IT Aromatic hydrocarbons, occurrence

RL: POL (Pollutant); OCCU (Occurrence)

(polycyclic; compn. of org. particulate matter emitted from an industrial-scale boiler **burning** no. 2 distillate **fuel**

50-32-8, Benzo[a]pyrene, occurrence 50-79-3, 2,5-Dichlorobenzoic acid IT 56-55-3, Benz[a]anthracene 57-10-3, Hexadecanoic acid, occurrence 57-11-4, Octadecanoic acid, occurrence 65-85-0, Benzoic acid, occurrence 82-05-3, 7H-Benz[de]anthracen-7-one 84-65-1, Anthraquinone 85-01-8, Phenanthrene, occurrence 87-65-0, 2,6-Dichlorophenol 100-21-0, 1,4-Benzenedicarboxylic acid, occurrence 106-48-9, 4-Chlorophenol 112-37-8, Undecanoic acid 112-85-6, Behenic acid 112-95-8, Eicosane 120-12-7, Anthracene, occurrence 121-91-5, 1,3-Benzenedicarboxylic acid, occurrence 129-00-0, Pyrene, occurrence 143-07-7, Dodecanoic acid, occurrence 192-97-2, Benzo[e]pyrene 203-12-3, Benzo[ghi]fluoranthene 205-99-2, Benzo[b]fluoranthene 206-44-0, Fluoranthene 207-08-9, Benzo[k]fluoranthene 334-48-5, Decanoic acid 486-25-9, 9H-Fluoren-9-one 506-12-7, Heptadecanoic acid 506-30-9, Eicosanoic acid 506-38-7, Pentacosanoic acid 506-46-7, Hexacosanoic acid 535-80-8, 3-Chlorobenzoic acid 544-63-8, Tetradecanoic acid, occurrence 544-85-4, Dotriacontane 557-59-5, Tetracosanoic acid 593-49-7, Heptacosane 629-92-5, Nonadecane 629-94-7, Heneicosane 629-97-0, Docosane 629-99-2, Pentacosane 630-01-3, Hexacosane 630-02-4, Octacosane 630-03-5, Nonacosane 630-04-6, Hentriacontane 630-05-7, Tritriacontane 638-53-9, Tridecanoic acid 638-67-5, Tricosane 638-68-6, Triacontane 646-30-0, Nonadecanoic acid Tetracosane 2433-96-7, Tricosanoic acid 2840-51-9, 2-Methylfluoren-9-one 86853-88-5, 1H-Benz[de]anthracen-1-one RL: POL (Pollutant); OCCU (Occurrence) (compn. of org. particulate matter emitted from an industrial-scale boiler burning no. 2 distillate fuel oil)

L7 ANSWER 34 OF 56 CAPLUS COPYRIGHT 2002 ACS

- AN 1997:445913 CAPLUS
- DN 127:111128
- TI Results of the joint project "fuel from rape"
- AU Hacker, Claus-M.; Schliephake, Dietrich
- CS FIB Forschungs-, Industrie- und Umweltberatungsgesellschaft mbH, Velbert, D-42552, Germany
- SO European Motor Biofuels Forum, Proceedings, 2nd, Graz, Sept. 22-25, 1996

(1996), 353-360 Publisher: Joanneum Research Forschungsgesellschaft, Graz, Austria.

CODEN: 64RCAP

- DT Conference
- LA English
- CC 52-1 (Electrochemical, Radiational, and Thermal Energy Technology)
 Section cross-reference(s): 45
- AB The report includes selected results of the joint project "Fuel from Rape" which investigates into the agricultural, process and chem. engineering framework for the utilization of rape seed oil and its conversion products as fuel. The entire process chain from the cultivation to the oil mill and the chem. conversion into fuel and also practical testing was assessed in 15 individual projects. We were able to prove that through the use of rape seed oil in refineries we can produce a fuel (DKR) with excellent exhaust emission values. Keypoints of the project work were the assessment of energy and CO2 balance and a comparison of the bio-fuels DKR, RME and ROR.
- ST diesel fuel rapeseed oil methyl ester
- IT Air pollution

(control; diesel fuel from rapeseed oil)

IT Diesel fuel

(diesel fuel from rapeseed oil)

IT Fatty acids, uses

RL: BMF (Bioindustrial manufacture); NUU (Other use, unclassified); BIOL (Biological study); PREP (Preparation); USES (Uses) (esters, rape-oil, Me esters; diesel fuel from rapeseed oil)

L7 ANSWER 35 OF 56 CAPLUS COPYRIGHT 2002 ACS

- AN 1997:434816 CAPLUS
- DN 127:69961
- TI Survey about biodiesel exhaust emissions and their environmental effects
- AU Krahl, Jurgen; Munack, Axel; Bahadi, Mufit; Schumacher, Leon; Elser, Nancy
- CS Inst. Biosystems Engineering, Federal Agricultural Res. Centre, Braunschweig, Germany
- Liquid Fuel and Industrial Products from Renewable Resources, Proceedings of the Liquid Fuel Conference, 3rd, Nashville, Sept. 15 -17, 1996 (1996), 136-148. Editor(s): Cundiff, John S. Publisher: American Society of Agricultural Engineers, St. Joseph, Mich.

 CODEN: 64QYAI
- DT Conference
- LA English
- CC 59-3 (Air Pollution and Industrial Hygiene)
- In Europe, the use of rapeseed fuels in diesel engines has been intensively investigated since the energy crisis of the early 1970s. In the beginning, the emphasis was placed on the tech. possibilities assocd. with the use of rapeseed oil as a fuel. However, research has shown that pure rapeseed oil can only be used in specially designed engines. Research that followed indicated that rapeseed oil Me ester (RME) was a suitable replacement for petroleum diesel fuel (DF). After this discovery, research has focused on the engine exhaust emissions that result when fueling with both unmodified rapeseed oil and RME. In the USA research has focused on soybean oil methylester (SME). Both RME and SME are called biodiesel. In Germany biodiesel must fulfill the std. DIN V 51606. Initially, environmental related research concd. on the federally regulated hydrocarbons (HC), carbon monoxide (CO), and oxides of nitrogen (NOx) exhaust gas emissions (Vellguth, 1987). In addn., a series of current publications compare the environmentally important but non-regulated polycyclic arom. hydrocarbons (PAH), aldehydes, ketones and in some cases, the arom. compds. The paper presented is based on a former publication of Krahl et al. (1994), that spanned the data collected to

```
Mar., 1994. This paper includes addnl. data taken after Mar. of 1994.
    biodiesel exhaust emission
ST
     Soybean oil
ΙT
     RL: NUU (Other use, unclassified); USES (Uses)
        (Me ester; survey of biodiesel exhaust emissions and their
        environmental effects)
     Exhaust gases (engine)
IT
        (diesel; survey of biodiesel exhaust emissions and their
        environmental effects)
     Fatty acids, uses
TT
     RL: NUU (Other use, unclassified); USES (Uses)
        (esters, rape-oil, Me esters; survey of biodiesel exhaust
        emissions and their environmental effects)
TΨ
     Air pollution
     Soot
        (survey of biodiesel exhaust emissions and their
        environmental effects)
     Aldehydes, formation (nonpreparative)
ΙT
     Aromatic compounds
     Hydrocarbons, formation (nonpreparative)
     RL: FMU (Formation, unclassified); POL (Pollutant); FORM (Formation,
     nonpreparative); OCCU (Occurrence)
        (survey of biodiesel exhaust emissions and their
        environmental effects)
     71-43-2, Benzene, formation (nonpreparative)
                                                    630-08-0, Carbon monoxide,
IT
     formation (nonpreparative)
                                  11104-93-1, Nitrogen oxide, formation
     (nonpreparative)
     RL: FMU (Formation, unclassified); POL (Pollutant); FORM (Formation,
     nonpreparative); OCCU (Occurrence)
        (survey of biodiesel exhaust emissions and their
        environmental effects)
     ANSWER 36 OF 56 CAPLUS COPYRIGHT 2002 ACS
L7
Full Text
     1997:317055 CAPLUS
AN
     127:37003
DN
     Life cycle analysis of biofuels under different environmental aspects
ΤI
     Kaltschmitt, M.; Reinhardt, G. A.; Stelzer, T.
AU
     Institut fur Energiewirtschaft und Rationelle Energieanwendung (IER),
CS
     Universitat Stuttgart, Stuttgart, D-70565, Germany
     Biomass and Bioenergy (1997), 12(2), 121-134
SO
     CODEN: BMSBEO; ISSN: 0961-9534
PΒ
     Elsevier
DT
     Journal
     English
LA
     52-1 (Electrochemical, Radiational, and Thermal Energy Technology)
CC
     Section cross-reference(s): 59
     The environmental impact of bioenergy carriers can be detd. with the help
AΒ
     of life cycle anal. The present study shows that bioenergy carriers offer
     some clear ecol. advantages over fossil fuels, such as conserving fossil
     energy resources or reducing the greenhouse effect, but they also have
     some definite disadvantages (in particular regarding certain airborne
     pollutants) when the overall life cycle is considered. The paper first
     discusses the methodol. approach for conducting a Life Cycle Anal. (LCA)
     for biofuels; this approach is then used for a case study of Rape Me Ester
     (RME) compared with diesel fuel. The same approach is then applied for
     some bioenergy routes discussed currently in Germany. For the different
     bioenergy routes the results of the LCA for Energy, CO2 equivalents, N2O
     emissions, SO2 equivalents, SO2 emissions and NOx emissions are
     given and discussed.
     biofuel life cycle analysis environmental aspect
ST
     Hydrocarbons, formation (nonpreparative)
```

IT

```
RL: FMU (Formation, unclassified); POL (Pollutant); FORM (Formation,
     nonpreparative); OCCU (Occurrence)
        (C>1; life cycle anal. of biofuels under different environmental
        aspects)
IT
    Wood
        (beech, wastes, energy carrier; life cycle anal. of biofuels
        under different environmental aspects)
TΤ
        (biofuels; life cycle anal. of biofuels under different environmental
        aspects)
     Barley
IT
     Grass (Poaceae)
     Miscanthus
     Orchard grass
     Poplar (Populus)
     Reed
     Triticale
     Wheat straw
     Willow (Salix)
     Winter wheat
     Wood waste
        (energy carrier; life cycle anal. of biofuels under different
        environmental aspects)
ΙT
     Rape oil
     Rye
     RL: TEM (Technical or engineered material use); USES (Uses)
        (energy carrier; life cycle anal. of biofuels under different
        environmental aspects)
IT
     Fatty acids, uses
     RL: TEM (Technical or engineered material use); USES (Uses)
        (esters, rape-oil, Me esters; life cycle anal. of biofuels
        under different environmental aspects)
     Potato (Solanum tuberosum)
IT
     Wheat
        (ethanol, energy carrier; life cycle anal. of biofuels under
        different environmental aspects)
IT
     Dust
     Environmental pollution
     Particles
        (life cycle anal. of biofuels under different environmental aspects)
IT
     Wood
        (spruce, wastes, energy carrier; life cycle anal. of biofuels
        under different environmental aspects)
     64-17-5, Ethanol, uses
IT
     RL: TEM (Technical or engineered material use); USES (Uses)
        (energy carrier; life cycle anal. of biofuels under different
        environmental aspects)
     64-17-5, Ethanol, uses
TΤ
     RL: TEM (Technical or engineered material use); USES (Uses)
        (fuel; life cycle anal. of biofuels under different
        environmental aspects)
                                                          50-32-8,
     50-00-0, Formaldehyde, formation (nonpreparative)
\mathbf{T}\mathbf{T}
                                                  71-43-2, Benzene, formation
     Benzo[a]pyrene, formation (nonpreparative)
     (nonpreparative) 74-82-8, Methane, formation (nonpreparative)
     124-38-9, Carbon dioxide, formation (nonpreparative) 630-08-0, Carbon
     monoxide, formation (nonpreparative) 7446-09-5, Sulfur dioxide,
     formation (nonpreparative) 7647-01-0, Hydrogen chloride, formation
      (nonpreparative) 7664-41-7, Ammonia, formation (nonpreparative)
     10024-97-2, Nitrous oxide, formation (nonpreparative)
                                                             11104-93-1,
     Nitrogen oxide, formation (nonpreparative)
                                                  41903-57-5,
     Tetrachlorodibenzodioxin
     RL: FMU (Formation, unclassified); POL (Pollutant); FORM (Formation,
```

nonpreparative); OCCU (Occurrence)
(life cycle anal. of biofuels under different environmental aspects)

L7 ANSWER 37 OF 56 CAPLUS COPYRIGHT 2002 ACS

Full Text

- AN 1997:263988 CAPLUS
- DN 126:280153
- TI Producing biodiesel for the "truck in the park" project
- AU Peterson, C.; Reece, Daryl; Thompson, Joe; Beck, Sidney; Haines, H.; Chase, C.
- CS Department of Agricultural Engineering, University of Idaho, Moscow, ID, 83844-2040, USA
- Proceedings Biomass Conference of the Americas: Energy, Environment, Agriculture and Industry, 2nd, Portland, Oreg., Aug. 21-24, 1995 (1995), 921-930 Publisher: National Renewable Energy Laboratory, Golden, Colo. CODEN: 64FMAT
- DT Conference
- LA English
- CC 52-1 (Electrochemical, Radiational, and Thermal Energy Technology) Section cross-reference(s): 45, 59
- One of the principal advantages of biodiesel is it's environmental compatibility. It's biodegradability and reduced toxicity make it an ideal candidate fuel for environmentally sensitive areas. Biodiesel has potential as a fuel for equipment operating in or near waterways, sensitive wildlife habitat and other environmentally sensitive areas. national park system has a mandate to maintain the environment in the areas they supervise. Use of biodiesel could be one more tool in achieving that goal. This paper is a progress report of a joint project between the University of Idaho, The Montana Department of Natural Resources and Conservation, Wyoming Department of Energy, the PNW and Alaska Regional Bioenergy Program, Chrysler Corporation and the National Park Service to fuel an on-road vehicle for service in Yellowstone National Park. A 5.9-L Cummins powered Dodge pickup is operated by NPS with fuel produced by the University of Idaho. Tests include regular dynamometer testing, emissions tests, injector coking anal., oil anal., detailed operational records and fuel characterization tests according to the ASAE proposed Engineering Practice for Testing of Fuels from Biol. Materials, X552.
- ST dynamometer testing emission truck biofuel; rape oil ethyl ester diesel fuel
- IT Diesel engines

Exhaust particles (engine)

(emission and performance of truck operation on rape oil Et ester diesel fuel)

IT Hydrocarbons, occurrence

RL: POL (Pollutant); OCCU (Occurrence)

(emission and performance of truck operation on rape
oil Et ester diesel fuel)

IT Air pollution

(exhaust; emission and performance of truck operation on rape oil Et ester diesel fuel)

IT Fatty acids, uses

RL: TEM (Technical or engineered material use); USES (Uses) (rape-oil, Et esters; emission and performance of truck operation on rape oil Et ester diesel fuel)

IT 630-08-0, Carbon monoxide, occurrence 11104-93-1, Nitrogen oxide nox,

RL: POL (Pollutant); OCCU (Occurrence)

(emission and performance of truck operation on rape
oil Et ester diesel fuel)

L7 ANSWER 38 OF 56 CAPLUS COPYRIGHT 2002 ACS

Full Text

- AN 1997:29421 CAPLUS
- DN 126:91773
- TI Introduction of rapeseed methyl ester in diesel **fuel** the French National Program
- AU Montagne, X.
- CS Institut Français du Petrole, Fr.
- SO Society of Automotive Engineers, [Special Publication] SP (1996), SP-1208(Topics in Alternative Fuels and Their Emissions), 239-248 CODEN: SAESA2; ISSN: 0099-5908
- PB Society of Automotive Engineers
- DT Journal
- LA English
- CC 51-9 (Fossil Fuels, Derivatives, and Related Products)
- The use of bio-fuels in Europe is justified by the common agricultural policy decisions, by the need to improve environment protection and by the search of alternative fossil energy sources. In such a context, France decided to conduct a national expt. to demonstrate that a diesel fuel contg., up to 5%, rapeseed Me ester (RME) could be handled as common diesel fuel by the distributors. Refiners (Elf, TOTAL), car and truck manufacturers (PSA, RENAULT SA, RENAULT TRUCKS), French civil services (industry and agricultural departments, ADEME) and an organization working on vegetable oils (ONIDOL) joined this program implemented and coordinated by IFP. Comprehensive tests were used to assess the impact of RME introduction on the main phys. and chem. characteristics of the blends produced, their compatibility with fuel additives and with plastic or metallic parts of engines and fuel lines. Running tests were used with private car and truck fleets, tests with car and truck engines on bench and chassis dynamometer to assess the behavior on aging, fouling and emissions. This paper presents a synthesis of the results obtained during this program which lasted from 1990 to 1995. Whereas its overall balance is pos. for the use of RME5 blends regarding aging, material compatibility, regulated (CO, UHC, particulates) or unregulated (aldehydes, PAH) pollutant emissions, it also points out some elements which have to be examd. as, for instance, a slight increase in NOx emissions or a slight deposit occurrence. Some improvement opportunities are proposed when needed and prospective development of the vegetable Me ester channel, used as diesel fuel in France or in Europe, is drawn up.
- ST rapeseed methyl ester diesel fuel
- IT Fatty acids, uses

RL: MOA (Modifier or additive use); USES (Uses) (esters, rape-oil, Me esters; introduction of rapeseed Me ester in diesel fuel - the French National Program)

IT Diesel fuel

RL: PEP (Physical, engineering or chemical process); RCT (Reactant); PROC (Process); RACT (Reactant or reagent)

(introduction of rapeseed Me ester in diesel **fuel** - the French National Program)

L7 ANSWER 39 OF 56 CAPLUS COPYRIGHT 2002 ACS

- AN 1996:514904 CAPLUS
- DN 125:200646
- TI Rape seed oil methyl ester fuel as alternative diesel fuel for high speed diesel engines for urban buses
- AU Jankowski, A.; Seczyk, J.; Reksa, M.; Sitnik, L.
- CS Inst. of Aeronautics, Warsaw, Pol.
- SO ICE (American Society of Mechanical Engineers) (1995), 24 (Natural Gas and Alternative Fuels for Engines 1995), 105-109
 CODEN: ICEIEG; ISSN: 1066-5048
- PB American Society of Mechanical Engineers

- DT Journal
- LA English
- CC 52-1 (Electrochemical, Radiational, and Thermal Energy Technology) Section cross-reference(s): 48, 59
- The research concerning the application of rape oil-derived fuels in diesel engines of city buses is presented. The results of testing a RABA MAN Diesel engine of catalog rated power 141 kW at speed 2100 rpm, stroke vol. 10.349 dm3, and direct injection into an HM-type chamber on a test bed are given using a Me ester of rapeseed oil (RME) fuel. The testing comprised the engine performance and exhaust emissions measurement in compliance with EEC 49. The obtained results were compared with those for diesel fuel. Road testing of buses fed with RME fuel was conducted. As shown by the engine performance characteristics, the energy efficiency of the engine was slightly higher when the rape seed oil-derived fuel was used. Approx. 15% redn. in NOx, ~12% redn. in hydrocarbons, and ~40% redn. in soot were obtained using the RME
- ST rapeseed oil methyl ester diesel fuel; engine diesel rapeseed oil fuel
- IT Engines

(diesel, rapeseed oil Me ester as alternative fuel for high-speed diesel engines for urban buses)

- IT Fatty acids, uses
 - RL: TEM (Technical or engineered material use); USES (Uses) (rape-oil, Me esters, rapeseed oil Me ester as alternative fuel for high-speed diesel engines for urban buses)
- IT Fuels, diesel

(substitutes, rapeseed oil Me ester as alternative fuel for high-speed diesel engines for urban buses)

L7 ANSWER 40 OF 56 CAPLUS COPYRIGHT 2002 ACS

- AN 1996:514895 CAPLUS
- DN 125:172181
- TI Thermodynamic analysis of the engine internal process to determine the suitability of vegetable oils as alternative fuels for diesel engines
- AU Raubold, W.
- CS Internal Combustion Engines Dept., Technical Univ. Berlin, Berlin, Germany
- SO ICE (American Society of Mechanical Engineers) (1995), 24(Natural Gas and Alternative Fuels for Engines 1995), 9-15
 CODEN: ICEIEG; ISSN: 1066-5048
- PB American Society of Mechanical Engineers
- DT Journal
- LA English
- CC 48-8 (Unit Operations and Processes)
 Section cross-reference(s): 52
- Test-bed results were presented for a swirl-chamber diesel engine using AB four different kinds of fuel: (1) diesel fuel (ref.), (2) unprocessed rapeseed oil, (3) short-chain (C8,10) fatty acids, and (4) an oil similar to rapeseed oil. The thermodn. anal. of the measured cylinder pressure curves were used to obtain more detailed information, in addn. to the std. performance characteristics and emissions. The resultant heat-release curves helped to show correlations between the properties of the fuels used and the test-bed results. In addn. to the gaseous emissions, the smoke nos. and the particulate emissions according to EPA regulations were also measured. The test engine did not meet the performance and durability requirements when fueled with rapeseed oil. When vegetable oils with long-chain fatty acids are to be burned, the injection system should be modified to alter the injection timing according to engine speed and load. Moderate loads and temps. in the swirl chamber obstruct the vaporization and the onset of combustion of long-chain fuels. In non-adapted swirl-chamber diesel engines, it is

```
most likely that vegetable oils with short-chain fatty acids can be
    burned without major problems. It is likely that the position of the
     injection nozzle can be redesigned so that less coke is formed.
     diesel engine rapeseed oil combustion; fatty acid combustion diesel engine
ST
IT
    Combustion
        (of vegetable oils; thermodn. anal. of combustion of
        vegetable oils as alternative fuel for
        swirl-chamber diesel engines)
    Fuels, diesel
IT
        (substitute; thermodn. anal. of combustion of vegetable oils
        as alternative fuel for swirl-chamber diesel engines)
TΨ
    Rape oil
    RL: NUU (Other use, unclassified); RCT (Reactant); RACT (Reactant or
     reagent); USES (Uses)
        (thermodn. anal. of combustion of vegetable oils as
        alternative fuel for swirl-chamber diesel engines)
    Fatty acids, reactions
     RL: NUU (Other use, unclassified); RCT (Reactant); RACT (Reactant or
     reagent); USES (Uses)
        (C8-10, substitute diesel fuel; thermodn. anal. of combustion
        of vegetable oils as alternative fuel for
        swirl-chamber diesel engines)
IT
     Engines
        (diesel, vegetable oil-fueled; thermodn. anal. of combustion
        of vegetable oils as alternative fuel for
        swirl-chamber diesel engines)
TT
    Engines
        (diesel, rape oil-fueled, thermodn. anal. of combustion of
        vegetable oils as alternative fuel for
        swirl-chamber diesel engines)
     ANSWER 41 OF 56 CAPLUS COPYRIGHT 2002 ACS
Full Text
AN
     1996:245103 CAPLUS
    124:293889
DN
     Reduction of pollutants by premixed combustion of fuel gases derived
TΙ
     from liquid fuels
     Stoffel, B.; Reh, L.
ΑIJ
     Zurich, Switz.
CS
     VDI-Berichte (1995), 1193 (Verbrennung und Feuerungen: 17. Deutscher
SO
     Flammentag, 1995), 549-56
     CODEN: VDIBAP; ISSN: 0083-5560
PΒ
     VDI-Verlag
DT
     Journal
LA
     German
     51-12 (Fossil Fuels, Derivatives, and Related Products)
CC
     Section cross-reference(s): 59
     The combustion of N-free and N-contg. liq. fuels (i.e., MeOH, EtOH,
AB
     n-heptane, unleaded gasoline, propane, light distillate fuel oil, and
     rape-oil Me ester) was examd. in a premix ceramic-fiber burner (15-kW
     thermal capacity). Combustion was characterized by the following steps:
     (1) rapid evapn. of atomized liq. fuel in the presence of a small amt.
     of water vapor in an externally heated evaporator, (2) mixing of the
     fuel gases with preheated combustion air, and (3) combustion at the
     ceramic fiber surface of the burner. For the N-free fuels (all the
     above fuels except for the fuel oil), extremely low NOx (10-50 mg/m3
     at air-fuel ratio, \lambda, 1.2; 5-20 mg/m3 at \lambda ~2) and
     CO emissions were attained. Under these conditions, combustion of the
     N-contg. fuel oil resulted in significantly higher NOx emissions,
     due to the nearly complete conversion of {\tt fuel-N} to {\tt NOx}\,.
     premixed combustion ceramic fiber burner; nitrogen oxide premixed
     combustion; fuel oil premixed combustion nitrogen oxide
```

```
IT
    Burners
        (ceramic fiber; redn. of NOx and CO emissions by premix
        combustion of liq. fuels in ceramic-fiber burner)
IT
        (light distillate, combustion of; redn. of NOx and CO emissions
       by premix combustion of liq. fuels in ceramic-fiber
       burner)
    Combustion
IT
        (premix; redn. of NOx and CO emissions by premix combustion
        of liq. fuels in ceramic-fiber burner)
    Synthetic fibers
IT
    RL: DEV (Device component use); USES (Uses)
        (ceramic, in burners; redn. of NOx and CO emissions
        by premix combustion of liq. fuels in ceramic-fiber
       burner)
    Ceramic materials and wares
TT
     RL: DEV (Device component use); USES (Uses)
        (fibers, in burners; redn. of NOx and CO emissions
        by premix combustion of liq. fuels in ceramic-fiber
       burner)
IT
    Gasoline
     RL: PEP (Physical, engineering or chemical process); RCT (Reactant); PROC
     (Process); RACT (Reactant or reagent)
        (lead-free, combustion of; redn. of NOx and CO emissions by
        premix combustion of liq. fuels in ceramic-fiber
       burner)
    Fatty acids, reactions
TΤ
     RL: PEP (Physical, engineering or chemical process); RCT (Reactant); PROC
     (Process); RACT (Reactant or reagent)
        (rape-oil, Me esters, combustion of; redn. of NOx and CO
        emissions by premix combustion of liq. fuels in
        ceramic-fiber burner)
     630-08-0, Carbon monoxide, formation (nonpreparative)
                                                             11104-93-1,
    Nitrogen oxide (NOx), formation (nonpreparative)
     RL: FMU (Formation, unclassified); POL (Pollutant); FORM (Formation,
     nonpreparative); OCCU (Occurrence)
        (formation of; redn. of NOx and CO emissions by premix
        combustion of liq. fuels in ceramic-fiber burner)
     64-17-5, Ethanol, reactions 67-56-1, Methanol, reactions
                                                                  74-98-6.
TT
     Propane, reactions 142-82-5, Heptane, reactions
     RL: PEP (Physical, engineering or chemical process); RCT (Reactant); PROC
     (Process); RACT (Reactant or reagent)
        (model fuel, combustion of; redn. of NOx and CO
        emissions by premix combustion of liq. fuels in
        ceramic-fiber burner)
     ANSWER 42 OF 56 CAPLUS COPYRIGHT 2002 ACS
L7
     1996:175004 CAPLUS
AN
     124:237078
DN
     Transient testing of soy methyl ester fuels in an indirect injection,
Тľ
     compression ignition engine
     Purcell, D. L.; McClure, B. T.; McDonald, J.; Basu, Hemendra N.
ΑU
     U.S. Bureau Mines, Twin Cities Research Center, Minneapolis, MN, 55417,
CS
     Journal of the American Oil Chemists' Society (1996), 73(3), 381-7
SO
     CODEN: JAOCA7; ISS
N: 0003-021X
PB
    AOCS Press
DT
     Journal
     English
LA
     52-1 (Electrochemical, Radiational, and Thermal Energy Technology)
CC
     Section cross-reference(s): 59
     An evaluation of the exhaust emissions from a compression ignition
AB
```

engine for fuels composed of 100 and 30% Me esters of soy oil (SME) is described. These fuels were compared with a low-sulfur, petroleum #2 diesel fuel in a Caterpillar 3304, prechamber, 75 kW diesel engine, operated over heavy- and light-duty transient test cycles developed by the United States Bureau of Mines. More than 60 h of testing was performed on each fuel. The objective was to det. the influence of the fuels upon diesel particulate matter (DPM) and gaseous emissions. The effect of a modern diesel oxidn. catalyst (DOC) also was detd. in an effort to minimize emissions. Neat SME produced a higher volatile fraction of the DPM, but much less carbon soot fraction, leading to overall DPM redns. of 23 to 30% for the light- and heavy-duty transients. The DOC further reduced the volatile fraction and the total DPM. The SME fuel reduced gaseous emissions of CO by 23% and hydrocarbons by over 30% without increasing NOx. The DOC further reduced CO and hydrocarbon levels. Mutagenicity of the SME exhaust was low. Results indicate that SME fuel, used with a proper DOC, may be a feasible emission redn. technol. for underground mines. soy methyl ester fuel ignition engine Hydrocarbons, formation (nonpreparative) RL: FMU (Formation, unclassified); POL (Pollutant); FORM (Formation, nonpreparative); OCCU (Occurrence) (emission; transient testing of soy Me ester fuels in an indirect injection compression ignition engine) Rare earth metals, uses RL: CAT (Catalyst use); USES (Uses) (oxidn. catalyst, with platinum; transient testing of soy Me ester fuels in an indirect injection compression ignition engine) Ignition Oxidation catalysts (transient testing of soy Me ester fuels in an indirect injection compression ignition engine) (diesel, indirect injection compression ignition; transient testing of soy Me ester fuels in) Exhaust gases (diesel, transient testing of soy Me ester fuels in an indirect injection compression ignition engine) Fatty acids, uses RL: TEM (Technical or engineered material use); USES (Uses) (soya, Me esters; transient testing of soy Me ester fuels in an indirect injection compression ignition engine) Fuels, diesel (substitutes, transient testing of soy Me ester fuels in an indirect injection compression ignition engine) 50-00-0, Formaldehyde, formation (nonpreparative) 630-08-0, Carbon monoxide, formation (nonpreparative) 10102-43-9, Nitric oxide, formation 10102-44-0, Nitrogen dioxide, formation (nonpreparative) (nonpreparative) 11104-93-1, Nitrogen oxide, formation (nonpreparative) RL: FMU (Formation, unclassified); POL (Pollutant); FORM (Formation, nonpreparative); OCCU (Occurrence) (emission; transient testing of soy Me ester fuels in an indirect injection compression ignition engine) 7440-06-4, Platinum, uses RL: CAT (Catalyst use); USES (Uses) (oxidn. catalyst, with rare earth; transient testing of soy Me ester fuels in an indirect injection compression ignition

L7 ANSWER 43 OF 56 CAPLUS COPYRIGHT 2002 ACS Full Text

AN 1996:122111 CAPLUS

engine)

TT

IT

TT

IT

ΙT

IT

IT

- DN 124:180971
- TI Combustion of soybean oil methyl ester in a direct injection diesel engine
- AU Scholl, Kyle W.; Sorenson, Spencer C.
- CS Caterpillar Inc., USA
- SO Alternate Fuels: A Decade of Success and Promise (1994), 555-67.
 Editor(s): Bata, Reda Mohamed. Publisher: Society of Automotive Engineers,
 Warrendale, Pa.
 CODEN: 62KQAI
- DT Conference
- LA English
- CC 52-1 (Electrochemical, Radiational, and Thermal Energy Technology) Section cross-reference(s): 59
- The purpose of this study is to investigate the combustion of soybean AB oil Me ester in a direct injection diesel engine, and compare it to that of a conventional diesel fuel. Exptl. measurements of performance, emissions, and rate of heat release were performed as a function of engine load for different fuel injection timings, and injector orifice diams. It was found that overall, the soybean oil Me ester behaved comparably to diesel fuel in terms of performance and rate of heat release. The Me ester fuel gave lower HC emissions and smoke no. than diesel fuel at optimum operating conditions. The results for CO emissions were varied. NOx emissions were strongly related to the cylinder pressure development. Changing the injection orifice diam. had less effect on engine performance when using diesel fuel, than with Me ester fuel. A smaller orifice diam. gave higher cylinder pressure and max. rate of pressure increase, higher NOx emissions, and a larger amt. of premixed burning for both fuels. The variation of injection timing had a pronounced effect on performance and emissions for both fuels. Conventional trends in emissions, performance and rate of heat release were obsd. for both fuels.
- ST combustion soybean **oil** methyl ester engine; diesel engine soybean **oil** methyl ester
- IT Combustion

(combustion of soybean **oil** Me ester in a direct injection diesel engine)

IT Hydrocarbons, formation (nonpreparative)

RL: FMU (Formation, unclassified); POL (Pollutant); FORM (Formation, nonpreparative); OCCU (Occurrence)

(emissions; combustion of soybean oil Me ester in a direct injection diesel engine)

IT Engines

(diesel, combustion of soybean **oil** Me ester in a direct injection diesel engine)

IT Fatty acids, uses

RL: RCT (Reactant); TEM (Technical or engineered material use); RACT (Reactant or reagent); USES (Uses)

(esters, soya, Me esters; combustion of soybean **oil** Me ester in a direct injection diesel engine)

IT 630-08-0, Carbon monoxide, formation (nonpreparative) 11104-93-1, Nitrogen oxide, formation (nonpreparative)

RL: FMU (Formation, unclassified); POL (Pollutant); FORM (Formation, nonpreparative); OCCU (Occurrence)

(emissions; combustion of soybean oil Me ester in a direct injection diesel engine)

L7 ANSWER 44 OF 56 CAPLUS COPYRIGHT 2002 ACS

- AN 1996:48676 CAPLUS
- DN 124:265467
- TI Comparative study of the boiling characteristics of vegetable oils for the evaluation as fuel
- AU Wenzel, G.; Lammers, P. Schulze

Inst. Landtechnik, Univ. Bonn, Bonn, D-53115, Germany CS Fett Wissenschaft Technologie (1995), 97 (Sonderausgabe 1), 475-81 SO CODEN: FWTEEG; ISSN: 0931-5985 Konradin-Industrieverlag PB DT Journal German LA 52-1 (Electrochemical, Radiational, and Thermal Energy Technology) CC Section cross-reference(s): 45 The boiling curves of vegetable oils (hazelnut, rapeseed, rice seed, AΒ sesame, cotton seed, safflower) were detected regarding their use as engine fuels. The diagrams are very similar. The oils decomp. during distn., the decompn. products are produced in different quantities, and 30% remain as a polymer tar. Shifting of b.ps. from 250-270° in the first fraction indicates a relation between b.p. and compn. of vegetable oils. The distn. products are instable and become dark with time. During decompn., acid water contg. short chain O compds. is generated, which ignites less well than long chain C enriched compds. This could explain the increased emission of aldehydes and ketones in exhaust gases of vegetable oils. vegetable oil boiling curve fuel STΙT Boiling point Distillation (boiling characteristics of vegetable oils for evaluation as Fatty acids, biological studies TT RL: BOC (Biological occurrence); BSU (Biological study, unclassified); BIOL (Biological study); OCCU (Occurrence) (boiling characteristics of vegetable oils for evaluation as fuel) Cottonseed oil TT RL: NUU (Other use, unclassified); PRP (Properties); USES (Uses) (boiling characteristics of vegetable oils for evaluation as fuel) IT Rape oil RL: NUU (Other use, unclassified); PRP (Properties); USES (Uses) (boiling characteristics of vegetable oils for evaluation as fuel) IT Safflower oil RL: NUU (Other use, unclassified); PRP (Properties); USES (Uses) (boiling characteristics of vegetable oils for evaluation as fuel) IT Fuels (bio-, boiling characteristics of vegetable oils for evaluation as fuel) Fats and Glyceridic oils TΤ RL: NUU (Other use, unclassified); PRP (Properties); USES (Uses) (hazelnut, boiling characteristics of vegetable oils for evaluation as fuel) Fats and Glyceridic oils IT RL: NUU (Other use, unclassified); PRP (Properties); USES (Uses) (rice bran, boiling characteristics of vegetable oils for evaluation as fuel) Fats and Glyceridic oils RL: NUU (Other use, unclassified); PRP (Properties); USES (Uses) (sesame, boiling characteristics of vegetable oils for evaluation as fuel) Fats and Glyceridic oils TT RL: NUU (Other use, unclassified); PRP (Properties); USES (Uses) (vegetable, boiling characteristics of vegetable oils for

57-10-3, Hexadecanoic acid, biological studies 57-11-4, Octadecanoic

acid, biological studies 60-33-3, Linolic acid, biological studies

evaluation as fuel)

TT

```
463-40-1, Linolenic acid 27104-13-8 28929-01-3
RL: BOC (Biological occurrence); BSU (Biological study, unclassified);
BIOL (Biological study); OCCU (Occurrence)
(boiling characteristics of vegetable oils for evaluation as fuel)
```

L7 ANSWER 45 OF 56 CAPLUS COPYRIGHT 2002 ACS

Full Text

- AN 1995:901606 CAPLUS
- DN 124:33576
- TI Fatty acid methyl esters as diesel fuel. Economic, ecological and energetic implications
- AU Gomez Herrera, Carlos
- CS Academico Numerario Real Academia Sevillana Ciencias, Seville, 41012, Spain
- SO Grasas y Aceites (Seville) (1995), 46(2), 121-9 CODEN: GRACAN; ISSN: 0017-3495
- PB Instituto de la Grasa y sus Derivados
- DT Journal; General Review
- LA Spanish
- CC 52-0 (Electrochemical, Radiational, and Thermal Energy Technology)
 Section cross-reference(s): 51
- A review with 13 refs. Rapeseed oils are transesterified with methanol to obtain fatty acid Me esters. Blends of these esters with diesel oil are sold in petrol stations in different European countries like any other fuel. This informative article starts by reviewing basic characteristics of diesel fuel, and continues with an anal. of phys. properties, chem. compn. and present specifications for the rapeseed Me esters. Subsequently several implications derived from the industrial development of this biofuel are discussed. These implications are economic, ecol. (nearly zero emissions for whole cycle of carbon dioxide, other exhaust emissions from combustion, eco-balances), and energetic (complete evaluation of energy expenditure for prodn., energetic ratios).
- ST review fatty acid methyl ester fuel; diesel fuel fatty acid ester review; rapeseed oil ester diesel fuel review
- IT Fatty acids, uses
 - RL: TEM (Technical or engineered material use); USES (Uses)
 (Me esters, economic and ecol. and energetic implications fatty
 acid Me esters as diesel fuel)
- IT Fatty acids, uses
 - RL: TEM (Technical or engineered material use); USES (Uses) (rape-oil, Me esters, economic and ecol. and energetic implications fatty acid Me esters as diesel fuel)
- IT Fuels, diesel

(substitutes, economic and ecol. and energetic implications fatty acid Me esters as diesel fuel)

L7 ANSWER 46 OF 56 CAPLUS COPYRIGHT 2002 ACS

- AN 1995:627087 CAPLUS
- DN 123:118312
- TI Rmissions characteristics of soy methyl ester fuels in an IDI compression ignition engine
- AU McDonald, J. F.; Purcell, D. L.; McClure, B. T.; Kittelson, D. B.
- CS U.S. Bureau of Mines, USA
- SO Society of Automotive Engineers, [Special Publication] SP (1995), SP-1093, 191-207
 CODEN: SAESA2; ISSN: 0099-5908
- DT Journal
- LA English

- CC 52-1 (Electrochemical, Radiational, and Thermal Energy Technology) Section cross-reference(s): 45, 59
- As part of an ongoing program to control the emissions of diesel-powered AB equipment used in underground mines, the U.S. Bureau of Mines evaluated exhaust emissions from a compression ignition engine using oxygenated diesel fuels and a diesel oxidn. catalyst (DOC). The fuels include neat (100%) soy Me ester (SME), and a blend of 30 vol.% SME with 70% petroleum diesel fuel. A Caterpillar 3304 PCNA engine was tested for approx. 50 h on each fuel. Compared with com. low-sulfur diesel fuel (D2), neat SME increased volatile org. diesel particulate matter (DPM) but greatly decreased non-volatile DPM, for a net decrease in total DPM. The DOC further reduced volatile and total DPM. NOx emissions were slightly reduced for the case of neat SME, but otherwise were not significantly affected. Peak brake power decreased 9% and brake specific fuel consumption increased 13 to 14% for the neat Me soyate because of its lower energy content compared with D2. An anal. of apparent heat release rates found that SME exhibited a shorter ignition delay and some part load redns. in premixed burn.
- ST mine diesel exhaust **emission** oxidn catalyst; **fuel** diesel soybean **oil** Me ester
- IT Fuels, diesel

Ignition

(emissions characteristics of soy Me ester fuels from diesel engine in mine)

IT Oxidation catalysts

(exhaust; emissions characteristics of soy Me ester

fuels from diesel engine in mine)

IT Exhaust gases

(catalytic-converter, **emissions** characteristics of soy Me ester **fuels** from diesel engine in mine)

IT Exhaust gases

(diesel, emissions characteristics of soy Me ester fuels from diesel engine in mine)

IT Fatty acids, uses

RL: TEM (Technical or engineered material use); USES (Uses) (soya, Me esters, emissions characteristics of soy Me ester fuels from diesel engine in mine)

IT 11104-93-1, Nitrogen oxide, occurrence

RL: POL (Pollutant); OCCU (Occurrence)

(emissions characteristics of soy Me ester fuels from diesel engine in mine)

L7 ANSWER 47 OF 56 CAPLUS COPYRIGHT 2002 ACS

- AN 1995:626783 CAPLUS
- DN 123:118304
- TI Performance of rapeseed methyl ester in diesel engine
- AU Nwafor, O. M. I.; Rice, G.
- CS Department of Engineering, University of Reading, UK
- SO Renewable Energy (1995), 6(3), 335-42 CODEN: RNENE3; ISSN: 0960-1481
- DT Journal
- LA English
- CC 52-1 (Electrochemical, Radiational, and Thermal Energy Technology)
 Section cross-reference(s): 45
- AB The paper presents the results of a research carried out to evaluate the performance of rapeseed Me ester (RME) on an unmodified diesel engine. The paper compares the effect of using RME in a diesel engine with baseline test on diesel fuel. The test results on rapeseed Me ester showed high friction power and a net redn. in hydrocarbon emissions. Carbon deposits on the injector were similar to those obsd. when running on diesel fuel. Fuel diln. of the lubricating oil was noted,

```
indicating an incomplete combustion due to the still low volatility of
    rapeseed Me ester diesel fuel; friction hydrocarbon emission rapeseed
ST
     Me ester
    Fuels, diesel
IT
        (performance of rapeseed Me ester as)
ΙT
    Combustion
       Ignition
        (performance of rapeseed Me ester in diesel engine)
     Lubricating oils
IT
        (diesel, diln. with rapeseed Me ester fuel during operation)
     Exhaust gases
IT
        (diesel, hydrocarbon emissions from rapeseed Me ester)
     Fatty acids, uses
TΨ
     RL: TEM (Technical or engineered material use); USES (Uses)
        (rape-oil, Me esters, fuel; performance of rapeseed
        Me ester in diesel engine)
     ANSWER 48 OF 56 CAPLUS COPYRIGHT 2002 ACS
L7
Full Text
     1995:595889 CAPLUS
AN
DN
     123:60892
     Plant oils as liquid energy carriers
TΙ
ΑU
     Widmann, Bernhard A.
     Bayerische Landesanstalt Landtechnik, Freising-Weihenstephan, Germany
CS
     GSF-Ber. (1995), 01/95, 25-45
SO
     CODEN: GSFBEM; ISSN: 0721-1694
DТ
     Report
     German
LA
     51-9 (Fossil Fuels, Derivatives, and Related Products)
CC
     Section cross-reference(s): 45, 59
     After a short summary of the development of and rationale for large-scale
AΒ
     use of vegetable oil-derived diesel fuel, engine tests were carried
     out for diesel fuel mixts. contg. 10% rapeseed oil or rapeseed-oil
     Me esters, pure rapeseed oil, and rapeseed-oil Me esters. Despite
     favorable emissions data and engine compatibility results, economically,
     the introduction of rapeseed oil-derived substitute diesel fuels makes
     more sense in local agricultural areas where markets such as inland marine
     diesel fuels, agricultural fuels, and protected watershed and mountain
     regions can provide special niches or take advantage of the favorable
     environmental aspects of vegetable oil-derived diesel fuels. It is
     entirely possible, at least for Germany, that a more widespread use of
     these fuels into the general diesel market will require large imports of
     raw materials, esp. from developing countries.
     substitute diesel fuel vegetable oil; rapeseed oil Me ester
     substitute diesel; air pollution vegetable oil diesel; engine
     compatibility vegetable oil diesel; economics vegetable substitute
     diesel fuel
     Air pollution
IT
        (air pollution and engine compatibility testing of vegetable
        oil-based substitute diesel fuels)
     Rape oil
IT
     RL: IMF (Industrial manufacture); NUU (Other use, unclassified); PREP
     (Preparation); USES (Uses)
        (air pollution and engine compatibility testing of vegetable
        oil-based substitute diesel fuels)
        (compression-ignition; air pollution and engine compatibility
```

testing of vegetable oil-based substitute diesel

RL: FMU (Formation, unclassified); POL (Pollutant); FORM (Formation,

Aldehydes, formation (nonpreparative)

```
nonpreparative); OCCU (Occurrence)
        (emissions; air pollution and engine compatibility testing of
       vegetable oil-based substitute diesel fuels)
    Fuels, diesel
TТ
        (substitute; air pollution and engine compatibility testing of
        vegetable oil-based substitute diesel fuels)
    Hydrocarbons, formation (nonpreparative)
TΨ
     RL: FMU (Formation, unclassified); POL (Pollutant); FORM (Formation,
     nonpreparative); OCCU (Occurrence)
        (unburned emissions; air pollution and engine compatibility
        testing of vegetable oil-based substitute diesel
     Aromatic hydrocarbons, formation (nonpreparative)
     RL: FMU (Formation, unclassified); POL (Pollutant); FORM (Formation,
     nonpreparative); OCCU (Occurrence)
        (C6-8, emissions; air pollution and engine compatibility
        testing of vegetable oil-based substitute diesel
        fuels)
     Engines
TΤ
        (diesel, air pollution and engine compatibility testing of vegetable
        oil-based substitute diesel fuels)
     Aromatic hydrocarbons, formation (nonpreparative)
TΤ
     RL: FMU (Formation, unclassified); POL (Pollutant); FORM (Formation,
     nonpreparative); OCCU (Occurrence)
        (polycyclic, emissions; air pollution and engine
        compatibility testing of vegetable oil-based substitute
        diesel fuels)
IT
     Fatty acids, uses
     RL: IMF (Industrial manufacture); NUU (Other use, unclassified); PREP
     (Preparation); USES (Uses)
        (rape-oil, Me esters, air pollution and engine compatibility
        testing of vegetable oil-based substitute diesel
        fuels)
     Fats and Glyceridic oils
IT
     RL: IMF (Industrial manufacture); NUU (Other use, unclassified); PREP
     (Preparation); USES (Uses)
        (vegetable, air pollution and engine compatibility testing of vegetable
        oil-based substitute diesel fuels)
     124-38-9, Carbon dioxide, formation (nonpreparative)
                                                             630-08-0, Carbon
     monoxide, formation (nonpreparative)
                                           7446-09-5, Sulfur dioxide,
     formation (nonpreparative) 11104-93-1, Nitrogen oxide, formation
     (nonpreparative)
     RL: FMU (Formation, unclassified); POL (Pollutant); FORM (Formation,
     nonpreparative); OCCU (Occurrence)
        (emissions; air pollution and engine compatibility testing of
        vegetable oil-based substitute diesel fuels)
     ANSWER 49 OF 56 CAPLUS COPYRIGHT 2002 ACS
L7
Full Text
     1995:589122 CAPLUS
AN
DN
     123:118330
     Rmissions from biodiesel combustion in a boiler of a heating system
ΤI
     De Stefanis, P.; Di Palo, C.; Montani, R.; Zagaroli, M.; Di Palo, V.;
AU
     Rotatori, M.
     Dip. Ambiente, ENEA, S. Maria di Galeria, 00060, Italy
CS
     Rivista dei Combustibili (1994), 48(9), 337-42
SO
     CODEN: RICOAP; ISSN: 0370-5463
     Centro Graphico Linate
PR
DΤ
     Journal
     Italian
T.A
     52-1 (Electrochemical, Radiational, and Thermal Energy Technology)
CC
```

Section cross-reference(s): 59

- The paper examines the results of combustion tests performed on a boiler of a hot water central heating system. The tested biodiesel **fuel** was a Me ester produced from vegetable **oils** by a transesterification reaction. The aim of the tests was the comparison between the biodiesel **emissions** and the gas **oil** ones, when **burning** at the same operating conditions. Even though the results of the tests do not allow to draw a conclusion, they provided the base for future expts.
- ST biodiesel **fuel** combustion **emission** boiler heater; vegetable **oil** methyl ester biodiesel **fuel**
- IT Combustion

(emissions from combustion of biodiesel fuel in boiler of hot water heating system)

IT Waste gases

(from combustion of biodiesel **fuel** in boiler of hot water heating system)

IT Fuels, diesel

(substitutes, vegetable oil Me ester; emissions from combustion of biodiesel fuel in boiler of hot water heating system)

IT Fatty acids, uses

RL: PEP (Physical, engineering or chemical process); TEM (Technical or engineered material use); PROC (Process); USES (Uses)

(vegetable-oil, Me esters, biodiesel fuel;
emissions from combustion of biodiesel fuel in boiler
of hot water heating system)

- IT 50-00-0, Formaldehyde, occurrence 50-32-8, Benzo[a]pyrene, occurrence 53-70-3, Dibenz[a,h]anthracene 56-55-3, Benz[a]anthracene 75-07-0, Acetaldehyde, occurrence 85-01-8, Phenanthrene, occurrence 120-12-7, Anthracene, occurrence 129-00-0, Pyrene, occurrence 191-24-2, Benzo[ghi]perylene 193-39-5, Indeno[1,2,3-cd]pyrene 205-99-2, Benz[e]acephenanthrylene 206-44-0, Fluoranthene 207-08-9, Benzo[k]fluoranthene 218-01-9, Chrysene 630-08-0, Carbon monoxide, occurrence 7446-09-5, Sulfur dioxide, occurrence 11104-93-1, Nitrogen oxide, occurrence
 - RL: POL (Pollutant); OCCU (Occurrence)
 (waste gases contg.; emissions from combustion of biodiesel
 fuel in boiler of hot water heating system)
- L7 ANSWER 50 OF 56 CAPLUS COPYRIGHT 2002 ACS

Full Text

- AN 1995:575721 CAPLUS
- DN 123:12364
- TI A life-cycle inventory for the production of alcohol sulfates in Europe
- AU Hirsinger, F.; Schick, K.-P.
- CS Duesseldorf, Germany
- SO Tenside, Surfactants, Detergents (1995), 32(2), 128-32, 134-9 CODEN: TSDEES; ISSN: 0932-3414
- PB Hanser
- DT Journal; General Review
- LA English
- CC 46-0 (Surface Active Agents and Detergents)
- AP Review with 1 ref. on the resources and energy requirements and environmental emission arising from the prodn. of 1000 kg of alc. sulfates (AS) based on petrochem. (AS-PC) and 3 oleochem. sources: palm oil (AS-PO), palm kernel oil (AS-PKO), and coconut oil (AS-CNO). The total energy requirements range from 52 to 73 GJ/1000 kg (AS-PC). The fossil-energy requirements range from 17.0 GJ (AS-PO) to 69.8 GJ (AS-PC), representing 33% and 95%, resp., of the total energy requirement for the products. Most of the atm. emissions arise from the prodn. and consumption of fuels and reflect the process energy requirements. Methane emissions arise from the manuf. of AS-PO and AS-PKO. Non-fossil CO2 arises from AS-PKO and AS-CNO prodn. due to

combustion of fibers and shells for energy generation at the oil mill. Most of the waterborne emissions arise from processing operations. COD ranges from 1.6 kg/1000 kg (AS-Pc) to 11 kg (AS-CNO), and dissolved solids range from 5.3 kg to 32 kg, resp. AS-PKO and AS-PO have a COD of about 3 kg and dissolved solids of about 7.6 kg. The high waterborne emissions from coconut systems arise from the run-off coconut water when the nuts are halved. The major part of the solid waste is fuel-related, ranging from 59% (AS-PKO) to 83% (AS-Pc) of the total solid waste, which ranges from 68 kg (AS-PO) to 88 kg (AS-PKO).

- ST review alc sulfate surfactant prodn; anionic surfactant prodn pollution review
- IT Waste solids

Wastewater

(prepn. of and pollution from prepn. of alc. sulfate surfactants)

IT Alcohols, preparation

RL: POL (Pollutant); SPN (Synthetic preparation); OCCU (Occurrence); PREP (Preparation)

(prepn. of and pollution from prepn. of alc. sulfate surfactants)

IT Coconut oil

RL: POL (Pollutant); SPN (Synthetic preparation); OCCU (Occurrence); PREP (Preparation)

(alkyl sulfate, prepn. of and pollution from prepn. of alc. sulfate surfactants)

IT Surfactants

(anionic, prepn. of and pollution from prepn. of alc. sulfate surfactants)

IT Fatty acids, preparation

RL: POL (Pollutant); SPN (Synthetic preparation); OCCU (Occurrence); PREP (Preparation)

(palm-oil, sulfo, esters, prepn. of and pollution from prepn. of alc. sulfate surfactants)

- L7 ANSWER 51 OF 56 CAPLUS COPYRIGHT 2002 ACS
- <u>Full Text</u>
- AN 1994:327416 CAPLUS
- DN 120:327416
- TI Performance and emission characteristics of a diesel engine operating on safflower seed oil methyl ester
- AU Isigigur, A.; Karaosmanoglu, F.; Aksoy, H. A.; Hamdullahpur, F.; Gulder, O. L.
- CS Chem. Eng. Dep., Istanbul Tech. Univ., Istanbul, 80626, Turk.
- SO Applied Biochemistry and Biotechnology (1994), 45-46, 93-102 CODEN: ABIBDL; ISSN: 0273-2289
- DT Journal
- LA English
- CC 52-1 (Electrochemical, Radiational, and Thermal Energy Technology) Section cross-reference(s): 51
- AB Evaluation and testing of safflower seed oil Me ester as a diesel fuel alternative was carried out. The kinematic viscosity and ASTM fuel properties of the Me ester fuel were within the limits specified for Grade No. 2-D diesel fuel. Engine tests were performed on a 4-cylinder, direct-injection CI (compression ignition) engine using Me ester and ref. diesel fuel; engine performance and exhaust emission characteristics were detd. Safflower seed oil Me ester revealed similar engine performance characteristics to the ref. Grade No. 2-D diesel fuel. Lower CO and hydrocarbon emissions were obtained when Me ester was used, and the negligible amt. of S content was an addnl. advantage of Me ester over diesel fuel.
- ST safflower oil methyl ester diesel fuel; engine safflower oil ester diesel emission
- IT Exhaust gases

(from diesel engine fueled with safflower-oil Me ester, low

```
pollutant levels in)
     Hydrocarbons, miscellaneous
TΤ
     RL: MSC (Miscellaneous)
        (in flue gases from safflower-oil Me ester-fueled diesel
        engine, low levels of)
TT
     Engines
        (diesel, direct-injection, compression-ignition, safflower-
        oil Me ester-fueled, performance of)
     Fatty acids, esters
IT
     RL: USES (Uses)
        (safflower-oil, Me esters, as diesel fuel, engine
        performance and emissions using)
TΤ
     Fuels, diesel
        (substitutes, safflower-oil Me ester, engine performance and
        emissions using)
     630-08-0, Carbon monoxide, miscellaneous 7704-34-9, Sulfur,
TT
     miscellaneous
     RL: MSC (Miscellaneous)
        (in flue gases from safflower-oil Me ester-fueled diesel
        engine, low levels of)
     ANSWER 52 OF 56 CAPLUS COPYRIGHT 2002 ACS
L7
Full Text
     1994:138747 CAPLUS
AN
     120:138747
DN
     Effect of fuel modifications on Detroit diesel engine exhaust emissions
ΤI
     Winsor, R E.
ΑU
     Detroit Diesel Corp., USA
CS
     IMechE Seminar Publication (1993), (2, Fuels for Automotive and Industrial
SO
     Diesel Engines), 35-43
     CODEN: ISEME4; ISSN: 1357-9193
DT
     Journal; General Review
     English
LA
     51-0 (Fossil Fuels, Derivatives, and Related Products)
CC
     Section cross-reference(s): 59
     A review, with 9 refs., of changes in pollutant emissions (esp.
AB
     hydrocarbons, CO, NOx, and particulates) based on fuel compns. and
     different types of synthetic diesel fuel and fuel additives. Types of
     fuels evaluated included rapeseed oil Me esters, soybean oil Me
     esters, ignition improvers, oxygenates, and diglyme and di-Me carbonate
     additives. Reformulated fuels can significantly reduce NOx, CO, and
     particulates from heavy-duty engines; similarly, oxygenated fuel
     additives can reduce particulates from heavy-duty engines by at least 20%.
     Ignition improver additives can provide significant NOx emission redn.
     Transient emission levels as low as 0.056 g/bhp-hr particulates with 4.2
     g/bhp-hr NOx were achieved without exhaust gas treatment.
     review diesel fuel air pollution; exhaust emission diesel fuel
     review; reformulated diesel fuel pollution review; synthetic diesel
     fuel pollution review; oxygenated diesel fuel pollution review;
     ignition improver diesel pollution review; nitrogen oxide diesel fuel
     review; particulate diesel fuel review
ΙT
     Fuels, diesel
        (compn. of and additives for, pollutant emissions in relation
        to)
     Alcohols, uses
     RL: USES (Uses)
        (diesel fuel contg., exhaust emissions from)
ΙT
     Ignition
        (of diesel fuel, additives for improvement of, exhaust
        emissions in relation to)
IT
     Particles
```

(airborne, formation of, in combustion of diesel fuel, effect

```
of fuel compn. and additives on)
IT
    Exhaust gases
        (diesel, air pollution by, effect of fuel compn. and
        additives on)
TT
    Fatty acids, esters
    RL: USES (Uses)
        (rape-oil, Me esters, diesel fuel contg., exhaust
        emissions from)
ΙT
    Fatty acids, esters
    RL: USES (Uses)
        (soya, Me esters, diesel fuel contg., exhaust
        emissions from)
                         616-38-6, Dimethyl carbonate
    111-96-6, Diglyme
ΤТ
    RL: USES (Uses)
        (diesel fuel contg., exhaust emissions from)
    7782-44-7D, Oxygen, org. compds.
TΤ
     RL: RCT (Reactant); RACT (Reactant or reagent)
        (diesel fuel contg., exhaust emissions from)
    630-08-0P, Carbon monoxide, preparation 11104-93-1P, Nitrogen oxide,
IT
    preparation
    RL: FORM (Formation, nonpreparative); PREP (Preparation)
        (formation of, in combustion of diesel fuel, effect of
        fuel compn. and additives on)
    ANSWER 53 OF 56 CAPLUS COPYRIGHT 2002 ACS
L7
Full Text
    1994:81416 CAPLUS
AN
    120:81416
DN
    Combustion of soybean oil methyl ester in a direct injection diesel engine
ΤI
     Scholl, Kyle W.; Sorenson, Spencer C.
ΑU
     Caterpillar Inc., USA
CS
     Society of Automotive Engineers, [Special Publication] SP (1993),
     SP-958 (New Developments in Alternative Fuels and Gasolines for SI and CI
    Engines), 211-23
    CODEN: SAESA2; ISSN: 0099-5908
DΤ
    Journal
    English
LA
    52-1 (Electrochemical, Radiational, and Thermal Energy Technology)
CC
     Section cross-reference(s): 59
     The purpose of this study is to investigate the combustion of soybean
AB
     oil Me ester in a direct injection diesel engine, and compare it to that
     of a conventional diesel fuel. Exptl. measurements of performance,
     emissions, and rate of heat release were performed as a function of
     engine load for different fuel injection timings, and injector orifice
     diams. It was found that overall, the soybean oil Me ester behaved
     comparably to diesel fuel in terms of performance and rate of heat
     release. The Me ester fuel gave lower hydrocarbon emissions and smoke
     no. than diesel fuel at optimum operating conditions. The results for
     CO emissions were varied. NOx emissions were strongly related to the
     cylinder pressure development. Changing the injection orifice diam. had
     less effect on engine performance when using diesel fuel, than with Me
     ester fuel. A smaller orifice diam. gave higher cylinder pressure and
     max. rate of pressure increase, higher NOx emissions, and a larger amt.
     of premixed burning for both fuels. The variation of injection timing
     had a pronounced effect on performance and emissions for both fuels.
     Conventional trends in emissions, performance and rate of heat release
     were obsd. for both fuels.
     soybean oil methyl ester fuel diesel; engine fuel soybean oil methyl ester
ST
     Hydrocarbons, miscellaneous
     RL: MSC (Miscellaneous)
        (emission of, in exhaust gases of soybean oil Me
```

ester-fueled direct injection diesel engine)

```
IT
    Combustion
        (of soybean oil Me ester, in direct injection diesel engine)
IT
    Exhaust gases
        (of soybean oil Me ester-fueled direct-injection diesel
        engine, emissions in)
IT
        (diesel, direct-injection soybean oil Me ester-fueled,
        performance of)
IT
    Fatty acids, esters
    RL: RCT (Reactant); RACT (Reactant or reagent)
        (soya, Me esters, combustion of, in direct injection diesel engine)
    7782-44-7
TT
     RL: USES (Uses)
        (combustion, of soybean oil Me ester, in direct injection
        diesel engine)
    11104-93-1, Nitrogen oxide, uses
TΨ
     RL: USES (Uses)
        (emission of, in exhaust gases of soybean oil Me
        ester-fueled direct injection diesel engine)
    630-08-0, Carbon monoxide, miscellaneous
ΙT
     RL: MSC (Miscellaneous)
        (emission of, in exhaust gases of soybean oil Me
        ester-fueled direct injection diesel engine)
    ANSWER 54 OF 56 CAPLUS COPYRIGHT 2002 ACS
L7
    1993:172370 CAPLUS
AN
    118:172370
DN
ΤI
    Water-in-oil-in-water emulsion fuels and their combustion
    Kanekiyo, Katsumasa
IN
    Nippon Kankyo Assessment Center, Japan
PA
SO
    Jpn. Kokai Tokkyo Koho, 6 pp.
     CODEN: JKXXAF
DT
    Patent
LΑ
     Japanese
IC
     ICM C10L001-32
     51-12 (Fossil Fuels, Derivatives, and Related Products)
     Section cross-reference(s): 59
FAN.CNT 1
     PATENT NO.
                                          APPLICATION NO. DATE
                     KIND DATE
     ______
                                                           19910128
     JP 04252294
                      A2
                           19920908
                                          JP 1991-41447
PΙ
                      B4
                           19940921
     JP 06074430
     The fuels are obtained by stirring 75-95 parts heavy oils having
AB
     viscosity 150-4000 cSt (50°), 5-25 parts H2O, and 0.01-0.5%
     nonionic surfactants (HLB value 5-12) of C4-12 linear or branched alkyl-
     or alkenyl-contg. polyoxyethylene Ph ethers (I), C8-20 (un)satd. linear or
     branched higher aliph. alc.-derived polyoxyethylene alkyl or alkenyl
     ethers (II), C8-20 (un)satd. linear or branched higher fatty
     acid-derived polyoxyethylene alkanoyl or alkenoyl ethers (III), and/or
     C8-20 (un) satd. linear or branched higher fatty acid alkanol
     amide-derived polyoxyethylene higher fatty acid alkanol amide ethers
     (IV) at 30-80° to give a water-in-oil emulsion (W) and stirring
     15-30 parts H2O, 0.01-1.0% surfactants contg. ≥1 nonionic
     surfactants (HLB value 10-18) selected from I-IV, and 70-85 parts W at
     30-80°, and their combustion process comprises preheating the
     fuels to decrease viscosity to ≤50 cSt and burning with an
     atomization burner. Emission of air pollutants, e.g., NOx, SOx, dust,
     etc., are prevented by using the fuels and the combustion process.
     emulsion fuel heavy oil surfactant; combustion emulsion fuel
     atomization burner; air pollution prevention emulsion fuel
```

Air pollution

ΙT

```
(prevention, water-in-oil-in-water emulsion fuels
       for)
    Polyethers, uses
TТ
    RL: USES (Uses)
       (surfactants, emulsion fuels contg. water and heavy
       oils and, for prevention of air pollution)
IT
    Surfactants
        (anionic, emulsion fuels contg. water and heavy oils
       and, for prevention of air pollution)
ΙT
    Fuel oil
        (emulsions, water-in-oil-in-water, contg. heavy oils
       and nonionic surfactants, for prevention of air pollution)
    Petroleum
TΤ
    RL: USES (Uses)
        (heavy, emulsion fuels contg. water and nonionic surfactants
       and, for prevention of air pollution)
    Surfactants
IT
        (nonionic, emulsion fuels contg. water and heavy oils
       and, for prevention of air pollution)
ΙT
    Combustion
        (spray, of water-in-oil-in-water emulsion fuels,
       for prevention of air pollution)
    7782-44-7
    RL: RCT (Reactant); RACT (Reactant or reagent)
        (combustion, spray, of water-in-oil-in-water emulsion
       fuels, for prevention of air pollution)
    8061-51-6, Sodium lignin sulfonate 9008-63-3 9016-45-9, Nonyl phenol
IT
    ethoxylate 25322-68-3D, derivs.
    RL: USES (Uses)
        (surfactants, emulsion fuels contg. water and heavy
       oils and, for prevention of air pollution)
   ANSWER 55 OF 56 CAPLUS COPYRIGHT 2002 ACS
T.7
Full Text
    1981:445868 CAPLUS
AN
DN
    95:45868
    Fuel oil additives
TI
    Toray Industries, Inc., Japan
PA
    Jpn. Kokai Tokkyo Koho, 3 pp.
SO
     CODEN: JKXXAF
DT
    Patent
LA
     Japanese
     C10L001-12; C10L001-18
IC
     51-9 (Fossil Fuels, Derivatives, and Related Products)
CC
FAN.CNT 1
                    KIND DATE
                                        APPLICATION NO. DATE
     PATENT NO.
     JP 56016593
PΙ
     Fuel oil additives contg. an Fe compd. and a C≥10 fatty
AB
     acid have an inhibiting effect on NOx formation during the combustion of
     fuel oil. Thus, an additive was prepd. by dilg. a mixt. contg.
     Fe(OH)O 2.36, stearic acid [57-11-4] 0.5, and fluid paraffin 5 kg with
     3.67 L kerosine. A heavy petroleum oil contg. 0.2 wt.% of the additive
     was burned; and the combustion gas formed contained 157 ppm NOx,
     compared to 198 ppm in the absence of the additive.
     fuel oil additive combustion improver; iron hydroxide oxide fuel
     additive; stearic acid fuel oil additive; nitrogen oxide emission
     control combustion
     Combustion
IΤ
        (of fuel oil, additive for nitrogen oxides
        emission control in)
     57-11-4, uses and miscellaneous
IT
```

```
RL: USES (Uses)
        (combustion improvers, contg. iron hydroxide oxide and stearic acid,
        for reduced nitrogen oxides formation)
     11104-93-1, uses and miscellaneous
TΤ
     RL: USES (Uses)
        (emission of, in fuel oil combustion,
        additives for prevention of)
     20344-49-4
IT
     RL: USES (Uses)
        (fuel oil additive compn. contg., for reduced
       nitrogen oxides formation during combustion)
     ANSWER 56 OF 56 CAPLUS COPYRIGHT 2002 ACS
L7
Full Text
     1973:434727 CAPLUS
AN
DN
     79:34727
     Effect of combustion on the thermal detoxication of gaseous emissions
TI
     Gurevich, N. A.
ΑU
     Inst. Gaza, Kiev, USSR
CS
     Khim. Tekhnol. (Kiev) (1973), (2), 46-50
SO
     CODEN: KHMTA6
DT
     Journal
     Russian
LΑ
     59-2 (Air Pollution and Industrial Hygiene)
CC
     The after burning of toxic emissions from the manuf. of synthetic
AB
     fatty acids, phthalic anhydride, drying oils, viscose fibers, and
     carbon black with the aid of natural gas, fuel oil, and coal was
     studied. The contribution of fuel combustion products to the toxicity
     of effluents, kind of fuel and its consumption, ratio of combustion
     products to gaseous emissions, specific air consumption, conditions and
     technol. process of after burning were taken into account in derivation
     of formulas, detg. the efficiency of thermal detoxication. The leading
     pollutants and toxicity factors (actual concn.-to-max. allowable concn.
     ratio were: (1) NOx, 8000-40,000; (2) SO2 + NO2, 20,000-60,000; (3)
     particulate matter + NO2 + SO2, 30,000-50,000 for combustion of natural
     gas, fuel oil, and coal, resp., where the lower limit corresponds to
     demands of hygienic standardization and the upper limit is based on
     phys.-chem. factors of synergistic action of combustion products. Thus,
     choice of fuel and technol. process affect substantially the efficiency
     of thermal detoxication of gaseous emissions. Detoxication efficiency
     may be increased considerably when using natural gas and decreasing its
     sp. consumption by rational use of reagents, heat, and by applying
     catalysts Coal and fuel oil are practically in applicable to thermal
     detoxication of effluents, for which toxicity factor lies below 50,000.
     The recommended method of detn. of total toxicity of atm. pollutants is
     intended exclusively for comparative evaluation of gaseous effluents.
     drying oil emission detoxication; thermal detoxication org vapor;
     viscose fiber emission detoxication; phthalic anhydride emission
     detoxication; fuel combustion emission detoxication; nitrogen oxide
     emission detoxication; combustion waste gas
IT
     RL: IMF (Industrial manufacture); PREP (Preparation)
        (drying, waste gas from manuf. of, thermal detoxication of)
IT
     Combustion
        (of waste gases, in afterburner, thermal detoxication in)
IT
     Waste gases
        (thermal detoxication of, in afterburner)
     Carbon black, preparation
IT
       Fatty acids, preparation
     Rayon, preparation
     RL: IMF (Industrial manufacture); PREP (Preparation)
         (waste gas from manuf. of, detoxication of, in afterburner)
```

```
TΤ
   Fuel oil
      Coal
```

Natural gas

RL: OCCU (Occurrence)

(waste gas thermal detoxication by, in afterburner)

7446-09-5, uses and miscellaneous 11104-93-1 RL: REM (Removal or disposal); PROC (Process) (removal of, from waste gas in afterburner)

TΤ 85-44-9P

RL: IMF (Industrial manufacture); PREP (Preparation) (waste gas from manuf. of, detoxication of, in afterburner)

=> file stnguide COST IN U.S. DOLLARS

TOTAL SINCE FILE ENTRY SESSION 172.25 172.04

FULL ESTIMATED COST

SINCE FILE TOTAL ENTRY SESSION

CA SUBSCRIBER PRICE

-34.69 -34.69

FILE 'STNGUIDE' ENTERED AT 17:42:55 ON 01 DEC 2002 USE IS SUBJECT TO THE TERMS OF YOUR CUSTOMER AGREEMENT COPYRIGHT (C) 2002 AMERICAN CHEMICAL SOCIETY, JAPAN SCIENCE AND TECHNOLOGY CORPORATION, AND FACHINFORMATIONSZENTRUM KARLSRUHE

FILE CONTAINS CURRENT INFORMATION. LAST RELOADED: Nov 29, 2002 (20021129/UP).

DISCOUNT AMOUNTS (FOR QUALIFYING ACCOUNTS)

=> d his

(FILE 'HOME' ENTERED AT 17:37:08 ON 01 DEC 2002)

FILE 'CAPLUS' ENTERED AT 17:37:39 ON 01 DEC 2002

273225 S FATTY ACID L1

837432 S FAT OR OIL L2 92558 S L1 AND L2 L3

0 S L3 AND (FUEL OE COAL) T.4

2364 S L3 AND (FUEL OR COAL) L5 342 S L5 AND (BURN? OR IGNIT? OR ENERGY) L6

56 S L6 AND EMISSION

FILE 'STNGUIDE' ENTERED AT 17:42:55 ON 01 DEC 2002

=> file caplus

COST IN U.S. DOLLARS SINCE FILE TOTAL ENTRY SESSION 1.86 174.11 FULL ESTIMATED COST

TOTAL SINCE FILE DISCOUNT AMOUNTS (FOR QUALIFYING ACCOUNTS) ENTRY SESSION

0.00 -34.69 CA SUBSCRIBER PRICE

FILE 'CAPLUS' ENTERED AT 18:01:31 ON 01 DEC 2002 USE IS SUBJECT TO THE TERMS OF YOUR STN CUSTOMER AGREEMENT. PLEASE SEE "HELP USAGETERMS" FOR DETAILS. COPYRIGHT (C) 2002 AMERICAN CHEMICAL SOCIETY (ACS)

Copyright of the articles to which records in this database refer is held by the publishers listed in the PUBLISHER (PB) field (available

for records published or updated in Chemical Abstracts after December 26, 1996), unless otherwise indicated in the original publications. The CA Lexicon is the copyrighted intellectual property of the American Chemical Society and is provided to assist you in searching databases on STN. Any dissemination, distribution, copying, or storing of this information, without the prior written consent of CAS, is strictly prohibited.

FILE COVERS 1907 - 1 Dec 2002 VOL 137 ISS 23 FILE LAST UPDATED: 29 Nov 2002 (20021129/ED)

This file contains CAS Registry Numbers for easy and accurate substance identification.

CAS roles have been modified effective December 16, 2001. Please check your SDI profiles to see if they need to be revised. For information on CAS roles, enter HELP ROLES at an arrow prompt or use the CAS Roles thesaurus (/RL field) in this file.

=> s 15 and byproduct

24054 BYPRODUCT

19941 BYPRODUCTS

39833 BYPRODUCT

(BYPRODUCT OR BYPRODUCTS)

L8 30 L5 AND BYPRODUCT

- => d l8 1-30 ti
- L8 ANSWER 1 OF 30 CAPLUS COPYRIGHT 2002 ACS
- TI Advances in biodiesel fuel research
- L8 ANSWER 2 OF 30 CAPLUS COPYRIGHT 2002 ACS
- TI Procedure and apparatus for the continuous production of bio-methanol and bio-ethanol diesel
- L8 ANSWER 3 OF 30 CAPLUS COPYRIGHT 2002 ACS
- TI Biodiesel fuel production by transesterification of oils
- L8 ANSWER 4 OF 30 CAPLUS COPYRIGHT 2002 ACS
- TI Organic compounding agent for powdered nitramon explosive
- L8 ANSWER 5 OF 30 CAPLUS COPYRIGHT 2002 ACS
- TI Non-TNT nitramon explosive for coal mine
- L8 ANSWER 6 OF 30 CAPLUS COPYRIGHT 2002 ACS
- TI Powdered ammonium nitrate-based explosives for quarry
- L8 ANSWER 7 OF 30 CAPLUS COPYRIGHT 2002 ACS
- TI Process for preparing feed supplements for ruminants
- L8 ANSWER 8 OF 30 CAPLUS COPYRIGHT 2002 ACS
- TI Process for preparing alkyl esters of fatty acids from fats and oils
- L8 ANSWER 9 OF 30 CAPLUS COPYRIGHT 2002 ACS
- TI Evaluation of method performance and detection limits for various flotation reagents used in the Florida phosphate industry
- L8 ANSWER 10 OF 30 CAPLUS COPYRIGHT 2002 ACS
- TI Optimization of enzymatic transesterification of rapeseed oil ester using response surface and principal component methodology
- L8 ANSWER 11 OF 30 CAPLUS COPYRIGHT 2002 ACS

- TI Biodiesel production: a review
- L8 ANSWER 12 OF 30 CAPLUS COPYRIGHT 2002 ACS
- TI Preparation of mixture of esters of C1-4 alcohols and fatty acids of natural oils and fats especially for use as diesel fuel or heating oil
- L8 ANSWER 13 OF 30 CAPLUS COPYRIGHT 2002 ACS
- TI Low temperature conversion of sugar-cane byproducts
- L8 ANSWER 14 OF 30 CAPLUS COPYRIGHT 2002 ACS
- TI Mixed vegetable and diesel oil as fuel
- L8 ANSWER 15 OF 30 CAPLUS COPYRIGHT 2002 ACS
- TI Refining method for waste edible oils as raw materials for recovery of diesel fuels, glycerin and substitute fuels for heavy-oil burners
- L8 ANSWER 16 OF 30 CAPLUS COPYRIGHT 2002 ACS
- TI Biodegradation of diesel and heating oil by Acinetobacter calcoaceticus MM5: its possible applications on bioremediation
- L8 ANSWER 17 OF 30 CAPLUS COPYRIGHT 2002 ACS
- TI Energy analysis of rape methyl ester (RME) production from winter oilseed rape
- L8 ANSWER 18 OF 30 CAPLUS COPYRIGHT 2002 ACS
- TI Production of diesel fuel from rape oil
- L8 ANSWER 19 OF 30 CAPLUS COPYRIGHT 2002 ACS
- TI Substitutes for sulfurized sperm oil from a mixture of natural and synthetic esters
- L8 ANSWER 20 OF 30 CAPLUS COPYRIGHT 2002 ACS
- TI Method for purifying fatty esters
- L8 ANSWER 21 OF 30 CAPLUS COPYRIGHT 2002 ACS
- TI The potential of biodiesel, from oilseed rape
- L8 ANSWER 22 OF 30 CAPLUS COPYRIGHT 2002 ACS
- TI Catalytic upgrading of biomass derivatives to transportation fuels
- L8 ANSWER 23 OF 30 CAPLUS COPYRIGHT 2002 ACS
- TI Emulsion fuel from heavy petroleum fractions
- L8 ANSWER 24 OF 30 CAPLUS COPYRIGHT 2002 ACS
- TI Conversion of high-acidity vegetable oils to ethyl esters in the presence of acid catalysts, for fuels
- L8 ANSWER 25 OF 30 CAPLUS COPYRIGHT 2002 ACS
- TI Ammonium nitrate-tall oil explosives
- L8 ANSWER 26 OF 30 CAPLUS COPYRIGHT 2002 ACS
- TI Principle of the new ATT process for converting vegetable **cils** to diesel **fuels**
- L8 ANSWER 27 OF 30 CAPLUS COPYRIGHT 2002 ACS
- TI Manufacture of uranium-containing heavy metal salts using sea water as raw material and producing pure water as byproduct
- L8 ANSWER 28 OF 30 CAPLUS COPYRIGHT 2002 ACS
- TI Extraction and transesterification of vegetable oils with ethanol
- L8 ANSWER 29 OF 30 CAPLUS COPYRIGHT 2002 ACS

- TI Continuous reactor with heterogeneous organic catalysts for transesterification of vegetable oils
- L8 ANSWER 30 OF 30 CAPLUS COPYRIGHT 2002 ACS
- TI Fuel oil additives

=> dl8 1 13 14 15 18 22 30 all

DL8 IS NOT A RECOGNIZED COMMAND

The previous command name entered was not recognized by the system. For a list of commands available to you in the current file, enter "HELP COMMANDS" at an arrow prompt (=>).

=> d 18 1 13 14 15 18 22 30 all

L8 ANSWER 1 OF 30 CAPLUS COPYRIGHT 2002 ACS

Full Text

- AN 2002:554404 CAPLUS
- DN 137:250109
- TI Advances in biodiesel fuel research
- AU Kann, Juri; Rang, Heino; Kriis, Juri
- CS Institute of Chemistry, Tallinn Technical University, Tallinn, 12618, Estonia
- SO Proceedings of the Estonian Academy of Sciences, Chemistry (2002), 51(2), 75-117
 - CODEN: PESCFO; ISSN: 1406-0124
- PB Estonian Academy Publishers
- DT Journal; General Review
- LA English
- CC 52-0 (Electrochemical, Radiational, and Thermal Energy Technology)
 Section cross-reference(s): 17
- AP Review of research on biodiesel fuel sources, properties, prepn.

 methods, prodn., exhaust gases emitted by using biodiesel fuel, anal.

 methods, and economic aspects. The main advantage of biodiesel fuel is
 lower concn. of greenhouse gases (esp. CO2) and other pollutants in motor
 exhaust gases compared to petroleum diesel fuel. The main concerns with
 biodiesel fuel are its relatively high price, instability, and low-temp.
 properties. The future aims in biodiesel fuel research are improvement
 of prodn. technol. and redn. of the costs of prodn. of plant oil by
 plant breeding, selection, and gene technol. The low-temp. properties and
 stability of biodiesel fuel can be improved by additives and genetic
 engineering of oil plants. The paper includes 250 refs.
- ST review biodiesel **fuel** transesterification **fatty acid** ester emission control
- IT Fats and Glyceridic oils, processes
 RL: CPS (Chemical process); PEP (Physical, engineering or chemical
 process); PROC (Process)

(as renewable raw materials for biodiesel; review of advances in biodiesel fuel research with regards to source oils and fatty acid distribution in triglycerides of fats and oils)

- IT Molecular structure-property relationship
 - (b.p., cetane no., viscosity, d., heats of combustion, iodine no., low temp. properties such as m.p., crystallite onset temp., pour and cloud point; review of phys. and chem. properties of diesel and various biodiesel esters)
- IT Diesel fuel substitutes

(biodiesel; review of advances in biodiesel **fuel** research with regards to source **oils**, additives, and processing)

IT Air pollution

(control, reduced pollutant emission using biodiesel; review of advances in biodiesel **fuel** research with regards to source

oils, additives, and processing)

IT Fatty acids, uses

RL: TEM (Technical or engineered material use); USES (Uses) (esters; review of advances in biodiesel **fuel** research with regards to source **oils**, additives, and processing)

IT Fatty acids, occurrence

RL: OCU (Occurrence, unclassified); OCCU (Occurrence) (fatty acid distribution in triglycerides of fats and oil used as renewable raw materials for biodiesel)

IT Diesel fuel additives

(for modification of viscosity, corrosion and lubrication properties, pour point and crystn., and polymn.-fouling; review of advances in biodiesel fuel research with regards to source oils, additives, and processing)

IT Genetic engineering

(manipulation of fatty acid distribution in triglycerides of oils for raw materials for biodiesel)

IT Wastes

(oil, as renewable raw materials for biodiesel; review of advances in biodiesel fuel research with regards to source oils, additives, and processing)

IT Transesterification

(processes, catalysts, and byproducts; review of advances in biodiesel fuel research with regards to source oils, additives, and processing)

IT Greenhouse gases

(reduced levels of; review of advances in biodiesel **fuel** research with regards to source **oils**, additives, and processing)

IT Exhaust gases (engine)

(review of advances in biodiesel **fuel** research with regards to source **oils**, additives, and processing)

RE.CNT 257 THERE ARE 257 CITED REFERENCES AVAILABLE FOR THIS RECORD

- (1) Aksoy, H; Fuel 1990, V69, P600 CAPLUS
- (2) Aksoy, H; J Am Oil Chem Soc 1988, V65, P936 CAPLUS
- (3) Ali, Y; J Am Oil Chem Soc 1995, V72, P1557 CAPLUS
- (4) Ali, Y; Liq Fuel Ind Prod Renewable Resour, Proc Liq Fuel Conf, 3rd 1996, P59 CAPLUS
- (5) Ali, Y; Soc Automot Eng 1997, SP-1247, P143
- (6) Allen, C; Fuel 1999, V78, P1319 CAPLUS
- (7) Allen, C; Liq Fuel Ind Prod Renewable Resour, Proc Liq Fuel Conf, 3rd 1996, P73 CAPLUS
- (8) Allen, H; US 2383579 1945 CAPLUS
- (9) Angelrot, D; FR 2763939 1998 CAPLUS
- (10) Auld, D; ASAE Publ 1982, 4-82, P92 CAPLUS
- (11) Bachler, A; AT 404137 1998 CAPLUS
- (12) Bagby, M; ACS Symp Ser 1996, V647, P248 CAPLUS
- (13) Bagley, S; Environ Sci Techn 1998, V32, P1183 CAPLUS
- (14) Bak, Y; Korean J Chem Eng 1996, V13(3), P242 CAPLUS
- (15) Basu, H; US 5525126 1996 CAPLUS
- (16) Batchelor, S; Ind Crops Prod 1995, V4(3), P193 CAPLUS
- (17) Bessee, G; Soc Automot Eng 1997, VSP-1274, P221 CAPLUS
- (18) Bhattacharyya, R; Fett/Lipid 1999, V101(10), P404
- (19) Billenstein, S; DE 3421217 1985 CAPLUS
- (20) Billenstein, S; EP 164643 B1 1989 CAPLUS
- (21) Bomke, M; EP 543356 1993 CAPLUS
- (22) Boocock, D; Proc Eur Biomass Conf, 8th, 1994 1995, V2, P1192 CAPLUS
- (23) Borgelt, S; Proc Altern Energy Conf 1994, P67 CAPLUS
- (24) Bradin, D; US 5578090 1996 CAPLUS
- (25) Bradshaw, G; US 2360844 1944 CAPLUS

- (26) Bunger, J; Mutat Res 1998, V415, P1
- (27) Chang, D; J Am Oil Chem Soc 1996, V73, P1549 CAPLUS
- (28) Chang, D; Soc Automot Eng 1997, VSP-1274, P153 CAPLUS
- (29) Choo, Y; Lipid Technology and Application 1997, P771 CAPLUS
- (30) Coteron, A; Res Devel in Oil Chem 1997, V1, P109 CAPLUS
- (31) Crookes, R; Energy Convers Mgm 1997, V38, P1785 CAPLUS
- (32) Cvengros, J; Bioresour Technol 1996, V55(2), P145 CAPLUS
- (33) Cvengros, J; Fett/Lipid 1999, V101(7), P261 CAPLUS
- (34) Cvengros, J; J Am Oil Chem Soc 1994, V71, P1349 CAPLUS
- (35) Cvengros, J; Pet Coal 1995, V37(2), P25 CAPLUS
- (36) Davies, B; EP 665873 B1 1996 CAPLUS
- (37) Davies, B; WO 94/10267 1996 CAPLUS
- (38) Demirbas, A; Fuel 1998, V77, P1117 CAPLUS
- (39) Demmering, G; DE 4040317 1992 CAPLUS
- (40) Demmering, G; EP 563070 1995 CAPLUS
- (41) Devitt, M; Int J Amb Energy 1993, V14(4), P195
- (42) Diasakou, M; Fuel 1998, V77, P1297 CAPLUS
- (43) Diesel, R; Die Entstehung des Dieselmotors 1913
- (44) Dimming, T; DE 19908978 2000 CAPLUS
- (45) Dimming, T; Freiberg Forschungsh A 1999, VA 852, P34
- (46) Domac, J; Naphtha 1998, V49(5), P159 CAPLUS
- (47) Dunn, R; J Am Oil Chem Soc 1999, V76, P109 CAPLUS
- (48) Dunn, R; Recent Res Dev Oil Chem 1997, 1, P31
- (49) Dunn, R; Trans ASAE 2000, V43, P1203 CAPLUS
- (50) Durbin, T; Environ Sci Technol 2000, V34, P349 CAPLUS
- (51) Eckl, P; Plant Oils as Fuels. Proc Symp, 1997 1998, P123 CAPLUS
- (52) Enchelmaier, H; DE 4238195 1994 CAPLUS
- (53) Encinar, J; Ind Eng Chem Res 1999, V38, P2927 CAPLUS
- (54) Ergun, N; WO 99/26913 CAPLUS
- (55) Fabisz, E; Przem Chem 1999, V78(5), P175 CAPLUS
- (56) Ferreira-Dias, S; Biomass, Proc Biomass Conf Am, 4th 1999, V1, P343 CAPLUS
- (57) Foglia, T; Proc World Conf Oilseed Edible Oils Process 1996 1998, V1, P121 CAPLUS
- (58) Foidl, N; WO 97/00234 CAPLUS
- (59) Foidl, N; Bioresour Technol 1996, V58(1), P77 CAPLUS
- (60) Fragioudakis, K; J Inst Energy 1998, V71(488), P126
- (61) Frauen, M; Plant Oils as Fuels. Proc Symp 1997 1998, P240 CAPLUS
- (62) Freedman, B; ASAE Publ 1982, 4-82, Pl17 CAPLUS
- (63) Freedman, B; J Am Oil Chem Soc 1984, V61, P1215 CAPLUS
- (64) Freedman, B; J Am Oil Chem Soc 1984, V61, P1638 CAPLUS
- (65) Freedman, B; J Am Oil Chem Soc 1986, V63, P1370 CAPLUS
- (66) Freedman, B; J Am Oil Chem Soc 1986, V63, P1375 CAPLUS
- (67) Gaskoks-Vertrieb, W; AU 387399 1989
- (68) Geller, D; Trans ASAE 1999, V42, P859 CAPLUS
- (69) Germani, M; DE 4324875 1994 CAPLUS
- (70) Ginosar, D; WO 00/05327 CAPLUS
- (71) Gomez Herrera, C; Grasas Aceites (Madrid) 1995, V46(2), P121 CAPLUS
- (72) Gong, J; Fuel 2001, V80, P437 CAPLUS
- (73) Goodrum, J; Bioresour Technol 1996, V56(1), P55 CAPLUS
- (74) Goodrum, J; Liq Fuel Ind Prod Renewable Resour, Proc Liq Fuel Conf, 3rd 1996, P128 CAPLUS
- (75) Graboski, M; Prog Energy Comb Sci 1998, V24(1), P125
- (76) Gutsche, B; Fett/Lipid 1997, V99(12), P418 CAPLUS
- (77) Haas, M; J Am Oil Chem Soc 1996, V73, P1498
- (78) Haller; Beilsteins Handbuch 1920, V2
- (79) Haller; Compt Rend 1906, V143, P805
- (80) Hamasaki, K; Kagoshima Daigaku Kogakubu Kenkyn Hokoku 1997, V39, P23 CAPLUS
- (81) Hanna, M; J Am Oil Chem Soc 1996, V73, P759 CAPLUS
- (82) Hanna, M; Recent Res Dev Oil Chem 1997, 1, P309
- (83) Harold, S; Lipid Techn 1997, V9(2), P33 CAPLUS
- (84) Harrington, K; Biomass 1986, V9(1), P1 CAPLUS

- (85) Harrington, K; J Am Oil Chem Soc 1985, V62, P1009 CAPLUS
- (86) Harwood, J; Biochim Biophys Acta 1996, V1301, P7 CAPLUS
- (87) Hassett, D; ASAE Publ 1982, 4-82, P127
- (88) Hayafuji, S; JP 10245586 1989 CAPLUS
- (89) Hillion, G; Lipids 1999, V6(5), P435 CAPLUS
- (90) Hock, O; AU 626014 1992 CAPLUS
- (91) Hofman, P; DE 3512497 1986 CAPLUS
- (92) Hofman, P; EP 198243 B1 1988 CAPLUS
- (93) Holcapek, M; J Chromatogr, A 1999, V858(1), P13 CAPLUS
- (94) Iwakura, K; JP 144172 2000 CAPLUS
- (95) Jackson, M; J Am Oil Chem Soc 1996, V73, P353 CAPLUS
- (96) Johanson, L; US 5520708 1996 CAPLUS
- (97) Junek, H; DE 3727981 1988 CAPLUS
- (98) Kaieda, M; J Biosci Bioeng 1999, V88, P627 CAPLUS
- (99) Kalayasiri, P; J Am Oil Chem Soc 1996, V73, P471 CAPLUS
- (100) Kara, J; Biomass Energy Environ, Proc Eur Bioenergy Conf, 9th 1996, V3, P1817 CAPLUS
- (101) Karaosmanoglu, F; Appl Biochem Biotechnol 1997, V61(3), P251
- (102) Karaosmanoglu, F; Energy Sources 1999, V21(3), P221 CAPLUS
- (103) Karman, D; Environ Res Forum 1997, V7-8, P139 CAPLUS
- (104) Karonis, D; Soc Automot Eng 1999, VSp-1461, P1 CAPLUS
- (105) Kikawa, H; JP 11228978 1999 CAPLUS
- (106) Kildiran, G; J Am Oil Chem Soc 1996, V73, P225 CAPLUS
- (107) Kincs, F; J Am Oil Chem Soc 1985, V62, P815 CAPLUS
- (108) Kirk-Othmer; Encyclopedia of Chemical Technology. Third edn 1978, V11
- (109) Kishida, M; JP 11236581 1999 CAPLUS
- (110) Klok, R; EP 391485 1993 CAPLUS
- (111) Klopfenstein, W; J Am Oil Chem Soc 1985, V62, P1029 CAPLUS
- (112) Knothe, G; ACS Symp Ser 1997, V660, P172
- (113) Knothe, G; J Am Oil Chem Soc 1998, V75(8), P1007 CAPLUS
- (114) Knothe, G; Proc Liq Fuel Conf, 3rd 1996, P54 CAPLUS
- (115) Komers, K; Fett/Lipid 1997, V99(2), P52 CAPLUS
- (116) Koncar, M; 2nd European Motor Biofuels Forum 1996, P171
- (117) Konig, J; Proc Int Conf Stab Handl Liq Fuels, 6th, 1997 1998, V2, P833
- (118) Korbitz, W; Plant Oils as Fuels. Proc Symp 1997 1998, P3
- (119) Korbitz, W; Renewable Energy 1999, V16, P1078 CAPLUS
- (120) Kordesch, V; 2nd European Motor Biofuels Forum 1996, P247 CAPLUS
- (121) Koseki, K; JP 09194859 1997 CAPLUS
- (122) Kossmehl, S; 2nd European Motor Biofuels Forum, Graz, Austria 1996, P217
- (123) Kotowski, W; Karbo 1999, V44(2), P69 CAPLUS
- (124) Krahl, J; Biomass Energy Environ, Proc Env Bioenergy Conf, 9th 1996, V3, P1657 CAPLUS
- (125) Krahl, J; Liq Fuel Ind Prod Renewable Resour, Proc Liq Fuel Conf, 3rd 1996, P149 CAPLUS
- (126) Krahl, J; Plant Oils as Fuels. Proc Symp, 1997 1998, P104 CAPLUS
- (127) Krahl, J; Soc Automot Eng 1996, SP-1208, P311
- (128) Kramaschke, V; EP 937767 1999 CAPLUS
- (129) Kricka, T; Naphtha 1999, V50(10), P337 CAPLUS
- (130) Krull, M; EP 931824 1999 CAPLUS
- (131) Krull, M; EP 931825 1999 CAPLUS
- (132) Kusdiana, D; Fuel 2001, V80, P693 CAPLUS
- (133) Kusy, P; ASAE Publ 1982, 4-82, P127 CAPLUS
- (134) Lal, K; US 5338471 1994 CAPLUS
- (135) Lal, K; EP 604125 1994 CAPLUS
- (136) Lechner, M; J High Resolut Chromatogr 1997, V20(11), P581 CAPLUS
- (137) Lee, I; J Am Oil Chem Soc 1995, V72, P1155 CAPLUS
- (138) Lee, I; J Am Oil Chem Soc 1996, V73, P631 CAPLUS
- (139) Leodolter, A; AT 398777 1995
- (140) Lepper, H; DE 3444893 1986 CAPLUS
- (141) Lewtas, K; EP 629231 B1 1999 CAPLUS
- (142) Lewtas, K; WO 93/18115 1999 CAPLUS
- (143) Lopez Sastre, J; Energia (Madrid) 1995, V21(5), P71 CAPLUS

- (144) Lozano, P; Fresenius' J Anal Chem 1996, V354, P319 CAPLUS
- (145) Ma, F; Biores Technol 1999, V70(1), P1 CAPLUS
- (146) Ma, F; Bioresour Technol 1999, V69(3), P289 CAPLUS
- (147) Ma, F; Ind Eng Chem Res 1998, V37, P3768 CAPLUS
- (148) Majerczak, V; GB 2331761 1999 CAPLUS
- (149) Mauderly, J; Plant Oils as Fuels. Proc Symp, 1997 1998, P92 CAPLUS
- (150) Mauguin, P; Biomass Energy Environ, Proc Eur Bioenergy Conf, 9th 1996, V2, P1435 CAPLUS
- (151) McDonald, J; Plant Oils as Fuels. Proc Symp 1997 1998, P141 CAPLUS
- (152) Mittelbach, M; AT 388743 B 1989 CAPLUS
- (153) Mittelbach, M; 2nd European Motor Biofuels Forum 1996, P183 CAPLUS
- (154) Mittelbach, M; Chromatographia 1996, V42(7/8), P431 CAPLUS
- (155) Mittelbach, M; Energ Agric 1985, V4(2), P207
- (156) Mittelbach, M; Energy Agric 1983, V2(4), P369 CAPLUS
- (157) Mittelbach, M; J Am Oil Chem Soc 1988, V65, P1185 CAPLUS
- (158) Mittelbach, M; J Am Oil Chem Soc 1990, V67, P168 CAPLUS
- (159) Mittelbach, M; J Am Oil Chem Soc 1999, V76, P545 CAPLUS
- (160) Muller, M; EP 406684 B1 1998 CAPLUS
- (161) Muniyappa, P; Bioresour Technol 1996, V56(1), P19 CAPLUS
- (162) Nimcevic, D; J Am Oil Chem Soc 2000, V77, P275 CAPLUS
- (163) Noureddini, H; US 6015440 2000 CAPLUS
- (164) Noureddini, H; US 6174501 2001 CAPLUS
- (165) Noureddini, H; J Am Chem Soc 1998, V75, P1775 CAPLUS
- (166) Nwafor, O; Appl Energy 1996, V54(4), P345 CAPLUS
- (167) Oberdorster, G; Plant Oils as Fuels. Proc Symp, 1997 1998, P89 CAPLUS
- (168) Oliveira, J; Ind Eng Chem Res 2000, V39, P4450 CAPLUS
- (169) Ozaktas, T; Energy Sources 1997, V19(2), P173 CAPLUS
- (170) Peterson, C; Biomass Bioenergy 1996, V10(5/6), P331 CAPLUS
- (171) Peterson, C; Biomass Bioenergy 1998, V14(2), P91 CAPLUS
- (172) Peterson, C; Trans ASAE 1983, V26, P1298
- (173) Peterson, C; Trans ASAE 1996, V39, P805 CAPLUS
- (174) Peterson, G; J Am Oil Chem Soc 1984, V61, P1593 CAPLUS
- (175) Poitrat, E; Proc Eur Biomass Conf, 8th, 1994 1995, V2, P1081 CAPLUS
- (176) Prankel, H; Biomass, Proc Biomass Conf Am, 4th 1999, V1, P805
- (177) Prankel, H; Liq Fuel Ind Prod Renewable Resour, Proc Liq Fuel Conf, 3rd 1996, P191
- (178) Pryde, E; ASAE Publ 1982, P101 CAPLUS
- (179) Purcell, D; J Am Oil Chem Soc 1996, V73, P381 CAPLUS
- (180) Radu, R; Soc Automot Eng 1997, SP-1298, P105
- (181) Radwan, M; Soc Automot Eng 1997, SP-1298, P61
- (182) Rahman, M; Lembaran Publ Lemigas 1995, V29(1), P33 CAPLUS
- (183) Rakow, G; Z Pflanzenzucht 1973, V69(1), P62
- (184) Rathbauer, J; Proc Eur Biomass Conf, 8th, 1994 1995, V2, P1174 CAPLUS
- (185) Reece, D; Liq Fuel Ind Prod Revewable Resour, Proc Liq Fuel Conf, 3rd 1996, P166 CAPLUS
- (186) Robbelen, G; Z Phlanzenzucht 1975, V75(2), P93
- (187) Rocco, V; ICE (Am Soc Mech Eng) Proc 17th Conf ASME 1995, 25, Pl
- (188) Roessler, P; ACS Symp Ser 1994, V566, P255 CAPLUS
- (189) Roine, P; Z Ernahrungswiss 1960, V1(1), P118
- (190) Romano, S; ASAE Publ 1982, 4-82, Pl06 CAPLUS
- (191) Ryan, T; ASAE Publ 1982, 4-82, P70 CAPLUS
- (192) Ryan, T; J Am Oil Chem Soc 1984, V61, P1610 CAPLUS
- (193) Saka, S; Fuel 2001, V80, P225 CAPLUS
- (194) Saka, S; Proc Biomass Conf Am 4th 1999, V1, P797 CAPLUS
- (195) Sams, T; 2nd European Motor Biofuels Forum 1996, P225 CAPLUS
- (196) Sams, T; Plant Oils as Fuels. Proc Symp 1997 1998, P64 CAPLUS
- (197) Samukawa, T; J Biosci Bioeng 2000, V90, P180 CAPLUS
- (198) Sankaran, V; US 4966876 1990 CAPLUS
- (199) Sasaki, T; EP 985654 2000 CAPLUS
- (200) Schafer, A; 2nd European Motor Biofuels Forum 1996, P233 CAPLUS
- (201) Schafer, A; Plant Oils as Fuels. Proc Symp 1997 1998, P29 CAPLUS
- (202) Schmidt, K; Soc Automot Eng 1996, VSP-1181, P113 CAPLUS

- (203) Schope, M; 2nd European Motor Biofuels Forum 1996, P311
- (204) Schwab, A; Fuel 1987, V66, P1372 CAPLUS
- (205) Serdari, A; Ind Eng Chem Res 1999, V38, P3543 CAPLUS
- (206) Serdari, A; J Propul Power 1999, V15(2), P224 CAPLUS
- (207) Shaheed, A; IMechE Conf Trans 1998, P287 CAPLUS
- (208) Shaw, J; Enzyme Microb Technol 1991, V13, P544 CAPLUS
- (209) Shimada, Y; WO 00/12743 CAPLUS
- (210) Shiro, S; JP 204392 2000 CAPLUS
- (211) Siler-Marinkovic, S; Hem Ind 1996, V50(7-8), P303 CAPLUS
- (212) Silver-Marinkovic, S; Fuel 1998, V77, P1389
- (213) Smith, M; US 2444486 1949
- (214) Someya, A; JP 09235573 1997 CAPLUS
- (215) Son, R; J Res 1999, V35(1/2), P67
- (216) Sourie, J; 2nd European Motor Biofuels Forum 1996, P305
- (217) Sovero, M; Plant Oils as Fuels. Proc Symp 1997 1998, P233 CAPLUS
- (218) Sprules, F; US 2366494 1945 CAPLUS
- (219) Srivastava, A; Renew Syst Energy Rev 2000, V4(2), P111 CAPLUS
- (220) Stalmach, F; CZ 283754 CAPLUS
- (221) Stavinoha, L; Soc Automot Eng 1999, SP-1482, P79
- (222) Stefanson, B; Can J Plant Sci 1964, V44, P359
- (223) Stern, R; EP 924185 1999 CAPLUS
- (224) Stumborg, M; Bioresour Technol 1996, V56(1), P13 CAPLUS
- (225) Stumborg, M; Proc Altern Energy Conf 1994, P157 CAPLUS
- (226) Sunderbrink, T; EP 716139 1996 CAPLUS
- (227) Suzuki, H; JP 07310090 1995 CAPLUS
- (228) Syassen, O; Plant Oils as Fuels. Proc Symp 1997 1998, P47 CAPLUS
- (229) Syldatk, C; DE 19838011 1999 CAPLUS
- (230) Tahir, A; ASAE Publ 1982, 4-82, P82 CAPLUS
- (231) Tanaka, Y; US 4303590 1981 CAPLUS
- (232) Tat, M; J Am Oil Chem Soc 1999, V76, P1511 CAPLUS
- (233) Tat, M; J Am Oil Chem Soc 2000, V77, P115 CAPLUS
- (234) Theil-Gangl, A; 2nd European Motor Biofuels Forum, Graz, Austria 1996, P273
- (235) Thompson, J; Liq Fuel Ind Prod Renewable Resour, Proc Liq Fuel Conf, 3rd 1996, P104 CAPLUS
- (236) Thompson, J; Trans ASAE 1998, V41, P931 CAPLUS
- (237) Trent, W; US 2383632 1945 CAPLUS
- (238) Uta, K; JP 11228977 1999 CAPLUS
- (239) Veermersh, G; 2nd European Motor Biofuels Forum 1996, P177
- (240) Vicente, G; Ind Crops Prod 1998, V8(1), P29 CAPLUS
- (241) Vukas, S; J Balk Tribol Assoc 1998, V4(3-4), P253 CAPLUS
- (242) Walker, K; 2nd European Motor Biofuels Forum 1996, P165 CAPLUS
- (243) Wang, W; Environ Sci Techn 2000, V34, P933 CAPLUS
- (244) Watanabe, Y; J Am Oil Chem Soc 2000, V77, P355 CAPLUS
- (245) Weiss-Schur, G; DE 4135294 1993 CAPLUS
- (246) Wenzel, G; J Agric Food Chem 1997, V45, P4748 CAPLUS
- (247) Williamson, A; Appl Energy 1998, V59(2-3), P187
- (248) Wimmer, T; WO 92/009268
- (249) Wimmer, T; WO 93/09212 CAPLUS
- (250) Wimmer, T; AT 394374 B 1992 CAPLUS
- (251) Wolf, G; DE 19904194 1999 CAPLUS
- (252) Womac, A; Proc Liq Fuel Conf, 3rd 1996, P177 CAPLUS
- (253) Wong, A; Proc Biomass Conf Am, 4th 1999, V1, P837 CAPLUS
- (254) Worgetter, M; Proc Biomass Conf Am 3rd 1997, V2, P1043 CAPLUS
- (255) Wu, W; J Am Oil Chem Soc 1998, V75, P1173 CAPLUS
- (256) Wu, W; J Am Oil Chem Soc 1999, V76, P517 CAPLUS
- (257) Zheng, D; Bioresour Technol 1996, V57(2), P137 CAPLUS
- L8 ANSWER 13 OF 30 CAPLUS COPYRIGHT 2002 ACS

Full Text

- AN 1998:593782 CAPLUS
- DN 129:191451

```
Low temperature conversion of sugar-cane byproducts
ΤI
    Lutz, Harald; Esuoso, Kayode; Kutubuddin, Mohamed; Bayer, Ernst
ΑU
    Institute of Organic Chemistry, University of Tubingen, D-72076, Germany
CS
    Biomass and Bioenergy (1998), 15(2), 155-162
so
    CODEN: BMSBEO; ISSN: 0961-9534
    Elsevier Science Ltd.
PB
DT
    Journal
LA
    English
    52-1 (Electrochemical, Radiational, and Thermal Energy Technology)
CC
    Section cross-reference(s): 49, 60
    This work reports the low temp. conversion (LTC) of the most important
AB
     sugar-cane byproducts, i.e., sugar-cane bagasse, filter mud, molasses
     and alc. sludge, into oil, char, reaction water and non-condensable
    gases. The oil was analyzed for fatty acids and hydrocarbons.
     Active carbon was produced from the char and was characterized
     subsequently. Filter mud gave the highest yield of LTC oil (20.6%),
     while other samples recorded yields lower than 6%. The heating values of
     the oils were between 24.5 kJ g-1 and 35.6 kJ g-1. Thermogravimetric
     studies of the LTC oil from filter mud indicated that 99% was vaporized
     at temps. below 450°. Varying concns. of C8-C30 hydrocarbons were
     detected in the oil. The distribution pattern of hydrocarbons, however,
     was unusual compared to typical oils from LTC. The yields of LTC chars
     were between 35.4% and 77.6%. These chars have been activated and the
     conditions were optimized. Active carbon from bagasse recorded a high
     iodine and methylene blue no. (1180 mg g-1 and 275 mg g-1, resp.). The
     BET surface is also very high (1035 m2 g-1) and consists of a large
     proportion of micro- and mesopores. Active carbons produced from the
     other samples however exhibited also fairly high iodine, methylene blue
     and BET values. These results are discussed comparatively and the
     potential of the wastes is outlined.
    sugarcane byproduct conversion fuel oil
    Hydrocarbons, preparation
     RL: SPN (Synthetic preparation); PREP (Preparation)
        (C8-C30; low temp. conversion of sugarcane byproducts)
TΤ
    Mud
        (filter mud; low temp. conversion of sugarcane byproducts)
IT
     Bagasse
     Calorific value
     Chars
     Sludges
     Sugarcane
        (low temp. conversion of sugarcane byproducts)
ΙT
     Alkanes, preparation
     Alkenes, preparation
     Hydrocarbon oils
     RL: SPN (Synthetic preparation); PREP (Preparation)
        (low temp. conversion of sugarcane byproducts)
TТ
     Molasses
        (sludge; low temp. conversion of sugarcane byproducts)
IT
     Fuel oil
       Fuel oil
        (synthetic, pyrolytic; low temp. conversion of sugarcane
        byproducts)
TΤ
     7440-44-0P, Carbon, preparation
     RL: SPN (Synthetic preparation); PREP (Preparation)
        (activated; low temp. conversion of sugarcane byproducts)
     64-17-5P, Ethanol, preparation
     RL: IMF (Industrial manufacture); PREP (Preparation)
        (sludge; low temp. conversion of sugarcane byproducts)
     ANSWER 14 OF 30 CAPLUS COPYRIGHT 2002 ACS
L8
Full Text
```

```
1997:635644 CAPLUS
AN
DN
    127:309420
    Mixed vegetable and diesel oil as fuel
ΤI
    Zubr, J.; Matzen, R.
ΑU
    Department of Agricultural Sciences, The Royal Veterinary and Agricultural
CS
    University, Frederiksberg, 1958, Den.
    Biomass for Energy and the Environment, Proceedings of the European
SO
     Bioenergy Conference, 9th, Copenhagen, June 24-27, 1996 (1996), Volume 3,
     1644-1653. Editor(s): Chartier, Philippe. Publisher: Elsevier, Oxford,
     UK.
     CODEN: 65BUA6
     Conference
DТ
    English
T.A
     52-1 (Electrochemical, Radiational, and Thermal Energy Technology)
CC
     Section cross-reference(s): 11
     Biofuel for diesel engines was introduced to the market in certain
AB
     European countries recently. Vegetable oil as raw material for the
     biofuel originates from oilseed crops grown on set-aside land with EC
     subsidies. Prodn. of the biofuel includes the conversion process of
     esterification, requiring special equipment and a considerable input in
     the form of additives, energy, and labor. Byproducts from
     esterification, e.g., glycerin and polluted water, are unavoidable. To
     minimize the prodn. expenses and to eliminate the byproducts, an
     alternative fuel was found in the form of a mixt. contg. diesel oil
     and crude vegetable oil. For this purpose a naturally pure vegetable
     oil was chosen from seeds of false flax Camelina sativa. At the present
     time, Camelina is not known as an agricultural crop in practice. However,
     the crop can be grown under different climatic conditions using a low
     input and environmentally friendly cultivation without application of
     pesticides. Camelina oil is characterized by a high content of unsatd.
     fatty acids (about 90%). Iodine no. of the oil is about 160. The
     mixed fuel was tested in a Farymann Diesel engine, run at const. optimum
     load of 4.00 kW with 3260 R/min. The engine was fueled with pure diesel
     oil and with two mixts. contg. camelina oil. Each fuel was tested
     by running the engine for 250 h. Specific consumption of pure diesel
     oil was 271.6 g/kWh. When running the engine on the mixed fuel with 5
     and 10% camelina oil, the specific consumption of fuel was 273.4 g/kWh
     and 277.1 g/kWh, resp. Carbon deposits on the piston and combustion
     chamber, and the amts. of soot in the exhaust gas, were similar for all
     tested fuels. Carbon deposits on the injection nozzle were slightly
     increased with increasing proportions of camelina oil in the mixed
     fuel. Independent of the fuel, after running for 250 h, the function
     of the injectors was still within the norm for ordinary performance.
     vegetable oil diesel oil fuel blend; camelina oil diesel oil
ST
     fuel blend; biofuel vegetable oil diesel oil blend; biodiesel
     camelina oil diesel oil blend
IT
     Fuels
        (alternative; mixed vegetable and diesel oil as fuel
        )
IT
     Fuels
        (biofuels; mixed vegetable and diesel oil as fuel)
IT
     Analytical numbers
        (iodine no.; mixed vegetable and diesel oil as fuel
     Calorific value
     Camelina sativa
     Cetane number
     Cloud point
     Coking
     Density
     Diesel engines
     Diesel fuel
```

```
Flash point
    Soot
    Viscosity
        (mixed vegetable and diesel oil as fuel)
IT
    Rape oil
    Soybean oil
    Sunflower oil
    RL: PRP (Properties)
        (mixed vegetable and diesel oil as fuel)
    Fats and Glyceridic oils, reactions
TΤ
    RL: PRP (Properties); RCT (Reactant); RACT (Reactant or reagent)
        (vegetable; mixed vegetable and diesel oil as fuel)
    7440-44-0, Carbon, formation (nonpreparative)
TΤ
    RL: FMU (Formation, unclassified); FORM (Formation, nonpreparative)
        (deposits; mixed vegetable and diesel oil as fuel)
    57-10-3, Palmitic acid, properties 57-11-4, Stearic acid, properties
IT
     60-33-3, Linoleic acid, properties 112-80-1, Oleic acid, properties
    112-86-7, Erucic acid 463-40-1, Linolenic acid 506-30-9, Arachidic
    acid 5561-99-9, Gondoic acid 25448-01-5, Eicosadienoic acid
     27070-56-0, Eicosatrienoic acid
    RL: PRP (Properties)
        (mixed vegetable and diesel oil as fuel)
    ANSWER 15 OF 30 CAPLUS COPYRIGHT 2002 ACS
L8
Full Text
    1997:614387 CAPLUS
AN
    127:265530
DN
    Refining method for waste edible oils as raw materials for recovery of
TI
    diesel fuels, glycerin and substitute fuels for heavy-oil burners
IN
     Someya, Akio
     Someya Shoten Y. K., Japan
PΑ
SO
     Jpn. Kokai Tokkyo Koho, 4 pp.
     CODEN: JKXXAF
DT
     Patent
     Japanese
LA
    ICM C10L001-02
IC
     ICS B01J027-02; C10L001-08; C11B013-00; C11C003-10; C07B061-00
     52-1 (Electrochemical, Radiational, and Thermal Energy Technology)
CC
     Section cross-reference(s): 17, 45, 60
FAN.CNT 1
                                         APPLICATION NO. DATE
                    KIND DATE
     PATENT NO.
     _____
                                          -----
    JP 09235573 A2 19970909
JP 3028282 B2 20000404
                                         JP 1996-67154 19960228
     The title method comprises heating waste edible oils in a caustic
     alkali-dissolved MeOH soln. for transesterification to sep. higher fatty
     acid Me esters as diesel fuels, neutralizing the byproducts to
     distn. recover MeOH and to sep. refined glycerin, esterifying the
     remainder of higher fatty acids with MeOH and H2SO4 catalyst,
     neutralizing the H2SO4 catalyst and water washing for removal, and
     obtaining higher fatty acid Me esters and fatty acids as
     heavy-oil burner substitute fuels.
     waste edible oil diesel fuel recovery; burner heavy oil substitute
     fuel; glycerin recovery waste edible oil fuel
     Fatty acids, uses
     RL: NUU (Other use, unclassified); PUR (Purification or recovery); PREP
     (Preparation); USES (Uses)
        (Me esters; refining method for waste edible oils as raw
        materials for recovery of diesel fuels, glycerin and
        substitute fuels for heavy-oil burners)
```

(cooking oil; refining method for waste edible oils

IT

93

as raw materials for recovery of diesel fuels, glycerin and substitute fuels for heavy-oil burners) TΤ Wastes (edible oils; refining method for waste edible oils as raw materials for recovery of diesel fuels, glycerin and substitute fuels for heavy-oil burners) Fuel oil IT (heavy, substitute; refining method for waste edible oils as raw materials for recovery of diesel fuels, glycerin and substitute fuels for heavy-oil burners) ΙT Burners (oil-fired; refining method for waste edible oils as raw materials for recovery of diesel fuels, glycerin and substitute fuels for heavy-oil burners) Diesel fuel IT (refining method for waste edible oils as raw materials for recovery of diesel fuels, glycerin and substitute fuels for heavy-oil burners) Fatty acids, uses IT RL: NUU (Other use, unclassified); PUR (Purification or recovery); PREP (Preparation); USES (Uses) (refining method for waste edible oils as raw materials for recovery of diesel fuels, glycerin and substitute fuels for heavy-oil burners) IT Fuel oil (substitutes; refining method for waste edible oils as raw materials for recovery of diesel fuels, glycerin and substitute fuels for heavy-oil burners) Fats and Glyceridic oils, uses RL: NUU (Other use, unclassified); PEP (Physical, engineering or chemical process); PROC (Process); USES (Uses) (vegetable, cooking oil wastes; refining method for waste edible oils as raw materials for recovery of diesel fuels, glycerin and substitute fuels for heavyoil burners) 56-81-5P, Glycerin, preparation TΤ RL: BYP (Byproduct); PREP (Preparation) (refining method for waste edible oils as raw materials for recovery of diesel fuels, glycerin and substitute fuels for heavy-oil burners) ANSWER 18 OF 30 CAPLUS COPYRIGHT 2002 ACS L8Full Text 1995:806351 CAPLUS AN 123:204328 DN Production of diesel fuel from rape oil TТ Skopal, Frantisek; Komers, Karel; Machek, Jaroslav TN Czech Rep. PA SO Czech Rep., 5 pp. CODEN: CZXXED DT Patent Czech LA C10L001-02; C10L001-18; C07C067-03; C11C003-04 IC 52-1 (Electrochemical, Radiational, and Thermal Energy Technology) CC

| Section cross-reference(s): 19 | | | | | |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|--------|-----------------|--------------------|------------------|
| FAN. CNT 1 | | | | | |
| The state of the s | | | | | |
| | PATENT NO. | KIND | DATE | APPLICATION NO. | DATE |
| | | | | | |
| ΡI | CZ 278914 | В6 | 19940817 | CZ 1992-2208 | 19920715 |
| | SK 277856 | В6 | 19950510 | SK 1992-2208 | 19920715 |
| PRAI | CZ 1992-2208 | | 19920715 | | |
| AB | Diesel fuel is p | roduce | d from rape oil | . by transesterifi | cation with MeOH |

in the presence of a KOH catalyst. H3PO4 10-50% mol. excess (KOH basis) is then added. After neutralization, unreacted MeOH is removed by vacuum evapn. at 666-1333 Pa or air bubbling at 20-50°, condensed, and recycled. The pptd. KH2PO4 is sepd. by filtration or centrifuging and used as a fertilizer. The liq. phase is sepd. to obtain an upper layer of the synthetic diesel fuel and a lower aq. glycol layer. diesel fuel manuf rape oil

ST

Fertilizers

RL: IMF (Industrial manufacture); PEP (Physical, engineering or chemical process); PREP (Preparation); PROC (Process)

(potassium dihydrogen phosphate byproduct from synthetic diesel fuel manuf.)

Rape oil

RL: PEP (Physical, engineering or chemical process); PROC (Process) (transesterification of rape oil with methanol in manuf. of diesel fuel)

Fatty acids, preparation

RL: IMF (Industrial manufacture); PREP (Preparation) (rape-oil, Me ester; as synthetic diesel fuel)

IT Fuels, diesel

(synthetic, prodn. of synthetic diesel fuel from rape oil)

1310-58-3, Potassium hydroxide, uses TΤ

RL: CAT (Catalyst use); USES (Uses)

(as catalyst in transesterification of rape oil in manuf. of synthetic diesel fuel)

7778-77-0P, Potassium phosphate (KH2PO4) ΙT

RL: IMF (Industrial manufacture); PEP (Physical, engineering or chemical process); PREP (Preparation); PROC (Process)

(byproduct from synthetic diesel fuel manuf. as fertilizer)

7664-38-2, Phosphoric acid, uses TT

RL: NUU (Other use, unclassified); USES (Uses)

(in transesterification of rape oil in manuf. of diesel fuel)

67-56-1, Methanol, reactions TТ

RL: RCT (Reactant); RACT (Reactant or reagent) (in transesterification of rape oil in manuf. of diesel fuel)

ANSWER 22 OF 30 CAPLUS COPYRIGHT 2002 ACS L8

<u>Full</u>

- 1993:653564 CAPLUS ΑN
- DN 119:253564
- Catalytic upgrading of biomass derivatives to transportation fuels ΤI
- Olson, Edwin S.; Sharma, Ramesh K. ΑU
- Universal Fuel Dev. Associates, Inc., Grand Forks, ND, 58201, USA CS
- Energy from Biomass and Wastes (1993), 16, 739-51 SO CODEN: EBWADU; ISSN: 0277-7851
- DTJournal
- LΑ
- 52-1 (Electrochemical, Radiational, and Thermal Energy Technology) CC Section cross-reference(s): 51
- Hydrocracking of biomass-derived materials for manuf. of transportation fuels was investigated under several conditions. Data on the conversion of fatty acids to high-quality gasoline products are presented. These studies serve as models for the use of waste oils and byproducts, e.g., tall acids, that could serve as inexpensive precursors for transportation fuels. Studies with Ni-substituted synthetic mica montmorillonite and its alumina-pillared form catalysts gave high yields of distillate in the gasoline range contg. high percentage of branched alkanes and low percentage of arom. hydrocarbons.

```
biomass deriv catalytic upgrading transportation fuel; gasoline
ST
     synthetic fatty acid conversion; mica montmorillonite catalyst biomass
     upgrading fuel
     Tall oil
TТ
     RL: USES (Uses)
        (catalytic upgrading of, to transportation fuels)
     Alkanes, preparation
IT
     Cycloalkanes
     RL: FORM (Formation, nonpreparative)
        (formation of, in catalytic upgrading of biomass derivs. to
        transportation fuels)
     Gasoline
TΤ
     RL: USES (Uses)
        (manuf. of, catalytic upgrading of biomass derivs. for)
     Catalysts and Catalysis
TT
        (synthetic mica montmorillonite, nickel-substituted, alumina-pillared,
        for upgrading of biomass derivs. to transportation fuels)
     Aromatic hydrocarbons, preparation
     RL: FORM (Formation, nonpreparative)
        (C6-8, formation of, in catalytic upgrading of biomass derivs. to
        transportation fuels)
ΙT
     Fuels
        (automotive, manuf. of, catalytic upgrading of biomass derivs. for)
     Aromatic hydrocarbons, preparation
IT
     RL: FORM (Formation, nonpreparative)
        (bicyclic, formation of, in catalytic upgrading of biomass derivs. to
        transportation fuels)
     Alkanes, preparation
TT
     RL: FORM (Formation, nonpreparative)
        (branched, formation of, in catalytic upgrading of biomass derivs. to
        transportation fuels)
     Mica-group minerals, compounds
     RL: USES (Uses)
        (interstratification compds., with montmorillonite, nickel-substituted,
        alumina-pillared, synthetic, catalysts, for upgrading of biomass
        derivs. to transportation fuels)
IT
     Wastes
        (oil, vegetable, catalytic upgrading of, to transportation
        fuels)
     Aromatic hydrocarbons, preparation
TΤ
     RL: FORM (Formation, nonpreparative)
        (tricyclic, formation of, in catalytic upgrading of biomass derivs. to
        transportation fuels)
     Fats and Glyceridic oils
IT
     RL: USES (Uses)
        (vegetable, waste, catalytic upgrading of, to transportation
        fuels)
     112-80-1, Oleic acid, uses
TΤ
     RL: USES (Uses)
        (catalytic upgrading of, to transportation fuels)
     1318-93-0D, Montmorillonite, interstratification compds. with mica,
     nickel-substituted, alumina-pillared
     RL: USES (Uses)
        (synthetic, catalysts, for upgrading of biomass derivs. to
        transportation fuels)
     ANSWER 30 OF 30 CAPLUS COPYRIGHT 2002 ACS
L8
Full Text
AN
     1967:413600 CAPLUS
DN
     67:13600
     Fuel oil additives
TI
     Basic Inc.
PA
```

```
SO
    Brit., 4 pp.
     CODEN: BRXXAA
DТ
    Patent
LA
   English
IC
   ClOL
CC 51 (Petroleum, Petroleum Derivatives, and Related Products)
FAN.CNT 1
                                          APPLICATION NO. DATE
                     KIND DATE
     PATENT NO.
     ______
                           19670308
PΤ
    GB 1061161
                           19630529
PRAI US
    Carboxylic acids are dispersants for metal-contg. corrosion inhibitors in
AΒ
     fuel oil concentrates. The dispersant may be a tall oil acid, a
     rosin acid, a hydrogenated rosin acid, an aromatic or alkylaromatic acid,
     a naphthenic acid or a fatty acid. Acid loadings of 0.5-15.0 wt.%
     enable concentrates to be prepd. contg. ≤84 wt. % solid inhibitor
     while maintaining stability and good pumping characteristics. These
     properties are due to the formation of a soap between the acid and the
     metal-contg. inhibitor and hence similar results can be obtained by adding
     the appropriate carboxylic acid salt. In an example, 300 g. Dolomite were
     added to 150 g. No. 2 fuel oil in a Waring blender to give a nonfluid
     paste contg. 66.7% solids. The addn. of 1 g. tallene (a byproduct
     recoverable from waste paper liquors which comprises a mixt. of fatty and
     rosin acids) converted the mix to an extremely fluid and pumpable
     dispersion. The method permits higher loadings of corrosion inhibitors in
     additive concentrates and reduces the unit power requirements of any
     operation, such as grinding, which may subsequently be carried out on the
     INHIBITORS CORROSION FUEL OILS; FUEL OILS CORROSION INHIBITORS;
     CORROSION INHIBITORS FUEL OILS; METAL CORROSION INHIBITORS CONTG;
     DISPERSANTS CORROSION INHIBITORS
     Acids, uses and miscellaneous
     RL: USES (Uses)
        (carboxylic, as dispersant for metal-contg. corrosion inhibitors for
        fuel oils)
IT
    Fuel oil, reactions
        (corrosion by, dispersants for inhibitors for, carboxylic acids)
     Acids, uses and miscellaneous
TT
     RL: USES (Uses)
        (metal-contg. corrosion inhibitor dispersant from carboxylic, for
        fuel oils)
IT
     Tallene
     RL: USES (Uses)
        (as dispersant for metal-contg. corrosion inhibitors in fuel
        oil)
     17069-72-6
TΤ
     RL: USES (Uses)
        (as fuel oil additive)
     1317-43-7
IT
     RL: USES (Uses)
        (calcined, as fuel oil additive)
=> ly
LY IS NOT A RECOGNIZED COMMAND
The previous command name entered was not recognized by the system.
For a list of commands available to you in the current file, enter
"HELP COMMANDS" at an arrow prompt (=>).
=> log y
                                                 SINCE FILE
                                                                 TOTAL
COST IN U.S. DOLLARS
```

ENTRY

SESSION

FULL ESTIMATED COST 35.27 209.38

DISCOUNT AMOUNTS (FOR QUALIFYING ACCOUNTS) SINCE FILE TOTAL

DISCOUNT AMOUNTS (FOR QUALIFYING ACCOUNTS)
SINCE FILE TOTAL
ENTRY SESSION
CA SUBSCRIBER PRICE
-4.34 -39.03

STN INTERNATIONAL LOGOFF AT 18:12:18 ON 01 DEC 2002